

Milestones/Deliverables

	Model Elements	SD	DD	CD	Constr. Coord.	Fabrication
s						
/stems						
Syst						
uilding						
Buil						
ш						

PARTICIPATING ORGANIZATIONS



The American
InstituteAGC of America
General CONTRACTORS OF AMERICA
Quality People. Quality Projects.





Copyright © 2017 BIM Forum







LOD Spec 2017 Part I

Version: 2017

November 2017

For Building Information Models

Nothing contained in this work shall be considered the rendering of legal advice. Readers are responsible for obtaining such advice from their own legal counsel. This work and any forms herein are intended solely for educational and informational purposes.

All images are intended to illustrate building conditions in compliance with common building codes. However, the images do not take into account site specific conditions, regional building codes and other important information that may require a material change for specific projects. These illustrations do not make representation for fitness for a particular project nor for code or design compliance.

Copyright © 2017 by BIMForum. All rights reserved

The LOD Specification Part I and Part II as well as the LOD Specification Guide are made available to the public without charge. In order to maintain the integrity and usefulness of these documents as a reference standard, certain restrictions apply to their use. These documents are licensed to the public under Creative Commons licenses as follows:

Part I of this work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License (http://creativecommons.org/licenses/by-nc-nd/4.0/).

Part II of this work is licensed under the Creative Commons Attribution-NonCommercial 4.0 International License (<u>http://creativecommons.org/licenses/by-nc/4.0/</u>).

The LOD Spec Guide is licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License (<u>http://creativecommons.org/licenses/by-nc-nd/4.0/</u>).

Licensing questions should be directed to LOD@BIMForum.org.

ACKNOWLEDGEMENTS

Many thanks to all the individuals and organizations who reviewed and contributed to this work, and to the following industry association representatives and co-chairs of the major discipline subgroups who made this document possible:

Overall Co-Chairs

Jan Reinhardt, Adept Project Delivery

Jim Bedrick, FAIA, AEC Process Engineering

Domain Co-Chairs

	Design	Construction
Structures	Will Ikerd, PE, LEED AP IKERD Consulting, LLC	David Merrifield Steel Fab, Inc.
Exterior Skin	James Vandezande, AIA HOK	Jon McFarland Wheaton Sprague
Interior Construction	Ron Dellaria, AIA, CSI Collaborative Construction Consultants	Brian Filkins The Beck Group
Conveying	Brian Skripac, Assoc. AIA, LEED AP BD+C Cannon Design	Ken Flannigan, LEED AP KONE
Building Services	Birgitta Foster VDCO Tech	David Francis Murray Company
Civil	Will Ikerd, PE, LEED AP IKERD Consulting, LLC	Gregg Madsen, RPLS Wier & Associates, Inc.
Bridge: Highway & Rail	Will Ikerd, PE, LEED AP IKERD Consulting, LLC	David Merrifield Steel Fab, Inc.
Legal	Carl G. Roberts, Law Offices of Carl G	. Roberts LLC

Industry Association Representatives

Dmitri Alferieff, Associated General Contractors

Michael Bomba, Esq., American Institute of Architects

Overall Editing and Graphics Creation

IKERD Consulting, LLC (IKERD.com) & BIMxD Solutions, LLC (BIMxD.com)

Additional Contributors

In addition, we'd like to thank the many contributors from all sectors of the industry who helped make this specification possible, including:

Andy Jizba, US CAD Benjamin Crosby, Yates Construction Bill Klorman, Klorman Construction & ACI 131 BIM Committee Member (Concrete) Brenda Ikerd, Ikerd Consulting, IKERD.com (Structures, Civil) Chuck Eastman, Ph.D, Georgia Institute of Technology David Merrifield, Steel Fab, Inc. Eloisa Amaya, Ikerd Consulting, IKERD.com (Graphics Editing, Structures, and Cover) Jamie L. Davis, PE. LEED AP, Ryan Biggs | Clark Davis Engineering & Surveying (Masonry) Jason P. Lien, PE, Precast Concrete Institute (PCI) BIM Committee, EnCon United (Precast) Jessica Butcher, Ikerd Consulting, IKERD.com (Graphics Editing, Structures, and Anchors) Joe Cipra, Vulcraft/Verco Group (Structural Steel Open Web Joists and Metal Deck) Joe Powell, EIT, Ikerd Consulting, IKERD.com (MEP) John Russo, AIA, President, US Institute of Building Documentation (Laser Scanning & Level Of Accuracy) Kirk Capristo, Astorino (Cover) Lee Garduno, Southland Industries (MEP) Luke Faulkner, LEED AP, AISC (Structural Steel) Matthew J. Gomez PE, SE, Gerdau (Structural Steel) Michael Bolduc, PE (MA), Simpson Gumpertz & Heger (Structural) Michael Gustafason, PE, Autodesk (Structural) Michael Mulder, Southland Industries (MEP) Murat Karakas, Arup (MEP) Natasha Wright, Ikerd Consulting, IKERD.com (Graphics Editing, Structures, and Anchors) Paul J. Hause, PE. Structural Consultants Inc. (Structural) Peter J. Carrato, Ph.D., PE, SE, Bechtel & ACI 131 BIM Committee Chair (Concrete) R. Wayne Muir, P.E., Structural Consultants Inc. & SEI-CASE BIM Committee Co-Chair (Structures) Rebecca Stanford, Ikerd Consulting, IKERD.com (Structures) Roger Becker, PE, SE, Precast Concrete Institute (PCI) Managing Director of Research and Development (Precast) Scott Babin, ITW Building Components Group (Wood) Soheil Seigali, Klorman Construction (Concrete) Steven Bumbalough, ITW Building Components Group (Wood)

EXECUTIVE SUMMARY

For a detailed guide on the use of this Specification see LOD Spec Guide.

The Level of Development (LOD) Specification is a reference tool intended to improve the quality of communication among users of Building Information Models (BIMs) about the characteristics of elements in models. The LOD Specification expands upon the LOD schema developed by the American Institute of Architects (AIA) for its *E202-2009 BIM and Digital Data Exhibit* and updated for the AIA's *G202-2013 Project BIM Protocol Form*¹ by providing definitions and illustrations of BIM elements of different building systems at different stages of their development and use in the design and construction process.

Building Information Modeling presents information about a construction project or structure in the form of three-dimensional graphical representations of elements (e.g., doors, beams, etc.), which can be further associated with information about other characteristics of those elements. It is possible for the graphical representation of an element, taken alone, to suggest that greater accuracy or intention can be attributed to the element than is in fact the case. The AIA's LOD Schema was developed to provide a more systematic way of conveying the extent of reliance that may be placed on an element. Many participants in the design and construction process felt, however, that the industry would benefit from a more detailed treatment of the AIA's brief narrative definitions.

Discussions within the BIMForum led to the creation of a multi-disciplinary task force to develop and maintain the *LOD Specification*. The *LOD Specification* is an organized collection of interpretations of the AIA's LOD definitions describing input and information requirements and providing graphical examples of the different levels of development of a broad variety of building element classes.

Users of the *LOD Specification* are cautioned that the it does not prescribe the necessary levels of development for different steps in the construction process. That determination is left to each project team. It is believed, however, that the availability of more precise definitions will reduce the risks of miscommunication among members of project teams when the expectations for different stages in the design and construction process are established, through easier identification of what each member of the team is expected to deliver and greater predictability of the level of effort that is required to create each member's deliverables.

The *LOD Specification* is organized by CSI Uniformat 2010^2 , with the subclasses expanded to Level 4 (and in a few cases to Level 5) to provide detail and clarity to the element definitions. The *LOD Specification* addresses only LOD 100 through LOD 400 of the AIA's LOD Schema, along with a new level – LOD 350 – which was added between LOD 300 and LOD 400 to better address the information levels required for effective trade coordination. The *LOD Specification* does not address LOD 500 since that LOD relates to field verification and is not an indication of progression to a higher level of geometry or information. See below for the Fundamental LOD Definitions.

The LOD Specification does not prescribe who the author of a particular component at a given LOD should be, as that will vary from one project to another. However, the document does provide a concise schematic means through the spreadsheet in Part II for a project team to identify model element authors, again in the interest of improving communication among model users. In addition, the LOD Specification task force has been working with software developers to provide a means within the software of tagging individual elements within a model with their current LOD level.

The LOD Specification is intended as a reference standard, but is also intended to evolve as the use of BIM develops. The Specification is updated annually, and previous versions are maintained on the BIMForum website (<u>www.bimforum.org/lod</u>). Users are invited to provide comments and recommendations for consideration in future editions. These should be sent by email to LOD@BIMForum.org.



¹ AIA Contract Document *G202-2013, Building Information Modeling Protocol Form* is part of a series of digital practice documents the AIA published in June 2013. This series consists of *AIA E203™–2013, Building Information Modeling and Digital Data Exhibit, AIA G201™–2013, Project Digital Data Protocol Form*, and *AIA G202™–2013, Project Building Information Modeling Protocol Form*. For general information on the documents and downloadable samples see <u>www.aia.org/digitaldocs</u>. For executable versions of the documents see <u>http://www.aia.org/contractdocs</u>.

² UniFormat[™] Numbers and Titles used in this publication are from UniFormat[™], published by CSI and Construction Specifications Canada (CSC), and are used with permission from CSI. For a more in-depth explanation of UniFormat[™] and its use in the construction industry visit <u>http://www.csinet.org</u> or contact CSI, 110 South Union Street, Suite 100, Alexandria, VA 22314. (800) 689-2900.

CONTENTS

EXECU	ITIVE SI	UMMARY	4
CHANG	GES FRO	OM 2016 VERSION	10
UPDAT	ES OF	THIS DOCUMENT	12
FUNDA	MENTA	L LOD DEFINITIONS	13
PART I	– ELEN	IENT GEOMETRY	15
N/A 36	-51 OFF	FICE RESOURCES	15
N/A	36-5	1 73 11 13 11 19 SPACES	15
N/A	36-5	1 73 11 13 17 11 Horizontal Grids	16
N/A	36-5	1 73 11 13 17 13 Vertical Levels	16
A 21-	-01 SUE	3STRUCTURE	18
A10	21-0	1 10 Foundations	
A1	010	21-01 10 10 Standard Foundations	
A1	020	21-01 10 20 Special Foundations	24
A20	21-0	1 20 Subgrade Enclosures	
A2	2010	21-01 20 10 Walls for Subgrade Enclosures	29
A40	21-0	1 40 Slabs-on-Grade	
A4	010	21-01 40 10 Standard Slabs-on-Grade	
A4	020	21-01 40 20 Structural Slabs-on-Grade	31
A4	030	21-01-40-30 Slab Trenches TBD	
A4	040	21-01-40-40 Pits and Bases TBD	
A4	090	21-01-40-90 Slab-On-Grade Supplementary Components TBD	
A60	21-0	1-60 Water and Gas Mitigation TBD	
A6	6010	21-01-60-10 Building Subdrainage TBD	
A6	6020	21-01-60-20 Off-Gassing Mitigation TBD	
A90	21-0	11-90 Substructure Related Activities TBD	
A9	010	21-01-90-10 Substructure Excavation TBD	
A9	020	21-01-90-20 Construction Dewatering TBD	
A9	030	21-01-90-30 Excavation Support TBD	
A9	040	21-01-90-40 Soil Treatment TBD	
B 21	-02 00 0	00 SHELL	
B10	21-0	2 10 Superstructure	
B1	010	21-02 10 10 Floor Construction	
B1	020	21-02 10 20 Roof Construction	56
B1	080	21-02 10 80 Stairs	
B20	21-0	2 20 Exterior Vertical Enclosures	64
B2	2010	21-02 20 10 Exterior Walls	65
B2	2020	21-02 20 20 Exterior Windows	78
B2	2050	21-02 20 50 Exterior Doors and Grilles	83
B2	2070	Exterior Louvers and Vents	
B30	21-0	2 30 Exterior Horizontal Enclosures	87

B3010	21-02 30 10 Roofing	
B3020	21-02 30 20 Roof Appurtenances	
B3040	21-02 30 40 Traffic Bearing Horizontal Enclosures	
B3060	21-02 30 60 Horizontal Openings	
B3080	21-02 30 80 Overhead Exterior Enclosures	
C 21-03 INT	reriors	
C10 21-	03 10 Interior Construction	
C1010	21-03 10 10 Interior Partitions	
C1020	21-03 10 20 Interior Windows	
C1030	21-03 10 30 Interior Doors	
C1040	21-03 10 40 Interior Grilles and Gates	
C1060	21-03 10 60 Raised Floor Construction	
C1070	21-03 10 70 Suspended Ceiling Construction	
C1090	21-03 10 90 Interior Specialties	
C20 21-	03 20 Interior Finishes	
C2010	21-03 20 10 Wall Finishes	
C2020	21-03 20 20 Interior Fabrications	
C2030	21-03 20 30 Flooring	
C2040	21-03 20 40 Stair Finishes	
C2050	21-03 20 50 Ceiling Finishes	
	00 SERVICES	
D10 21-	04 10 Conveying	
D1010	21-04 10 10 Vertical Conveying Systems	
D1030	21-04 10 30 Horizontal Conveying	
D1050	21-04 10 50 Material Handling	
D1080	21-04 10 80 Operable Access Systems	
D20 21-	04 20 Plumbing	
D2010	21-04 20 10 Domestic Water Distribution	
D2020	21-04 20 20 Sanitary Drainage	
D2030	21-04 20 30 Building Support Plumbing Systems	
D2050	21-04 20 50 General Service Compressed-Air	
D2060	21-04 20 60 Process Support Plumbing Systems	
	04 30 Heating, Ventilation, and Air Conditioning (HVAC)	
D3010	21-04 30 10 Facility Fuel Systems	
D3020	21-04 30 20 Heating Systems	
D3030	21-04 30 30 Cooling Systems	
D3050	21-04 30 50 Facility HVAC Distribution Systems	
D3060	21-04 30 60 Ventilation	
D3070	21-04 30 70 Special Purpose HVAC Systems	
	04 40 Fire Protection	
D4010	21-04 40 10 Fire Suppression	
D4030	21-04 40 30 Fire Protection Specialties	

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

D50 21	-04 50 Electrical	
D5010	21-04 50 10 Facility Power Generation	160
D5020	21-04 50 20 Electrical Service and Distribution	
D5030	21-04 50 30 General Purpose Electrical Power	
D5040	21-04 50 40 Lighting	167
D5080	21-04 50 80 Miscellaneous Electrical Systems	169
D60 21	-04 60 Communications	170
D6010	21-04 60 10 Data Communications	170
D6020	21-04 60 20 Voice Communications	170
D6030	21-04 60 30 Audio-Video Communication	171
D6060	21-04 60 60 Distributed Communications and Monitoring	171
D6090	21-04 60 90 Communications Supplementary Components	171
D70 21	-04 70 Electronic Safety and Security	171
D7010	21-04 70 10 Access Control and Intrusion Detection	171
D7030	21-04 70 30 Electronic Surveillance	171
D7050	21-04 70 50 Detection and Alarm	171
D7070	21-04 70 70 Electronic Monitoring and Control	171
D7090	21-04 70 90 Electronic Safety and Security Supplementary Components	172
D80 21	-04 80 Integrated Automation	172
D8010	21-04 80 10 Integrated Automation Facility Controls	172
E 21-05 00	00 EQUIPMENT & FURNISHINGS	173
E10 21	-05 10 Equipment	173
E1010	21-05 10 10 Vehicle and Pedestrian Equipment	173
E1030	21-05 10 30 Commercial Equipment	174
E1040	21-05 10 40 Institutional Equipment	176
E1060	21-05 10 60 Residential Equipment	177
E1070	21-05 10 70 Entertainment and Recreational Equipment	177
E1090	21-05 10 90 Other Equipment Associated Masterformat Sections: 11 90 00	178
E20 21	-05 20 Furnishings	178
E2010	21-05 20 10 Fixed Furnishings	179
E2050	21-05 20 50 Movable Furnishings	
F 21-06 00	00 SPECIAL CONSTRUCTION & DEMOLITION	
F10 21	-06 10 Special Construction	
F1010	21-06 10 10 Integrated Construction	
F1020	21-06 10 20 Special Structures Associated Masterformat Sections: 13 30 00 / 01 88 13	
F1030	21-06 10 30 Special Function Construction Associated Masterformat Sections:	190
F1050	21-06 10 50 Special Facility Components Associated Masterformat Sections:	
F1060	21-06 10 60 Athletic and Recreational Special Construction	
F1080	21-06 10 80 Special Instrumentation	191
F20 21	-06 20 Facility Remediation Associated Masterformat Sections:	191
F2010	21-06 20 10 Hazardous Materials Remediation	
F30 21	-06 30 Demolition	191

F3010	21-06 30 10 Structure Demolition	
F3030	21-06 30 30 Selective Demolition	
F3050	21-06 30 50 Structure Moving	
G10 21	-07 10 Site Preparation	191
G1010	21-07 10 10 Site Clearing	
G1020	21-07 10 20 Site Elements Demolition	
G1030	21-07 10 30 Site Element Relocations	
G1050	21-07 10 50 Site Remediation	
G1070	21-07 10 70 Site Earthwork	
G20 21	-07 20 Site Improvements	
G2010	21-07 20 10 Roadways	
G2020	21-07 20 20 Parking Lots	
G2030	21-07 20 30 Pedestrian Plazas and Walkways	
G2040	21-07 20 40 Airfields	
G2050	21-07 20 50 Athletic, Recreational, and Playfield Areas	
G2060	21-07 20 60 Site Development	
G2080	21-07 20 80 Landscaping	
G30 21	-07 30 Liquid and Gas Site Utilities	
G3010	21-07 30 10 Water Utilities	
G3020	21-07 30 20 Sanitary Sewerage Utilities	
G3030	21-07 30 30 Storm Drainage Utilities	
G3050	21-07 30 50 Site Energy Distribution	
G3060	21-07 30 60 Site Fuel Distribution	
G3090	21-07 30 90 Liquid and Gas Site Utilities Supplementary Components	
G40 21	-07 40 Electrical Site Improvements	
G4050	21-07 40 50 Site Lighting	
G50 21	-07 50 Site Communications	
G5010 –	- Site Communications Systems	
G90 21	-07 90 Miscellaneous Site Construction	200
G9010	21-07 90 10 Tunnels	
N/A 23-13 S	TRUCTURAL AND EXTERIOR ENCLOSURE PRODUCTS	
N/A 23	-13-23 Mechanical Fasteners, Adhesives, and Sealants	
N/A	23-13 23 11 Mechanical Fasteners – L-Bolt	
N/A	23-13 23 11 Mechanical Fasteners – J-Bolt	
N/A	23-13 23 11 Mechanical Fasteners – Hex Head Bolt with Washer	
N/A	23-13 23 11 Mechanical Fasteners – Welded Headed Stud Bolt	
	23-13 23 11 Mechanical Fasteners – Adhesive Anchor	
N/A	23-13 23 11 Mechanical Fasteners – Undercut Anchor	210
N/A	23-13 23 11 Mechanical Fasteners – Torque-controlled Expansion Anchor (Sleeve Type)	212
N/A	23-13 23 11 Mechanical Fasteners – Torque-controlled Expansion Anchor (Stud Type)	214
N/A	23-13 23 11 Mechanical Fasteners – Drop-in Type Displacement-Controlled Expansion Anchor	216
N/A 23	-13 31 Structural Concrete Products	218

	N/A	23-13 31 17 Formwork– Concrete Column	.218
	N/A	23-13 31 17 Formwork- Concrete Slab	. 220
CI	VIL		. 222
	Highway B	Bridges Precast Structural I Girder (Concrete)	. 222
	Highway B	Bridge Girder Steel	. 225
	Railroad B	ridges Precast Structural I Girder (Concrete)	. 226
	Railroad B	ridge Girder Steel	. 228

CHANGES FROM 2016 VERSION

Note – Changes in the Element Geometry section are indicated with a change bar in the left margin. Items such as grammar corrections, added Uniformat descriptions, added Masterformat references, added or upgraded graphics, minor corrections/additions, etc. are marked with a bar but not detailed in this section.

General notes

Non-Graphic Information

All calls for non-graphic information have been deleted from Part I and addressed in Part II

"No-fly zones"

Where zones that are not to be penetrated by other elements are required by code, operational, or structural considerations (door swings, electrical panel access clearance, foundation element areas or bearing influence, etc.), an item has been added to LOD 300 definitions calling for the zones to be either modeled to facilitate clash detection or accommodated by model-checking software.

Opening Elements (doors, windows, etc.)

Existing LOD 350 calls for modeling of rough opening deleted, moved to definitions of walls, floors, and roofs.

Openings and Penetrations and Similar Elements

LOD 300 definitions have been adjusted to call for major openings such as windows, doors, and large mechanical elements to be modeled to nominal dimensions.

LOD 350 definitions have been adjusted to call for all penetrations to be modeled to rough opening dimensions.

Where elements such as MEP distribution components penetrate other elements such as walls, the existing LOD 350 calls for modeling of the penetration element itself (e.g. a sleeve) have been clarified.

Specific Changes

Introduction		The Introduction has been removed and provided in a separate document – <i>LOD Spec 2017 Guide.</i> This Document also includes white papers on use of the spec.	
Executive Summary		Added	
Fundamental LOD Call for element location added Definitions – LOD 300		Call for element location added	
Uniformat	Omniclass		
N/A	36-51 73 11 13 11 19	Spaces – Added	
N/A	36-51 73 11 13 17 11	Horizontal Grids – Added	
N/A	36-51 73 11 13 17 13	Vertical Levels - Added	
A10	21-01 10	Foundations – LOD 200. Provision for location added	
A1020.10.10	21-01 10 20 20	Helical Piles and Piers – Added	
A4010	21-01 40 10	 Standard Slabs-on-Grade LOD 300. Provision for openings added LOD 400. Provision for fully modeled rebar added 	

B1020	21-02 10 20	Roof Construction – logic clarification added:
		 If modeling roof as a single composite element including structure use B1020
		 If modeling individual layers as separate elements use: B1020.10 Roof Structural Frame
		 B1020.20 Roof Decks, Slabs, and Sheathing
B1020.20	21-02 10 20 20	Roof Decks, Slabs, and Sheathing – Detail added
B1080.70	21-02 10 80 70	Metal Walkways – Detail added
B2010	21-02 20 10	Exterior Walls – logic clarification added:
		 If modeling wall as a single composite element use B2010 If modeling individual layers as separate elements use: B2010.10 Exterior Wall Veneer B2010.20 Exterior Wall Construction B2010.30 Exterior Wall Interior Skin
B2010	21-02 20 10	Exterior Walls – LOD 350. Requirement for hosted objects to be at LOD 350 deleted.
B2010.20.10	21-02 20 10 10	Exterior Wall Construction (Wood) – Previously B2010
B2010.20.20	21-02 20 10 20	Exterior Wall Construction (Cold-Form Metal Framoing) – Previously B2010
B2010.20.30	21-02 20 10 20 30	Exterior Wall Construction (Masonry) – Previously B2010
B2010.20.40	21-02 20 10 20 40	Exterior Wall Construction (Concrete) – Previously B2010
B2010.30	21-02 20 10 30	Exterior Wall Interior Skin
		 LOD 100 – Changed to N/A
		LOD 200 – Detail added
		LOD 300 – Detail added
B2020.30	21-02 20 20 30	Exterior Window Wall – LOD 300. "Structural support systems of wall to be modeled" deleted – addressed in wall element definitions
B3010	21-02 30 10	Roofing – Detail added
D1010.10	21-04 10 10 10	Elevators – Added detail
G1070.10	21-07 10 70 10	Grading – Added
N/A	23-13 23 11	Mechanical Fasteners – Added
N/A	23-13 31 17	Formwork - Added

UPDATES OF THIS DOCUMENT

While this document is intended as a reference that can be cited in agreements such as contracts and BIM execution plans, it is recognized that the use of BIM in design and construction is evolving. To accommodate this evolution this document will be updated periodically in clearly identifiable versions. A project can adopt a specific version and then has the option to remain with that version or update if a new version is published. Initially the target update frequency is annually, but that may change in the future. In addition, interim updates may be issued if needed.

Revision History

11/07/17	Level of Development Specification 2017	
08/25/17	Level of Development Specification 2017	
	DRAFT FOR PUBLIC COMMENT	
10/17/16	Level of Development Specification 2016	
08/25/16	Level of Development Specification 2016	Definitions have not been changed except for minor
	DRAFT FOR PUBLIC COMMENT	grammatical corrections and formatting. Engineered metal building structures, precast concrete, highway and rail road bridge content moved from Appendix to main body.
10/30/15	Level of Development Specification 2015	Definitions have not been changed except for minor grammatical corrections and formatting. New content released as an Appendix to Part A for engineered metal building structures, precast concrete, highway bridge content and rail road bridge content.
4/30/15	Level of Development Specification 2015	Definitions have not been changed except for minor
	DRAFT FOR PUBLIC COMMENT	grammatical corrections and formatting. Part B, Model Element Table, and Attribute Tables were added.
12/30/14	Level of Development Specification 2014	Definitions have not been changed except for minor grammatical corrections and formatting. Images and image notes have been added in <i>blue italics font</i> .
8/22/13	Level of Development Specification 2013	
4/24/13	Initial draft for public review	

Revision Process

Public Comment

Each new version is first released as a draft for public comment. Feedback is evaluated and resolved prior to the publishing of the official version.

Appendix

An increasing number of professional organizations are adopting this Specification and providing additional content relating to their domains. To accommodate information that becomes available after the public-comment release but prior to the final release, content is developed in collaboration with industry organizations and leading expert practitioners, and then vetted by the LOD working group. This content is released as an Appendix to Part A and as additional identified Attribute Table tabs in Part B. The new content is then integrated into the next public comment draft.

FUNDAMENTAL LOD DEFINITIONS³

LOD 100

The Model Element may be graphically represented in the Model with a symbol or other generic representation, but does not satisfy the requirements for LOD 200. Information related to the Model Element (i.e. cost per square foot, tonnage of HVAC, etc.) can be derived from other Model Elements.

BIMForum Interpretation: LOD 100 elements are not geometric representations. Examples are information attached to other model elements or symbols showing the existence of a component but not its shape, size, or precise location. Any information derived from LOD 100 elements must be considered approximate.

LOD 200

The Model Element is graphically represented within the Model as a generic system, object, or assembly with approximate quantities, size, shape, location, and orientation. Non-graphic information may also be attached to the Model Element.

<u>BIMForum interpretation</u>: At this LOD elements are generic placeholders. They may be recognizable as the components they represent, or they may be volumes for space reservation. Any information derived from LOD 200 elements must be considered approximate.

LOD 300

The Model Element is graphically represented within the Model as a specific system, object or assembly in terms of quantity, size, shape, location, and orientation. Non-graphic information may also be attached to the Model Element.

<u>BIMForum interpretation</u>: The quantity, size, shape, location, and orientation of the element as designed can be measured directly from the model without referring to non-modeled information such as notes or dimension call-outs. The project origin is defined and the element is located accurately with respect to the project origin.

LOD 350

The Model Element is graphically represented within the Model as a specific system, object, or assembly in terms of quantity, size, shape, location, orientation, and interfaces with other building systems. Non-graphic information may also be attached to the Model Element.

<u>BIMForum interpretation</u>. Parts necessary for coordination of the element with nearby or attached elements are modeled. These parts will include such items as supports and connections. The quantity, size, shape, location, and orientation of the element as designed can be measured directly from the model without referring to non-modeled information such as notes or dimension call-outs.

LOD 400

The Model Element is graphically represented within the Model as a specific system, object or assembly in terms of size, shape, location, quantity, and orientation with detailing, fabrication, assembly, and installation information. Non-graphic information may also be attached to the Model Element.

<u>BIMForum interpretation.</u> An LOD 400 element is modeled at sufficient detail and accuracy for fabrication of the represented component. The quantity, size, shape, location, and orientation of the element as designed can be measured directly from the model without referring to non-modeled information such as notes or dimension call-outs.



³ The definitions for LOD 100, 200, 300, 400, and 500 included in this Specification represent the updated language that appears in the AIA's most recent BIM protocol document, *G202–2013, Building Information Modeling Protocol Form.* The LOD 100, 200, 300, 400 and 500 definitions are produced by the AIA and have been used by permission. Copyright © 2013. The American Institute of Architects. All rights reserved. LOD 350 was developed by the BIMForum working group. Copyright © 2013. The BIMForum and the American Institute of Architects. All rights reserved.

LOD 500

The Model Element is a field verified representation in terms of size, shape, location, quantity, and orientation. Non-graphic information may also be attached to the Model Elements.

<u>BIMForum interpretation</u>. Since LOD 500 relates to field verification and is not an indication of progression to a higher level of model element geometry or non-graphic information, this Specification does not define or illustrate it.

Example – Light Fixture:

- 1) 100 cost/sf attached to floor slabs
- 2) 200 light fixture, generic/approximate size/shape/location
- 3) 300 Design specified 2x4 troffer, specific size/shape/location
- 4) 350 Actual model, Lightolier DPA2G12LS232, specific size/shape/location
- 5) 400 As 350, plus special mounting details, as in a decorative soffit

PART I – ELEMENT GEOMETRY

N/A

36-51

OFFICE RESOURCES

N/A

36-51 73 11 13 11 19 **SPACES**

Associated Masterformat Sections: N/A

100	 Spaces are modeled as generic objects with approximate size, shape and location. This level is typically appropriate for design of spatial requirements where space objects are placed in a model either in a random manner for quantification or in a 'blocking and stacking' process. Bounding elements are not required, but may be needed if specific dimensions are desired. Element modeling to include: Space object based on area required by program or brief. 	From http://revitaddons.blogspot.com/2014/02/free-space- planning-massing-from-excel.html
200	 Spaces are modeled or placed with bounding elements such as walls and columns that are at a minimum of LOD200. Perimeter and area of spaces are calculated with respect to the bounding elements. LOD of spaces shall not exceed the LOD of the bounding elements. For example, if interior partitions are defined at LOD200, the space objects for the project cannot be delivered at LOD300. Element modeling to include: Vertical bounding elements at LOD200 Space objects that automatically associate with vertical 	From http://cad-3d.blogspot.com/2012/06/improve-usage-
	 Space objects that automatically associate with vertical bounding elements 	of-bim-during-early.html
300	Spaces are modeled or placed with bounding elements that are at a minimum of LOD300. Perimeter and area of spaces are calculated with respect to the bounding elements. Element modeling to include:	

Horizontal Grids

Vertical Levels

Uniformat Omniclass

	 Vertical bounding elements at LOD300 Space objects that automatically associate with vertical bounding elements 	
350	Comply with the LOD300 requirements.	
	Volume of the space is accurately calculated to the nearest horizontal finish surface such as a ceiling or underside of slab above.	
	Element modeling to include:	
	 Vertical bounding elements to minimum LOD300 Horizontal bounding elements such as ceilings or slabs Space objects that automatically associate with vertical and horizontal bounding elements 	


N/A N/A

36-51 73 11 13 17 11 36-51 73 11 13 17 13

Includes: Grids and elevations used to coordinate and annotate models.

100 Grids & Elevations 200 A-1 ZZ Equipment, Building, Campus, Civil, and GIS is approximate in ELEV-2 its relation to the content in the given model. PROX Z-global 2-2-Ð 0 Ì E LOD 200 Grids & Elevations

Back to TOC





Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

21-01 SUBSTRUCTURE

Associated Masterformat Sections: 01 82 00

Foundations

Associated Masterformat Sections: 01 82 13

21-01 10

100	Assumptions for foundations are included in other modeled elements such as an architectural floor element or volumetric mass that contains layer for assumed structural framing depth.	
	Or, schematic elements that are not distinguishable by type or material. Assembly depth/thickness and locations still flexible.	
200	Element modeling to include:	
	 Approximate size and shape of foundation element Structural building grids for local project coordinate system are defined in model and approximately coordinated with civil coordinate . 	

A1010

Α

A10

21-01 10 10

Standard Foundations

Includes: Formwork, concrete, masonry and reinforcement. Includes Standard Foundation Supplementary Components as appropriate. May Include: Related Activities: Excavation, dewatering, excavation support systems, backfill and compaction, and soil treatment.

Note - for formwork see Structural Concrete Products

Associated Masterformat Sections: 01 82 13

100	See <u>A10</u>
200	See <u>A10</u>
300	Elements are modeled to the design-specified size and shape of the foundation.
	Element modeling to include:
	 Overall size and geometry of the foundation element Sloping surfaces or floor depressions External dimensions of the members Main openings such as elevators and other shafts

A1010.10 21-01 10 10 10 Wall Foundations (Shallow Foundations)

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 04 20 00 / 06 14 00

100	See A10	
200	 See A10 Image Notes: Generic wall foundation is modeled. Site is generically modeled from geotechnical information in geotechnical report. 	1 A1010.10-LOD-200 Wall Foundation
300	 Element modeling to include: Overall size and geometry of the foundation element Sloping surfaces. External dimensions of the members Geotechnical bearing strata elevation is modeled from geotechnical report. Area of bearing influence – modeled or accommodated by model checking software Image Notes: Wall foundation sizes are accurately modeled with footings where applicable. Bearing elevation is modeled from the geotechnical report. Geotechnical regions are shown for context and not required to be modeled as part of this element at this LOD. 	2 A1010.10-LOD-300 Wall Foundation
	9) See slab on grade for related conditions at this LOD.	

350	Element modeling to include:	
	 Location of sleeve penetrations Pour joints Chamfer Moisture retarder Dowels All exposed embeds or reinforcement such as lintels Expansion joints Geotechnical Bearing Strata is modeled from geotechnical report estimates. 	
	Image Notes:	
	9) Grade beam sizes are modeled with interfaces to other systems such as but not limited to slab turn downs, key-ways between concrete pours, construction joints and reinforcing dowels into adjacent pours.	
	10) Bearing elevation is modeled from the geotechnical report with the addition on interface elements such as void boxes where applicable.	3
	11) Geotechnical regions are shown for context and not required to be modeled as part of this element at this LOD.	3 A1010.10-LOD-350 Wall Foundations (Shallow Foundations)
	12) See slab on grade for related conditions at this LOD.	
400	Element modeling to include:	
	 Rebar including hooks and lap splices Dowels Coursing for unit masonry defined Waterproofing 	

A1010.30 21-0

21-01 10 10 30

Column Foundations (Deep Foundations)

Associated Masterformat Sections: 03 30 00

100	See <u>A10</u>	
200	See <u>A10</u>	

200 EL . dalir to include


300	Elemen	t modeling to include:	
	1) 2) 3) 4)	Assumed bearing depth per geotechnical report with designed penetration geometry modeled. Top of Pier Size of Pier Area of bearing influence - modeled or accommodated by model checking software	
	Image 1	Notes:	
	5)	Pier sizes are accurately modeled with top of pier elevation, estimated depth to bearing and specified depth of penetration into bearing strata.	
	6)	specified depth of penetration into bearing strata. Geotechnical regions are shown for context and not required to be modeled as part of this element at this LOD.	A 1010.30-LOD-300 Column Foundations (Deep foundations)

350 Element modeling to include:

- Actual Top of Pier (TOP) and expected Bottom of Pier (BOT) modeled per engineer's review of site conditions
- Foundation dowel locations and anchor rods if applicable.

Image Notes:

- Pier sizes are accurately modeled with interfaces to other systems such as but not limited to slab turn downs, key-ways between concrete pours, construction joints and reinforcing dowels into adjacent pours.
- Geotechnical regions are shown for context and not required to be modeled as part of this element at this LOD.



400	Element modeling to include:	
+00	 Depth to bearing stratum Penetration into bearing stratum Locations of lap splices Rebar including hooks and lap splices Dowels Pier sled or Pier wheel for side clear cover Pier bolster for bottom clear cover 	
	Image Notes:	
	• Pier modeling is developed to include all fabrication content that is part of the element.	
	• Geotechnical regions are shown for context and not required to be modeled as part of this element at this LOD.	
	 Pier sled, pier wheel, pier bolsters and other related items are not shown in image for clarity. 	<image/> <image/> <image/>



Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

A1010.90 21-01 10 10 90

Standard Foundation Supplementary Components TBD

A1020

21-01 10 20

Special Foundations

Includes: Drilling, casing, bell bottom, excavation, dewatering, removal of excavated, materials, reinforcing, and concrete. Drilled Piers, Driven Piles, Mat Foundation, elevator pits.

Associated Masterformat Sections: 31 60 00

100	See <u>A10</u>	
200	See <u>A10</u>	
300	 See <u>A1010</u> 1) <u>Elevator pit slabs are sloped correctly</u> 2) Sump pits are shown at correct locations and geometries 	
350	 Element modeling to include: Location and size of sleeve penetrations and MEP openings Chamfer Pour joints Dowels All elements needed for cross-trade collaboration are to be modeled Actual location and shape of structural element Exposed embeds or reinforcement such as lintels Penetrations detailed and modeled Expansion joints 	
400	 Element modeling to include: Rebar detailing including hooks and lap splices Dowels Moisture retarder Coursing for unit masonry defined Waterproofing 	

A1020.10 21-01 10 20 20 Includes: Piles, pile driving, pile cut off, pile testing. Driven Piles

TBD

Back to TOC

A1020.10.10 21-01 10 20 20 Associated Masterformat Sections: N/A Helical Piles, Helical Piers

100	See <u>A10</u>	
200	See <u>A10</u> Helical Pile	
		A1020.10.10 LOD 200 Helical Piers
300	 Element modeling to include: Pile system type Pile material Coating Influence area modeled or accommodated by model checking software 	
		A1020.10.10 LOD 300 Helical Piers

	350	Element modeling to include: Spacing Plate Size Bearing Strata 			
				A1020.10.10 LOD 350 Helical Piers	
	400	Element modeling to include: • Full fabrication connect	ctions		
		04.04.40.00.00		A1020.10.10 LOD 400 Helical Piers	
	020.20 020.30	21-01 10 20 20 21-01 10 20 30	Caisso Specia	ns I Foundation Walls	TBD TBD
A1	A1020.40 21-01 10 20 40 Founda		ation Anchors	TBD	
A1	020.50	21-01 10 20 50	Underp	binning	TBD

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

Uniformat	Omniclass		
A1020.60	21-01 10 20 60	Raft Foundations	TBD
A1020.70	21-01 10 20 70	Pile Caps	TBD

A1020.80 21-01 10 20 80 Includes: Formwork, reinforcement, and concrete. Grade Beams

Associated Masterformat Sections: 03 30 00

100	See <u>A10</u>	
200	 See <u>A10</u> Image Notes: Generic beam geometry is shown. Geotechnical regions are shown for context and not required to be modeled as part of this element at this LOD. 	7 A1020.80-LOD-200 Grade Beams
300	 See <u>A1010</u> Image Notes: Grade Beam See slab on grade (<u>A4010</u>, <u>A4020</u>) for related conditions at this LOD. Geotechnical regions are shown for context and not required to be modeled as part of this element at this LOD. 	8 A1020.80-LOD-300 Grade Beams

350	Element modeling to include:	
	 Water stops Pour joints and sequences required to identify reinforcing lap spice, scheduling, etc. Chamfer 	1
	Image Notes:	
	• Grade beam sizes are modeled with interfaces to other systems such as but not limited to slab turn downs, key-ways between concrete pours, construction joints and reinforcing dowels into adjacent pours.	
	• Interface elements such as void boxes or critical bearing zones are modeled where applicable.	
	• See slab on grade ((<u>A4010</u> , <u>A4020</u>) for related conditions at this LOD.	4
	• Geotechnical regions are shown for context and not required to be modeled as part of this element at this LOD.	
		9 A1020.80-LOD-350 Grade Beams
400	Element modeling to include:	
	 Detailed post-tensioned components Rebar including hooks and lap splices Dowels Waterproofing 	

A20

21-01 20

Subgrade Enclosures

Associated Masterformat Sections: 01 82 16

100	Solid mass model representing overall building volume; or, schematic wall elements that are not distinguishable by type or material. Assembly depth/thickness and locations still flexible.
200	 Element modeling to include: Approximate size and shape of the subgrade enclosure element. Structural building grids for local project coordinate system are defined in model and coordinated with global civil coordinate system (State Plane Coordinate System, etc). Suggested Baseline Attributes Member Type

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

A2010 21-01 20 10 Walls for Subgrade Enclosures

Includes: Perimeter walls enclosing building space below grade. Includes formwork, reinforcing, concrete and masonry. Includes Subgrade Enclosure Wall Supplementary Components as appropriate. May Include: Related Activities: Excavation, dewatering, excavation support systems, backfill and compaction, and soil treatment.

Associated Masterformat Sections: 01 82 16


100	See <u>A20</u>	
200	See <u>A20</u>	
300	 Element modeling to include: Overall size and geometry of the subgrade element Sloping surfaces External dimensions of the element Major openings such as large mechanical elements modeled to nominal dimensions. 	
350	Element modeling to include: Chamfers All penetrations modeled to rough opening dimensions. 	
	 Pour joints Rebar and any embedded elements modeled at congested areas where specified by project BXP which is typically with in a set distance from the area of congestion. 	
	 Any permanent shoring or forming structures such as void boxes insulation 	
	 Expansion joints Moisture retarder Exposed embeds or reinforcement such as lintels Penetrations detailed and modeled 	
400	Expansion joints Element modeling to include:	
	 Rebar including hooks and lap splices Dowels Coursing for unit masonry defined Waterproofing 	

A2010.10	21-01 20 10 10	Subgrade Enclosure Wall Construction	TBD
A2010.20	21-01 20 10 20	Subgrade Enclosure Wall Interior Skin	TBD
A2010.90	21-01 20 10 90 TBD	Subgrade Enclosure Wall Supplementary Componen	ts

Back to TOC

A40 21-01 40

Slabs-on-Grade



A4010

21-01 40 10

Standard Slabs-on-Grade

Includes: Slab construction supported continuously by earth or compacted fill. Includes fine grading, subbase layer, mud slab, insulation, vapor retarder, waterproofing, formwork, expansion joints, control joints, reinforcement, concrete, and finishing includes: Slabs-On-Grade Supplementary Components as appropriate. May Include: Related Activities: Excavation, dewatering, excavation support systems, backfill and compaction, and soil treatment.

Associated Masterformat Sections: 03 30 00

100	See <u>A40</u>	
200	See <u>A40</u>	
300	 Element modeling to include: Overall size, thickness and geometry of the slab Major openings such as large mechanical elements modeled to nominal dimensions. Slab depressions Edge turn downs Material strength Surfaces modeled to actual slopes 	11 A4010-LOD-300 Standard Slabs-on-Grade

350	 Element modeling to include: All penetrations modeled to rough opening dimensions. Pour joints Control joints Expansion joints Water stops Rebar and any embedded elements modeled at congested areas where specified by project BIMXP which is typically with in a set distance from the area of congestion. Void boxes Anchor rods Dowels Post-tension profile and strands if required by the BXP. 	12 A4010-LOD-350 Standard Slabs-on-Grade
400	 Element modeling to include: Fully modeled rebar Actual slab dimensions and profiles with fully modeled rebar Post tensioning components All joints Water proofing Finish 	

A4020 21-01 40 20 Structural Slabs-on-Grade

Includes: Self-supporting slab construction not supported continuously by earth or compacted fill. Includes formwork, accessories, reinforcement, concrete, and finishing. Includes Slabs-On-Grade Supplementary Components as appropriate. May Include: Related Activities: Excavation, dewatering, excavation support systems, backfill and compaction, and soil treatment.

Associated Masterformat Sections: 03 30 00

100	See <u>A40</u>	
200	See <u>A40</u>	

300	Element modeling to include:	
	 Overall size, thickness and geometry of the slab-on-grade Major openings such as large mechanical elements modeled to nominal dimensions. Slab depressions Edge turn downs All sloping surfaces included in model element with exception of elements affected by manufacturer selection which are not known at this LOD. Such conditions could include floor geometry differences where different <u>specified</u> manufacturers will not be known until the <u>actual</u> system is selected. 	13 A4020-LOD-300 Structural Slabs-on-Grade
350	 Element modeling to include: All penetrations modeled to rough opening dimensions. Pour joints Control joints Expansion joints Water Stops Rebar and any embedded elements modeled at congested areas where specified by project BXP which is typically with in a set distance from the area of congestion. Void boxes Anchor rods Moisture retarder Dowels Post-tension profile and strands modeled if required by the BXP Element modeling to include: Fully modeled rebar Actual slab dimensions and profiles with fully modeled rebar Post tensioning components All joints Water proofing Finish 	the second secon
A4030	21-01-40-30 Slab Trench	es TBD
A4040	21-01-40-40 Pits and Bas	es TBD
A4090	21-01-40-90 Slab-On-Gra	de Supplementary Components TBD
Back to TOC	Conversion Conversion to 2017 by BIME or um All rights reserved	32

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

Uniformat	Omniclass		
A60	21-01-60	Water and Gas Mitigation	TBD
A6010	21-01-60-10	Building Subdrainage	TBD
A6020	21-01-60-20	Off-Gassing Mitigation	TBD
A90	21-01-90	Substructure Related Activities	TBD
A9010	21-01-90-10	Substructure Excavation	TBD
A9020	21-01-90-20	Construction Dewatering	TBD
A9030	21-01-90-30	Excavation Support	TBD
A9040	21-01-90-40	Soil Treatment	TBD

SHELL

Associated Masterformat Sections: 01 83 00

21-02 00 00

B10 21-02 10

Β

Superstructure

Associated Masterformat Sections: 01 83 13

100	Assumptions for structural framing are included in other modeled elements such as an architectural floor element that contains a layer for assumed structural framing depth or schematic structural elements that are not distinguishable by type or material.	
	Assembly depth/thickness or component size and locations still flexible.	

B1010 21-02 10 10

Floor Construction

Associated Masterformat Sections: 01 83 13

100	See <u>B10</u>	
200	Model elements to include:	
	 Floor with approximate dimensions Approximate supporting framing members Structural grids defined accurately 	

B1010.10

21-02 10 10 10

Floor Structural Frame

Includes: Structural elements required for support of floor construction within basements and above grade. Includes columns, girders, beams, trusses, joists. Includes cast-in-place concrete, precast concrete, unit masonry, metal framed, and wood framed systems. Includes framed and sleeved openings for services. Includes Floor Construction Supplementary Components as appropriate.

Specific structural systems within this section are listed as follows:

- Concrete B1010.10.10 Precast Structural Inverted T Beam B1010.10.11 Precast Structural Column B1010.10.12 Masonry B1010.10.20 Steel Framing Columns B1010.10.30 Steel Framing Beams B1010.10.40 Steel Framing Bracing Rods B1010.10.50 Steel Joists B1010.10.60 Cold-Formed Metal Framing B1010.10.70 B1010.10.80
- Wood Floor Trusses

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 04 20 00 / 05 10 00 / 05 20 00 05 21 23 / 05 42 00 / 05 44 00 / 06 11 00 / 06 13 00 / 06 13 26 / 06 17 33 / 06 17 36 06 17 53 / 06 18 13 / 06 18 16 / 06 50 00

B1010.10.10 21-02 10 10 10 10 Floor Structural Frame (Concrete)

Associated Masterformat Sections: 03 30 00 / 03 40 00

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

100	See <u>B10</u>	
200	Element modeling to include:	
	 Type of structural concrete system Approximate geometry (e.g. depth) of structural elements 	
300	Element modeling to include:	
	 Composite model assembly by type with overall thickness of structural frame Specific sizes and locations of main concrete structural members modeled per defined structural grid with correct orientation Concrete defined per spec (strength, air entrainment, aggregate size, etc.) All sloping surfaces included in model element with exception of elements affected by manufacturer selection 	
350	Element modeling to include:	
	 Reinforcing Post-tension profiles and strand locations Reinforcement called out, modeled if required by the BXP, typically only in congested areas Pour joints and sequences to help identify reinforcing lap splice locations, scheduling, etc. Expansion Joints Embeds and anchor rods Post-tension profile and strands modeled if required by the BXP Penetrations for items such as MEP Any permanent forming or shoring components Shear reinforcing and stud rails Critical structural zones for coordination, including but not limited to zones that cannot be penetrated, cut, or damaged Chamfer 	
400	 Element modeling to include: All reinforcement including post tension elements detailed and modeled camber, etc. 	

B1010.10.11 21-02 10 10 10 11 Precast Structural Inverted T Beam (Concrete)

Includes: Structural elements required for support of floor construction within basements and above grade. Includes columns, girders, beams, trusses, joists. Includes cast-in-place concrete, precast concrete, unit masonry, metal framed, and wood framed systems. Includes framed and sleeved openings for services.Includes Floor Construction Supplementary Components as appropriate.

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 04 20 00 / 05 10 00 / 05 20 00 05 21 23 / 05 42 00 / 05 44 00 / 06 11 00 / 06 13 00 / 06 13 26 / 06 17 33 / 06 17 36 06 17 53 / 06 18 13 / 06 18 16 / 06 50 00

Back to TOC

100	See <u>B10</u>	
200	Element modeling to include:	-
	 Type of structural concrete system Approximate geometry (e.g. depth) of structural elements 	
		15 B1010.10-LOD 200 Precast Structural Inverted T Beam (Concrete)
300	Element modeling to include:	
	 Specific sizes and locations of main concrete structural members modeled per defined structural grid with correct orientation All sloping surfaces included in model element with exception of elements affected by manufacturer selection 	16 B1010.10-LOD 300 Precast Structural Inverted T Beam (Concrete)

350	Element modeling to include:	
	 Reinforcing Post-tension profiles and strand locations Reinforcement called out, modeled if required by the BXP, typically only in congested areas Chamfer Pour joints and sequences to help identify reinforcing lap splice locations, scheduling, etc. Lifting devices Expansion Joints Embeds and anchor rods Post-tension profile and strands modeled if required by the BXP Penetrations for items such as MEP Any permanent forming or shoring components 	
		17 B1010.10-LOD 350 Precast Structural Inverted T Beam (Concrete)
400	Element modeling to include:	
	 All reinforcement including post tension elements detailed and modeled Finishes 	
		18 B1010.10-LOD 400 Precast Structural Inverted T Beam (Concrete)

B1010.10.12 21-02 10 10 10 12 Precast Structural Column (Concrete)

Includes: Structural elements required for support of floor construction within basements and above grade. Includes columns, girders, beams, trusses, joists. Includes cast-in-place concrete, precast concrete, unit masonry, metal framed, and wood framed systems. Includes framed and sleeved openings for services. Includes Floor Construction Supplementary Components as appropriate.


Associated Masterformat Sections: 03 30 00 / 03 40 00 / 04 20 00 / 05 10 00 / 05 20 00 05 21 23 / 05 42 00 / 05 44 00 / 06 11 00 / 06 13 00 / 06 13 26 / 06 17 33 / 06 17 36 06 17 53 / 06 18 13 / 06 18 16 / 06 50 00

100	See <u>B10</u>	
200	 Element modeling to include: Type of structural concrete system Approximate geometry (e.g. depth) of structural elements 	
		19 B1010.10- LOD 200 Precast Structural Column (Concrete)

300	Element modeling to include:	
	 Specific sizes and locations of main concrete structural members modeled per defined structural grid with correct orientation All sloping surfaces included in model element with exception of elements affected by manufacturer selection 	20 B1010.10 - LOD 300 Precast Structural Column
		(Concrete)
350	 Element modeling to include: Reinforcing Post-tension profiles and strand locations Reinforcement called out, modeled if required by the BXP, typically only in congested areas Chamfer Pour joints and sequences to help identify reinforcing lap splice locations, scheduling, etc. Expansion Joints Lifting devices Embeds and anchor rods Post-tension profile and strands modeled if required by the BXP Penetrations for items such as MEP Any permanent forming or shoring components 	21 B1010.10 - LOD 350 Precast Structural Column (Concrete)



Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.



B1010.10.20 Floor Structural Frame (Masonry) 21-02 10 10 10 20

Associated Masterformat Sections: 04 20 00

100	See <u>B10</u>	
200	Element modeling to include:	
	Type of structural masonry system	
300	Element modeling to include:	
	 Specific sizes of main structural elements modeled per defined structural grid with correct dimensions Rough openings with reinforcement and lintels called out Penetrations for items such as MEP 	
350	 Element modeling to include: Actual location and shape of structural masonry element All exposed embeds or reinforcement such as lintels All penetrations modeled to rough opening dimensions Expansion joints Grouted cell locations 	

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

400	Element modeling to include:	
	 Waterproofing Coursing Reinforcing Grout 	

B1010.10.30 21-02 10 10 10 30 Floor Structural Frame (Steel Framing Columns)

Associated Masterformat Sections: 05 10 00

100	Generic column element, See <u>B10.</u>	23 B1010.10-LOD-100 Floor Structural Frame (Steel Framing Columns)
200	See <u>B1010</u>	24 B1010.10-LOD-200 Floor Structural Frame (Steel Framing Columns)
300	 Element modeling to include: Specific sizes of main vertical structural members modeled per defined structural grid with correct location and orientation 	25 B1010.10-LOD-300 Floor Structural Frame (Steel Framing Columns)

350	 Element modeling to include: Actual elevations and location of member connections Main elements of typical connections applied to all structural steel connections such as base plates, gusset plates, anchor rods, etc. Any miscellaneous steel members with correct size, shape, orientation, and material. Any steel structure reinforcement such as web stiffeners, sleeve penetrations, etc. 	
		26 B1010.10-LOD-350 Floor Structural Frame (Steel Framing Columns)
400	Element modeling to include: • Welds • Coping of members • Cap pates • Washers, nuts, etc. • All assembly elements	27 B1010.10-LOD-400 Floor Structural Frame (Steel Framing Columns)

Back to TOC

B1010.10.40 21-02 10 10 10 40 Floor Structural Frame (Steel Framing Beams)

Associated Masterformat Sections: 05 10 00 $\,/\,$ 05 20 00 $\,/\,$ 05 21 23

100	See B10	
200	See <u>B1010</u>	
300	 Element modeling to include: Specific sizes of main horizontal structural members modeled per defined structural grid with correct orientation, slope and elevation • 	28 B1010.10-LOD-300 Floor Structural Frame (Steel Framing Beams)
350	 Element modeling to include: Actual elevations and location of member connections Main elements of typical connections applied to all structural steel connections such as base plates, gusset plates, anchor rods, etc. Any miscellaneous steel members with correct size, shape, orientation and material Any steel structure reinforcement such as web stiffeners, sleeve penetrations, etc. 	29 B1010.10-LOD-350 Floor Structural Frame (Steel Framing Beams)
400	Element modeling to include: • Welds • Coping of members • Bent plates, cap pates, etc. • Bolts, washers, nuts, etc. • All assembly elements	30 B1010.10-LOD-400 Floor Structural Frame (Steel Framing Beams)

B1010.10.50 21-02 10 10 10 50 Floor Structural Frame (Steel Framing Bracing Rods)

Associated Masterformat Sections: 05 10 00

100	See <u>B10</u>	
200	See <u>B1010</u>	
300	 Element modeling to include: Specific sizes of main structural braces modeled per defined structural grid 	31 B1010.100-LOD-300 Floor Structural Frame (Steel Framing Bracing Rods)
350	 Element modeling to include: Connection details Actual elevations and location of member connections Main elements of typical connections applied to all structural steel connections such as base plates, gusset plates, anchor rods, etc. Any miscellaneous steel members with correct size, shape, orientation and material 	32 B1010.100-LOD-350 Floor Structural Frame (Steel Framing Bracing Rods)
400	Element modeling to include: Welds Clevis Bolts, washers, nuts, etc. All assembly elements 	33 B1010.100-LOD-400 Floor Structural Frame (Steel Framing Bracing Rods)

B1010.10.60 21-02 10 10 10 60 Floor Structural Frame (Steel Joists)

Associated Masterformat Sections: 05 10 00 / 05 20 00 / 05 21 23

100	See <u>B10</u>	
200	 Element modeling to include: Approximate depth 	
		34 B1010.10-LOD-200 Floor Structural Frame (Steel Joists)
300	Element modeling to include: Joist size, depth, slope, and material Spacing and end elevations Joist seat depth 	35 B1010.10-LOD-300 Floor Structural Frame (Steel Joists)



Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

350	 Element modeling to include, information needed for cross trade collaboration such as: Actual final joist profile locations with accurate panel points Joist bridging and lateral braces. Fire protection coating Any miscellaneous steel pertaining to the joist Joist seat width Erection details for installation Chord and web member section profiles are defined Joist layout in coordination with metal deck fasteners would be confirmed Non-standard joist seat depths and\or sloping joist seat 	36 B1010.10-LOD-350 Floor Structural Frame (Steel
400	Element modeling to include: • Welds • Connection plates • Member fabrication part number • Quantity • Spacing • Anchorage • Material required for proper installation • Mark identification that correlates with bill of material Type of shop paint if required	Joists)

B1010.10.70 21-02 10 10 10 70 Floor Structural Framing (Cold Formed Metal Framing)

Associated Masterformat Sections: 05 10 00 / 05 42 00 / 05 44 00

Back to TOC

100	See <u>B10</u>	
- 200	Element modeling to include:	
200	 Element modeling to include: Rough architectural masses Approximate member depth Desired member spacing 	
300	 Element modeling to include: floor element with design-specified locations and geometries 	
350	 Element modeling to include: Members modeled at any interface with wall edges (top, bottom, sides) or opening through wall Bridging or straps 	
400	 Element modeling to include: Welds Connections Member fabrication part number Any part required for complete installation 	

B1010.10 21-02 10 10 10 Floor Structural Frame (Masonry Framing)

Includes: Structural elements required for support of floor construction within basements and above grade. Includes columns, girders, beams, trusses, joists. Includes cast-in-place concrete, precast concrete, unit masonry, metal framed, and wood framed systems. Includes framed and sleeved openings for services. Includes Floor Construction Supplementary Components as appropriate.

Associated Masterformat Sections: 04 20 00

100	See B10	
100		

200	See B10	
200	See BTU	38 B1010.10-LOD-200 Floor Structural Frame (Masonry Framing)
300	 Element modeling to include: floor element with design-specified locations and geometries 	39 B1010.10-LOD-300 Floor Structural Frame (Masonry Framing)
350	 Element modeling to include: Members modeled at any interface with wall edges (top, bottom, sides) or opening through wall Any regions that would impact coordination with other systems such as but not limited to: Bond Beam & Lintel Regions Reinforcing & Embed Regions Jam Regions Any other grouted regions 	40 B1010.10-LOD-350 Floor Structural Frame (Masonry Framing)

400	Element modeling to include:	1
400	Element modeling to include: Reinforcing Connections Grouting Material Jams Bond Beams Lintels Member fabrication part number Any part required for complete installation	
		41 B1010.10-LOD-400 Floor Structural Frame (Masonry Framing)

B1010.10.80 21-02 10 10 10 80 Floor Structural Frame (Wood Floor Trusses)

Associated Masterformat Sections: 06 11 00 / 06 13 26 / 06 17 53

See <u>B10</u> 100

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

I

Uniformat Omniclass

200	Element modeling to include:	
	 Top chord or bottom chord bearing Truss orientation Approximate depth Approximate width Truss orientation Approximate centerline location of individual trusses 	
		42 B1010.10-LOD-200 Floor Structural Frame (Wood Floor Trusses)
300	 Element modeling to include: Truss size, depth, and material with sloping geometry Spacing and end elevations Support locations 	
		43 B1010.10-LOD-300 Floor Structural Frame (Wood Floor Trusses)
350	 Element modeling to include: Actual final truss profile with accurate panel points Bridging and lateral braces Fire protection coating Any miscellaneous framing pertaining the truss Erection details for installation Chord and web member section profiles are accurately defined Truss layout in coordination with deck fasteners would be confirmed Hold down locations for large bolts. 	
		44 B1010.10-LOD-350 Floor Structural Frame (Wood Floor Trusses)

400	Element modeling to include:	
	 Fasteners Sealant Truss plates and connection material Nails and fasteners Truss plates. Deck patterns and joints 	
		45 B1010.10-LOD-400 Floor Structural Frame (Wood Floor Trusses)

B1010.20 21-02 10 10 20 Floor Decks, Slabs, and Toppings

Includes: Structural slab, deck, and sheathing floor construction at intermediate floors of basement construction and above grade. Includes cast-in-place concrete, precast concrete, cementitious decks and toppings, metal decking, wood sheathing, and wood decking. Includes framed and sleeved penetrations for services and housekeeping pads for equipment. Includes Floor Construction Supplementary Components as appropriate.

Specific structural systems within this section are listed as follows:

- Wood Floor Deck
- Metal Floor Deck
- <u>Composite Floor Deck</u>
- <u>Concrete</u>

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 03 50 00 / 05 30 00 / 05 34 00 05 35 00 / 06 12 00 / 06 15 00 / 06 16 00 / 06 18 00 / 06 53 00 / 06 73 00

B1010.20.10 21-02 10 10 20 10 Floor Decks, Slabs, and Toppings (Wood Floor Deck)

Associated Masterformat Sections: 06 12 00 / 06 15 00 / 06 16 00 / 06 18 00

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

100	
100	See <u>B10</u>
200	See <u>B10</u>
300	Element modeling to include:
	 Applicable slopes Expected framing member profiles, spacing, and material
350	Element modeling to include:
	 Deck edge location Actual framing member and location per manufacture All miscellaneous framing including braces, kickers, etc. Deck openings modeled with support framing around openings Point load locations Actual opening locations and sizes defined
400	Element modeling to include:
	 All framing accessory and fasteners modeled per expected installation Waterproofing

B1010.20.20 21-02 10 10 20 20 Floor Decks, Slabs, and Toppings (Metal Floor Deck)

Associated Masterformat Sections: 05 30 00 / 05 34 00 / 05 35 00

100	See <u>B10</u>
200	See <u>B10</u>
300	Element modeling to include:
	 Deck thickness Specific Framing member profiles, spacing, and material Opening locations are prescriptively defined with notes for additional miscellaneous framing Point load locations
350	Element modeling to include: Deck edge location Deck splice and end lap locations Actual deck profile and flute locations per manufacturer All miscellaneous framing including braces, kickers, etc. Deck openings modeled with support framing
400	Element modeling to include: All framing accessory and fasteners modeled per expected installation Welds Waterproofing

B1010.20.30 21-02 10 10 20 30

Floor Decks, Slabs, and Toppings (Composite Floor Deck)

Associated Masterformat Sections: 06 73 00

100	See <u>B10</u>	
200	See <u>B10</u>	
300	 Element modeling to include: Specific deck thickness Specific Framing member profiles, spacing, material Opening locations are prescriptively defined with notes for additional miscellaneous framing 	
350	Element modeling to include: • Deck edge location • Actual deck profile and flute locations per manufacture • Deck splice and end lap locations • Actual framing member and location per manufacture • All miscellaneous framing including deck support, deck closure, shear studs, etc. • Slab openings modeled with support framing around openings • Point load locations • Slab reinforcing modeled if specified in BXP	
400	Element modeling to include: All framing accessory and fasteners modeled per expected installation All slab reinforcing Welds Waterproofing 	

B1010.20.40 21-02 10 10 20 40 Floor Decks, Slabs, and Toppings (Concrete)

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 03 50 00

100	See <u>B10</u>	
200	Element modeling to include:	
	 Type of structural concrete system (e.g. cast-in-place or precast) Approximate geometry (e.g. depth) of structural elements 	

300	 Element modeling to include: Specific sizes and locations of main concrete structural members modeled per defined structural grid with correct orientation All sloping surfaces included in model element with exception of elements affected by manufacturer selection 	
350	 Element modeling to include: Reinforcement called out, modeled if required by the BXP, typically only in congested areas Chamfer Pour joints and sequences to help identify reinforcing lap splice locations, scheduling, etc. Expansion Joints Embeds and anchor rods Post-tension profile and strands modeled if required by the BXP Penetrations for items such as MEP Any permanent forming or shoring components Shear reinforcing and stud rails 	
400	 Element modeling to include: All reinforcement including post tension elements detailed and modeled Finishes 	

B1010.20.41 21-02 10 10 10 41 Precast Structural Double Tee (Concrete)

Includes: Structural elements required for support of floor construction within basements and above grade. Includes columns, girders, beams, trusses, joists. Includes cast-in-place concrete, precast concrete, unit masonry, metal framed, and wood framed systems. Includes framed and sleeved openings for services. Includes Floor Construction Supplementary Components as appropriate

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 04 20 00 / 05 10 00 / 05 20 00 05 21 23 / 05 42 00 / 05 44 00 / 06 11 00 / 06 13 00 / 06 13 26 / 06 17 33 / 06 17 36 06 17 53 / 06 18 13 / 06 18 16 / 06 50 00

100	See <u>B10B10</u>	
200	 Element modeling to include: Approximate geometry (e.g. depth) of structural elements 	
		46 B1010.20 – LOD 200 Precast Structural Double Tee (Concrete)

Back to TOC

300	Element modeling to include:			
	 Specific sizes and locations of m structural members modeled per structural grid with correct orient Concrete defined per spec (strer entrainment, aggregate size, etc All sloping surfaces included in r with exception of elements affect manufacturer selection 	r defined ation ngth, air .) nodel element	47 B1010.20 – LOD 300 Precast Structural Double Te (Concrete)	е
350	 Element modeling to include: Reinforcing Post-tension profiles locations Reinforcement called out, model by the BXP, typically only in const Chamfer Pour joints and sequences to he reinforcing lap splice locations, s Expansion Joints Lifting devices Embeds and anchor rods Penetrations for items such as M Any permanent forming or shorir 	led if required gested areas Ip identify scheduling, etc.	48 B1010.20 – LOD 350 Precast Structural Double Te (Concrete)	6
400	 Element modeling to include: All reinforcement including post relements detailed and modeled Finishes 	tension	49 B1010.20 – LOD 400 Precast Structural Double Te (Concrete)	е
B1010.30	21-02 10 10 30	Balcony Flo	or Construction	TBD
B1010.40	21-02 10 10 40	Mezzanine I	Floor Construction	TBD
B1010.50	21-02 10 10 50	Ramps		TBD

B1010.90

21-02 10 10 50

Floor Construction Supplementary Components

TBD

B1020 21-02 10 20 Associated Masterformat Sections: 01 81 13

Roof Construction

Note: This classification refers to roofs modeled as single composite objects (excluding structural frame). If individual layers are to be modeled refer to:

<u>B1020.10</u>	21-02 10 20 10	Roof Structural Frame
<u>B1020.20</u>	21-02 10 20 20	Roof Decks, Slabs, and Sheathing
<u>B3010</u>	21-02 30 10	Roofing

B1020.10 21-02 10 20 10 Roof Structural Frame

Description: Structural elements required for support of floor construction within basements and above grade. Includes columns, girders, beams, trusses, joists. Includes cast-in-place concrete, precast concrete, unit masonry, metal framed, and wood framed systems. Includes framed and sleeved openings for services. Includes Floor Construction Supplementary Components as appropriate.

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 04 20 00 / 05 10 00 / 05 20 00 / 05 21 23 / 05 42 00 / 05 44 00 06 11 00 / 06 13 00 / 06 13 26 / 06 17 33 / 06 17 3606 17 53 / 06 18 13 / 06 18 16 / 06 50 00

[See <u>B1010.10</u>]

B1020.20 21-02 10 20 20

Roof Decks, Slabs, and Sheathing

Includes: Structural roof deck, slab, and sheathing construction. Includes cast-in-place concrete, precast concrete, cementitious decks and toppings, metal decking, wood sheathing, wood decking, timber decking and expansion control. Includes framed and sleeved penetrations for services and housekeeping pads for equipment. Includes Roof Construction Supplementary Components as appropriate.

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 03 50 00 / 03 52 00 / 05 30 00 05 34 00 / 05 35 00 / 06 12 00 / 06 15 00 / 06 16 00 / 06 18 00 / 06 53 00 / 06 73 00

100	N/A	
200	Generic roof objects separated by type of material	
	Approximate thickness of layer represented by a single assembly.	
	Layouts and locations still flexible.	
300	Penetrations are modeled to nominal dimensions for major roof openings such as skylights and large mechanical elements.	
350	All penetrations are modeled at actual rough-opening dimensions.	
	Framing members at openings are modeled.	
400	Element modeling to include:	
	 Studs and tracks Individual masonry units Reinforcing Sheathing Insulation 	

B1020.30 21-02 10 20 30 Canopy Construction

Includes: Structural frame and decks, slabs, and sheathing for canopy construction.

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 05 10 00 / 05 19 19 / 05 20 00 / 06 11 00 / 06 12 00 / 06 13 00 / 06 15 00 / 06 16 00 / 06 17 00 / 06 18 00 / 06 50 00 / 06 73 00

[See <u>B1010.20</u>]

B1020.90 21-02 10 20 90 **Roof Construction Supplementary Components** TBD Includes: Vapor retarders, air barriers, insulation, fireproofing, firestopping, and expansion control to be included with roof construction elements above as appropriate

21-02 10 80 Stairs B1080

Includes: Stairs, fire escapes, metal walkways, and ladders.

Associated Masterformat Sections: 01 84 16


walkways, and ladders) are included in other modeled elements such as a spatial or massing element; or, schematic model element that indicates the approximate overall dimensions of the stair layout.

21-02 10 80 10 B1080.10 Stair Construction

Includes: Structural framing for exterior and interior stairs including treads, risers, and landings. Includes fire escapes and ladders.

Associated Masterformat Sections: 03 11 23 / 03 30 00 / 03 41 23 / 03 48 19 / 05 51 00 05 55 00 / 05 71 00 / 06 43 00

100	See <u>B1080</u>	
200	Generic model element with simplified treads and risers.	
	Nominal overall unit scope shall include:	
	 Nominal plan dimensions (length, width) Nominal vertical dimensions (levels, landings) 	
		50 B1080.10-LOD-200 Stair Construction



300	 Major stair support elements are modeled (stringers). Element is accurate as to Riser count Riser height Tread width Nosing conditions, including top and bottom Landing geometry 	
		51 B1080.10-LOD-300 Stair Construction
350	Secondary stair support elements are modeled (hangers, brackets, handrail connection points etc.).	52 B1080.10-LOD-350 Stair Construction

400	All stair elements are modeled to support fabrication and installation.	
		53 B1080.10-LOD-400 Stair Construction

B1080.20 21-02 10 80 10 Precast Structural Stairs (Concrete)

Includes: Structural framing for exterior and interior stairs including treads, risers, and landings. Includes fire escapes and ladders.

Associated Masterformat Sections: 03 11 23 $\,/\,$ 03 30 00 $\,/\,$ 03 41 23 $\,/\,$ 03 48 19 $\,/\,$ 05 51 00 05 55 00 $\,/\,$ 05 71 00 $\,/\,$ 06 43 00

100	See <u>B1080</u>	
-----	------------------	--

200	Element modeling to include:	
	 Type of structural concrete system Approximate geometry (e.g. depth) of structural elements 	55 B1080. 10-LOD 200 Precast Structural Stairs (Concrete)
300	 Element is accurate as to Riser count Riser height Tread width Nosing conditions, including top and bottom Landing geometry 	56 B1080.10-LOD 300 Precast Structural Stairs (Concrete)

Back to TOC

350	Element modeling to include:	
330	 Reinforcing Post-tension profiles and strand locations Reinforcement called out, modeled if required by the BXP, typically only in congested areas Pour joints and sequences to help identify reinforcing lap splice locations, scheduling, etc. Chamfer Expansion Joints Lifting devices Embeds and anchor rods Post-tension profile and strands modeled if required by the BXP All penetrations modeled to rough opening dimensions. Any permanent forming or shoring components 	
		57 B1080.10-LOD 350 Precast Structural Stairs (Concrete)
400	 Element modeling to include: All reinforcement including post tension elements detailed and modeled Finishes, , etc. 	58 B1080.10-LOD 400 Precast Structural Stairs (Concrete)

B1080.30


21-02 10 80 30

Stair Soffits

TBD

B1080.50 21-02 10 80 50 Stair Railings Associated Masterformat Sections: 05 15 00 / 05 52 00 / 05 73 00 / 06 43 16 / 06 63 00

06 81 00



400	[See <u>Fundamental LOD Definitions</u>]	
		61 B1080.50-LOD-400 Stair Railings

B1080.60 21-02 10 80 60 Associated Masterformat Sections: 05 51 23 Fire Escapes

[See <u>B1080.10</u> and <u>B1080.50</u>]

B1080.70 21-02 10 80 70 Metal Walkways Includes: Catwalks and gratings over horizontal openings

Associated Masterformat Sections: 05 51 36 $\,$ / 05 51 36.13 $\,$ / 05 53 00 $\,$

[See <u>B1080.10</u> and <u>B1080.50</u>]

10	0	See B1080	
20	0	Grating type	
			B1080.70 LOD 200 Grating

300	 Element modeling to include: Grating type and overall geometry. Thickness Surface pattern showing span direction. 	
350	 Element modeling to include: Panel layout and grating deck edges. Banding, openings, and grating penetrations. 	B1080.70 LOD 300 Grating
		B1080.70 LOD 350 Grating
400	Element modeling to include:	
	Full fabrication connections	

B1080.80 21-02 10 80 80 Ladders

21-02 20

Associated Masterformat Sections: 05 51 33 / 05 51 33.13 / 05 51 33.16 / 05 51 33.23

[See <u>B1080.10</u> and <u>B1080.50</u>]

B20

Exterior Vertical Enclosures

Associated Masterformat Sections: 01 83 16

100	Solid mass model representing overall building volume; or, schematic wall elements that are not distinguishable by type or material.	
	Assembly depth/thickness and locations still flexible.	

Back to TOC

Exterior Walls B2010 21-02 20 10

Includes: Exterior Wall Supplementary Components as appropriate. Includes Exterior Wall Opening Supplementary Components as appropriate. Includes: Solid wall construction that is composite in nature; in other words, multiple layers of materials to form an overall assembly.

Associated Masterformat Sections: 01 83 16

Note: This classification refers to walls modeled as single composite objects. If individual layers are to be modeled refer to:

<u>B2010.10</u>	21-02 20 10 10 Exterior Wall Veneer
<u>B2010.20</u>	21-02 20 10 20 Exterior Wall Construction
<u>B2010.30</u>	21-02 20 10 30 Exterior Wall Interior Skin

100	See <u>B20</u>	
200	Generic wall objects separated by type of material (e.g. brick wall vs. terracotta).	
	Approximate overall wall thickness represented by a single assembly.	
	Layouts and locations still flexible.	
		62 B2010-LOD-200 Exterior Walls
300	Single model element with specific overall thickness that accounts for veneer, structure, insulation, air space, and interior skin specified for the wall system. (Refer to LOD350 and LOD400 for individually modeled elements)	
	Penetrations are modeled to nominal dimensions for major wall openings such as windows, doors, and large mechanical elements.	
		63 B2010-LOD-300 Exterior Walls
350	May be modeled as a dingle model element.	
	Main structural members such as headers and jambs at openings are modeled.	
	All penetrations are modeled at actual rough-opening dimensions.	
		64 B2010-LOD-350 Exterior Walls



Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.</u>

21-02 20 10 10 **Exterior Wall Veneer** B2010.10

Includes: Nonstructural outside face elements of exterior walls. Includes precast concrete, unit masonry, EIFS, manufactured siding, and stucco Includes water repellents, coatings, and painting.

Associated Masterformat Sections: 03 40 00 / 04 20 00 / 04 26 13 / 04 42 00 / 04 43 13 04 70 00 / 05 19 13 / 06 20 13 / 06 61 00 / 07 19 00 / 07 24 00 / 07 42 00 / 07 44 00 07 46 00 / 09 24 00 / 09 24 23 / 09 90 00

100	N/A	
200	Generic wall objects separated by type of material (e.g. brick wall vs. terracotta). Approximate thickness of layer represented by a single assembly. Layouts and locations still flexible.	
		65 B2010.10-LOD-200 Exterior Wall Veneer
300	Exterior wall veneer modeled as a separate element. Specific wall modeled to actual dimensions. Penetrations are modeled to nominal dimensions for major wall openings such as windows, doors, and large mechanical elements.	66 B2010.10-LOD-300 Exterior Wall Veneer
350	 Exterior wall veneer modeled as a separate element. All penetrations are modeled at actual rough-opening dimensions. Precast concrete panels are individually modeled. Connection points are specified. Connection to interfacing systems <i>Images notes:</i> Wall veneer element 	67 B2010.10-LOD-350 Exterior Wall Veneer
		67 62010.10-LOD-330 Exterior Wall Verieer

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

	 Skin layers including but not limited to waterproofing membrane Core framing Concrete slab edge 	
400	 Element modeling includes: Image notes: Individual masonry units Skin layers including Moisture barrier, sheathing, and insulation Core framing Bolt Concrete slab edge Weep holes 	68 B2010.10-LOD-400 Exterior Wall Veneer

B2010.20

21-02 20 10 20

Exterior Wall Construction

Includes: Exterior wall construction including backup systems for wall veneer. May be vertical load bearing. Includes cast-in-place concrete walls, precast concrete walls, unit masonry walls, metal framed wall systems, and wood framed wall systems.

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 04 20 00 / 05 41 00 / 06 11 00 06 12 00 / 06 16 00

100	N/A	
200	Generic wall objects separated by type of material (e.g. brick wall vs. terracotta).	
	Approximate thickness of layer represented by a single assembly.	
	Layouts and locations still flexible.	
300	Specific wall modeled to actual dimensions.	

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.</u>

	Penetrations are modeled to nominal dimensions for major wall openings such as windows, doors, and large mechanical elements.	
350	Exterior wall construction modeled as a separate element. All penetrations are modeled at actual rough-opening	
	dimensions.	
	Headers and jamb framing are modeled.	
400	Element modeling to include:	
	 Studs and tracks Individual masonry units Reinforcing Sheathing Insulation 	

B2010.20.10 21-02 20 10 20 10 Exterior Wall Construction (Wood)

Includes: Exterior Wall Supplementary Components as appropriate. Includes Exterior Wall Opening Supplementary Components as appropriate. Includes: Solid wall construction that is composite in nature; in other words, multiple layers of materials to form an overall assembly.

Associated Masterformat Sections: 01 83 16

100	N/A	
200	Generic wall objects separated by type of material (e.g. brick wall vs. terracotta).	
	Approximate thickness of layer represented by a single assembly.	
	Layouts and locations still flexible.	
		69 B2010.06-LOD-200 Exterior Wall (Wood)

300	Specific wall modeled to actual dimensions.	
	Penetrations are modeled to nominal dimensions for major wall openings such as windows, doors, and large mechanical elements. Shear panels	
		70 B2010.06-LOD-300 Exterior Wall (Wood)
350	 Wood framing is developed with sufficient elements to support detailed interface coordination with other systems such as MEP. All penetrations are modeled at actual rough-opening dimensions. Openings modeled with support framing around openings <i>Image notes:</i> Elements in red are critical wall support elements that cannot be easily cut for coordination of MEP opening through the walls. Infill wood framing modeling may be omitted at this LOD if stated in the BXP. Cladding and sheathing are not shown for clarity in this image. 	
		71 B2010.06-LOD-350 Exterior Wall (Wood)

400	Wood framing is developed with sufficient elements that support the fabrication of the wood framing system.	
	Image notes:1) Connection content is development in the wall elements. This includes but is not limited to	
	 fasteners, anchor rods, and other related hardware. 2) Cladding and sheathing are not shown for clarity in this image. 	
		72 B2010.06-LOD-400 Exterior Wall (Wood)

B2010.20.20 21-02 20 10 20 20 Exterior Wall Construction (Cold-Form Metal Framing)

Includes: Exterior Wall Supplementary Components as appropriate. Includes Exterior Wall Opening Supplementary Components as appropriate. Includes: Solid wall construction that is composite in nature; in other words, multiple layers of materials to form an overall assembly.

Associated Masterformat Sections: 01 83 16

100 N/A	
---------	--

200	Generic wall objects separated by type of material (e.g. brick wall vs. terracotta). Approximate thickness of layer represented by a single assembly. Layouts and locations still flexible.	
		73 B2010.05-LOD-200 Exterior Wall (Cold-Form Metal Framing)
300	Specific wall modeled to actual dimensions. Penetrations are modeled to nominal dimensions for major wall openings such as windows, doors, and large mechanical elements.	
	Shear panels	
		74 B2010.05-LOD-300 Exterior Wall (Cold-Form Metal Framing)

Back to TOC

350	Cold formed metal framing is developed with sufficient elements to support detailed interface coordination with other systems such as MEP. All penetrations are modeled at actual rough-opening dimensions.	
	Openings modeled with support framing around openings <i>Image notes:</i>	
	• Elements in red are critical wall support elements that cannot be easily cut for coordination of MEP opening through the walls.	
	• Diagonal bracing (kickers) that may be in the above ceiling space are modeled for coordination with other building content such as MEP passing along the wall in the above ceiling spaces.	
	• Infill cold formed metal framing modeling (Orange) may be omitted at this LOD if stated in the BXP.	75 B2010.05-LOD-350 Exterior Wall (Cold-Form Metal Framing)
	• Cladding and sheathing are not shown for clarity in this image.	

400	 Cold formed metal framing is developed with sufficient elements that support the fabrication of the CFMF system. <i>Image notes:</i> <i>Connection content is development in the wall elements. This includes but is not limited to fasteners, clips, and other related hardware.</i> <i>Cladding and sheathing are not shown for clarity in this image.</i> 	
		76 B2010.05-LOD-400 Exterior Wall (Cold-Form Metal Framing)

B2010.20.30 21-02 20 10 20 30 Exterior Wall Construction (Masonry)

Includes: Exterior Wall Supplementary Components as appropriate. Includes Exterior Wall Opening Supplementary Components as appropriate. Includes: Solid wall construction that is composite in nature; in other words, multiple layers of materials to form an overall assembly.

Associated Masterformat Sections: 01 83 16


100 N/A

Back to TOC

		T
200	Generic wall objects separated by type of material (e.g. brick wall vs. terracotta).	
	Approximate thickness of layer represented by a single assembly.	
	Layouts and locations still flexible.	77 B2010.04-LOD-200 Exterior Wall (Masonry)
300	Specific wall modeled to actual dimensions. Penetrations are modeled to nominal dimensions for major wall openings such as windows, doors, and large mechanical elements. Shear panels	
		78 B2010.04-LOD-300 Exterior Wall (Masonry)
350	 Element modeling to include: Members modeled at any interface with wall edges (top, bottom, sides) or opening through wall All penetrations are modeled at actual rough-opening dimensions. Openings modeled with support framing around openings Any regions that would impact coordination with other systems such as but not limited to: Bond Beam & Lintel Regions Jam Regions Any other grouted regions 	
		79 B2010.04-LOD-350 Exterior Wall (Masonry)



Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.



B2010.20.40 21-02 20 10 20 40 Precast Wall Construction (Concrete)

Includes: Exterior wall construction including backup systems for wall veneer. May be vertical load bearing. Includes cast-in-place concrete walls, precast concrete walls, unit masonry walls, metal framed wall systems, and wood framed wall systems.

Associated Masterformat Sections: 03 30 00 $\,/\,$ 03 40 00 $\,/\,$ 04 20 00 $\,/\,$ 05 41 00 $\,/\,$ 06 11 00 06 12 00 $\,/\,$ 06 16 00

100	N/A	
200	Generic wall objects separated by type of material (e.g. brick wall vs. terracotta).	
	Approximate thickness of layer represented by a single assembly.	
	Layouts and locations still flexible.	
300	Specific wall modeled to actual dimensions.	
	Penetrations are modeled to nominal dimensions for major wall openings such as windows, doors, and large mechanical elements.	
	Shear panels	
350	Element modeling to include:	
	 Reinforcing Post-tension profiles and strand locations Reinforcement called out, modeled if required by the BXP, typically only in congested areas Pour joints and sequences to help identify reinforcing lap splice locations, scheduling, etc. Expansion Joints Lifting devices Embeds and anchor rods Post-tension profile and strands modeled if required by the BXP All penetrations are modeled at actual rough-opening dimensions. Any permanent forming or shoring components Chamfer, reveals, etc. 	
		93 B2010.20– LOD 350 Precast Wall (Concrete)

400	Element modeling to include:	The second se
400	 Element modeling to include: All reinforcement including post tension elements detailed and modeled 	
		94 B2010.20– LOD 400 Precast Wall (Concrete)

B2010.30

21-02 20 10 30

Exterior Wall Interior Skin

Includes: Materials to provide finish or protective covering on inside of face of exterior walls. May include insulation and vapor retarder.

Associated Masterformat Sections: 09 20 00

100	N/A	
200	Generic wall objects separated by type of material (e.g. brick wall vs. terracotta).	
	Approximate thickness of layer represented by a single assembly.	
	Layouts and locations still flexible.	
300	Specific wall modeled to actual dimensions.	
	Penetrations are modeled to nominal dimensions for major wall openings such as windows, doors, and large mechanical elements.	

350	Exterior wall interior skin modeled as a separate element.	
	All openings modeled to rough opening dimensions.	
400	Element modeling to include:	
	1) Studs and tracks	
	Individual masonry units	
	Reinforcing	
	Wall board	
	Insulation	

B2010.40 21-02 20 10 40 Fabricated Exterior Wall Assemblies

TBD

Includes: Manufactured or fabricated assemblies that include exterior veneer and wall construction within one fabricated assembly and may also include interior skin. Includes Exterior Wall Supplementary Components as appropriate.

Associated Masterformat Sections: 04 25 00 / 07 42 63 / 07 44 63 / 08 44 00 / 08 45 00

Note: For Curtain Walls see:

B2020.30 21-02 20 20 30 Exterior Window Wall

B2010.50 21-02 20 10 50 Parapets

Includes: Exterior wall construction above plane of roof.

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 04 20 00 / 05 41 00 / 06 11 00 06 12 00 / 06 16 00

[See <u>B2010</u>, <u>B2010.10</u>, <u>B2010.20</u>, and <u>B2010.30</u>]

B2010.60 21-02 20 10 60 Equipment Screens

Includes: Exterior wall construction to screen equipment from public view.

Associated Masterformat Sections: 03 40 00 / 04 20 00 / 08 92 00

[See B2010, B2010.10, B2010.20, and B2010.30]

B2010.80	21-02 20 10 80	Exterior Wall Supplementary Components	TBD
B2010.90	21-02 20 10 90	Exterior Wall Opening Supplementary Components	TBD

21-02 20 20

Exterior Windows

Includes: Fixed or operable windows used singly and in multiples located in the exterior vertical enclosure. Includes Exterior Window Supplementary Components as appropriate. Includes windows units with louver blinds integrally set between glass panels. Includes metal, wood, plastic, and composite window units. May Include: Wall Opening Supplementary Components as appropriate.

Associated Masterformat Sections: 01 83 16 / 08 50 00

100 See <u>B20</u>

B2020

200	Windows approximate in terms of location, size, count and type. Units are modeled as a simple, monolithic component; or represented with simple frame and glazing.	
	Nominal unit size is provided.	

B2020.10 21-02 20 20 10 Exterior Operating Windows

Includes: Window screens and storm windows.

Associated Masterformat Sections: 08 50 00 / 08 51 66 / 08 52 66 / 08 53 66 / 08 54 66 08 51 69 / 08 52 69 / 08 53 69 / 08 54 69

100	See <u>B20</u>	
200	See <u>B2020</u>	
300	Units are modeled based on specified location and nominal size. Outer geometry (profile) of window frame elements and glazing modeled in correct location Operation is indicated.	
350	Attachment method of window to structure Embed elements Backer rod and sealant	
400	Detailed frame extrusion profiles Glazing sub-components (gaskets) Attachment components 1) End dam 2) Fasteners	

B2020.20 21-02 20 20 20 Associated Masterformat Sections: 08 50 00 Exterior Fixed Windows

[See <u>B2020.10</u>]

B2020.30 21-02 20 20 30 Associated Masterformat Sections: 08 43 00

See B20

Exterior Window Wall

100

Back to TOC

200	Generic wall objects representing major types of proposed window wall assemblies. Overall window wall assembly depth represented by a single model object. Layouts and locations still flexible.	
		95 B2020.30-LOD-200 Exterior Window Wall
300	Specified location and orientation of face of glass. Nominal face dimensions and thickness of glazing. Spacing, location, size and orientation of mullions. Operable components defined (windows, louvers and doors) and included in model.	96 B2020.30-LOD-300 Exterior Window Wall

Back to TOC

350	Mullion shapes and geometry defined.	
	Actual anchorage layouts and types defined and modeled.	
	Actual panel dimensions (including seating).	97 B2020.30-LOD-350 Exterior Window Wall



400	Complete mullion extrusion profiles.	
400	Complete mullion extrusion profiles. Interface details between wall systems (within) and wall and support systems including sealants, end dams, flashings and membranes.	
		98 B2020.30-LOD-400 Exterior Window Wall

B2020.50 21-02 20 20 50

Exterior Special Function Windows

Includes: Exterior windows with special characteristics for a special function.

Associated Masterformat Sections: 08 56 00 / 08 55 00 / 08 88 39 / 08 56 19 / 08 56 46 08 56 49 / 08 88 49 / 08 56 53 / 08 88 53 / 08 88 56 / 08 56 63 / 08 56 73 / 08 75 00 08 80 00

[See <u>B2020.10</u>]

Back to TOC

21-02 20 50 B2050 Exterior Doors and Grilles

Includes: Doors, grilles, and gates located in the exterior vertical enclosure. Includes screen and storm door assemblies. Includes Exterior Door Supplementary Components as appropriate. May Include: Wall Opening Supplementary Components as appropriate.

Associated Masterformat Sections: 01 83 16

100	Simple representation of a door unit. Size, count, and location are approximate.	
200	Units are modeled as a simple, monolithic component; or represented with simple frame and panel. Nominal unit size is provided.	

B2050.10 21-02 20 50 10 Exterior Entrance Doors

Includes: Exterior personnel door assemblies at main entrances. Includes automatic, revolving, balanced, and other special operating entrance doors, and sliding storefront wall systems.

Associated Masterformat Sections: 08 32 00 / 08 42 00 / 08 42 26 / 08 42 29 / 08 42 33 08 42 36 / 08 43 29

100	See <u>B20</u>	
200	See <u>B2050</u>	
300	Entrance door assemblies modeled by type to include the following:	
	Specific door panels and frames (if applicable).	
	Operation is specified. Spatial requirements for operation may be modeled if required by BXP.	
350	Major framing elements are modeled at jambs and head.	
	Thresholds	
	Operation or mechanism enclosures are modeled.	
	All connections and interfaces modeled including brackets and supports.	
400	Complete mullion extrusion profiles Actual panel size dimensions.	

B2050.20 21-02 20 50 20 Includes: Exterior personnel door assemblies other than at main entrances.

Exterior Utility Doors

Associated Masterformat Sections: 08 10 00

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

100	See <u>B20</u>	
200	See B2050	
300	See B2050.10	
350	See B2050.10	
400	All connections and interfaces modeled including brackets, supports, sealants, and thresholds.	

B2050.30 21-02 20 50 30 Exterior Oversize Doors

Includes: Large exterior door assemblies to allow for passage of large objects involving various operating methods. Includes Exterior Door Supplementary Components as appropriate including operators and drive mechanisms.

Associated Masterformat Sections: 08 33 00 / 08 36 00 / 08 36 13 / 08 36 16 / 08 36 19 08 36 23 / 08 34 16

100	See <u>B20</u>	
200	See <u>B2050</u>	
300	Oversize door assemblies modeled by type to include the following:	
	Door panels with nominal dimensions.	
	Frames with nominal dimensions.	
	Clearance zones are modeled or accommodated by model checking software for operation of overhead doors (other than coiling doors).	
	Enclosures and motor housings are modeled with overall nominal dimensions.	
350	Major framing elements in wall are modeled at jambs and head.	
	Attachment elements are modeled	
400	All connections and interfaces modeled including brackets, supports, sealants, and thresholds.	

21-02 20 50 40 B2050.40 Exterior Special Function Doors

Includes: Exterior door assemblies for a variety of special functions and applications involving a variety of operating methods. Includes Exterior Door Supplementary Components as appropriate including controls and operators.

Associated Masterformat Sections: 08 30 00 / 08 34 13 / 08 34 19 / 08 34 46 / 08 34 49 08 34 53 / 08 34 63 / 08 34 73 / 08 38 00 / 08 39 00 / 08 88 49 / 08 88 53 / 08 88 56

[See <u>B2050.20</u> or <u>B2050.30</u>]

B2050.60

21-02 20 50 60

Exterior Grilles

Includes: Exterior devices of open construction to provide moveable barrier to provide access through wall or other divider.

Associated Masterformat Sections: 08 33 00 / 08 35 16

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.</u>

100	See <u>B20</u>
200	See <u>B2050</u>
300	Grille assemblies modeled by type to include the following: Nominal size of unit. Operation is specified.
350	Major framing elements are modeled at jambs and head.
400	All connections and interfaces modeled including brackets, supports, sealants, and thresholds.

B2050.70 21-02 20 50 70 Exterior Gates

Includes: Exterior devices of solid or open construction to provide moveable barrier to provide access through wall or other divider.

Associated Masterformat Sections: 08 34 56

[See <u>B2050.60</u>]

B2050.90 21-02 20 70 Exterior Door Supplementary Components Includes frames, hardware, glazing and louvers that are part of door to be included with exterior door elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 08 10 00 / 08 30 00 / 08 71 00 / 08 80 00 / 08 91 26

B2070

Exterior Louvers and Vents

Includes: Exterior louvers which are not an integral part of mechanical equipment, including louvers connected to ducts.

Associated Masterformat Sections: 08 90 00

100	See <u>B20</u>	
200	Generic model element that is indicative of approximate area and location of intended louver/vent.	

B2070.10 21-02 20 70 10 Exterior Louvers

Associated Masterformat Sections: 01 83 16 / 08 91 00

100	See <u>B20</u>	
200	See <u>B2070</u>	
300	Louver assembly modeled by type, indicative of area and location of intended louver/vent.	
	Accurate frame and blade boundary areas.	
	Opening for louver is cut from host wall	

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

350	Major framing elements are modeled at connection points.	
	Connection points are modeled.	
400	All connections and interfaces modeled including brackets, supports, and sealants.	

B2070.50 21-02 20 70 50 Associated Masterformat Sections: 08 95 00

Exterior Vents

[See <u>B2070.10</u>]

B2080 21-02 20 80

Includes: Exterior enclosures, grilles and screens of wood, metal, plastic, and other materials for a variety of purposes including screening of equipment.

Exterior Wall Appurtenances

Associated Masterformat Sections:

[See <u>B2050</u>]

B2080.10 21-02 20 80 10 Exterior Fixed Grilles and Screens

Includes: Exterior enclosures, grilles and screens of wood, metal, plastic, and other materials for a variety of purposes including screening of equipment.

Associated Masterformat Sections: 05 70 00 / 06 49 00 / 06 60 00 / 06 80 00 / 10 82 13

[See <u>B2050.60</u>]

B2080.30 21-02 20 80 30

Exterior Opening Protection Devices

Includes: Manufactured items such as louvers, fins, shutters, demountable panels, awnings, and sun screens to provide sun control, privacy, security, insulation, and storm protection on exterior of windows, skylights, and entrances. Includes fixed and moveable, manually and electrically operated, and automatically controlled devices.

Associated Masterformat Sections: 10 71 00 / 10 71 13 / 10 71 16 / 10 73 13

[See <u>B2010.60</u>]

B2080.50 21-02 20 80 50 Exterior Balcony Walls and Railings

Includes: Exterior enclosures, grilles and screens of wood, metal, plastic, and other materials for a variety of purposes including screening of equipment.

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 04 20 00 / 05 41 00 / 06 11 00 06 16 00 / 05 52 00 / 05 73 00 / 06 43 16 / 06 63 00 / 06 81 00

[See <u>B2010.50</u>]

21-02 20 80 70 Exterior Fabrications

Includes: Exterior fabrications of a variety of materials formed to various profiles for a variety of purposes including column covers, decorative metal, ornamental woodwork, and plaster fabrications.

Back to TOC

B2080.70

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

Associated Masterformat Sections: 03 49 00 / 05 50 00 / 05 58 13 / 05 70 00 / 06 44 00 06 60 00 / 06 61 00 / 06 80 00 / 09 27 00

[See Fundamental LOD Definitions]

B2080.80 21-02 20 80 80 Bird Control Devices

Includes: Mechanical, electrical, physical, and chemical repellant systems, and protective devices.

Associated Masterformat Sections: 10 81 13

[See Fundamental LOD Definitions]

B2090 21-02 20 90 Exterior Wall Specialties

Includes: Complete fabrication of metal, wood, and fiberglass, including accessories and appurtenances. For example, clocks, belowgrade egress assemblies, and window wells.

Associated Masterformat Sections: 07 77 00 / 10 74 00 / 10 74 13 / 10 74 43 / 10 74 46

[See Fundamental LOD Definitions]

B30

21-02 30

Exterior Horizontal Enclosures

Associated Masterformat Sections: 01 83 16

100	Solid mass model representing overall building volume; or, schematic wall elements that are not distinguishable by type or material.	
	Assembly depth/thickness and locations still flexible.	

B3010

21-02 30 10

Roofing

Associated Masterformat Sections: 01 83 19

100	See <u>B30</u>	
200	Generic element representing roof exterior skin	
300	Specific element representing roof insulation and exterior skin modeled to actual dimensions.	
	Surface slopes (e.g. tapered insulation) are modeled to actual dimensions.	
	Penetrations are modeled to nominal dimensions for major wall openings such as skylights, and large mechanical elements.	
350	All penetrations are modeled at actual rough-opening dimensions.	
	Flashing	

B3010.10 21-02 30 10 10 Steep Slope Roofing Includes: Lapped roofing shingles, shakes and roofing tiles, including fastening and flashing products and methods. Includes Roofing Supplementary Components as appropriate.

Associated Masterformat Sections: 01 83 19 / 07 30 00 / 07 31 00 / 07 32 00 / 07 41 00 07 61 00 / 07 63 00

See B3010

B3010.50 21-02 30 10 50 Low-Slope Roofing Includes: Membrane roofing of various types and protected membrane roofing, including fastening and flashing products. Includes Roofing Supplementary Components as appropriate.

Associated Masterformat Sections: 01 83 19 / 07 50 00 / 07 55 00 / 07 55 63 / 07 76 00

[See B3010]

B3010.70 21-02 30 10 70 Canopy Roofing Includes: Roofing of various types over canopies. Includes Roofing Supplementary Components as appropriate.

Associated Masterformat Sections:

[See B1020]

B3010.70 21-02 30 10 70 Canopy Roofing

Includes: Roofing of various types over canopies. Includes Roofing Supplementary Components as appropriate.

Associated Masterformat Sections:

[See <u>B3010.10</u> or <u>B3010.50</u>]

B3010.90 21-02 30 10 90

Roofing Supplementary Components

Includes: substrate boards, vapor retarder, air barriers, deck insulation, flashing and sheet metal, and expansion joints to be included with roofing elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 07 22 00 / 07 26 00 / 07 27 00 / 07 62 00 / 07 65 00 07 71 13 / 07 71 16 / 07 71 19 / 07 71 29 / 09 28 00

B3020 21-02 30 20 Roof Appurtenances

Includes: Roof specialties and accessories installed on or in roofing or traffic bearing horizontal enclosure systems. Includes components for the management of rainwater, but excludes mechanical and structural items.

Associated Masterformat Sections:

100	See <u>B30</u>	
200	See Fundamental LOD Definitions	

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

B3020.10 21-02 30 20 10 Roof Accessories

Includes: Ladders, curbs, vents, walkways, and snow guards.

Associated Masterformat Sections: 05 51 33 / 07 72 00 / 07 72 13 / 07 72 23 / 07 72 26 07 72 46 / 07 72 53

100	See <u>B30</u>	
200	See Fundamental LOD Definitions	
300	Ladders: Specific assemblies indicating length and width. Required access/clearance space is modeled or accommodated by model checking software.	
	Walkways: Specific assemblies indicating length, width, and rail/guard height.	
	<u>Vents</u> : Specific assemblies indicating roof opening size. Roof opening element is included. Required service access space is modeled or accommodated by model checking software.	
350	Ladders: Specific assemblies indicating length, width, and attachment/anchoring members.	
	Walkways: Specific assemblies indicating length, width, rail/guard height, and support/attachment/anchoring members.	
	<u>Vents</u> : Specific assemblies indicating roof opening size and attachment/anchoring members if applicable.	
400	See Fundamental LOD Definitions	

B3020.30

21-02 30 20 30

Roof Specialties

Includes: Cupolas, spires, steeples, and weathervanes.

Associated Masterformat Sections: 10 74 00 / 10 74 23 / 10 74 26 / 10 74 29 / 10 74 33

[See Fundamental LOD Definitions]

B3020.70 21-02 30 20 70

Rainwater Management

Includes: Components to manage rain water from roofing and traffic bearing horizontal enclosures. Includes: Conductor heads, gutters, downspouts, scuppers, and splash blocks.

Associated Masterformat Sections: 07 71 23 / 07 71 33 / 03 48 16

[See <u>D2030.10</u> and <u>D2030.20</u>]

B3040

21-02 30 40

Traffic Bearing Horizontal Enclosures

Includes: Horizontal enclosures that are also traffic bearing. Includes Horizontal Enclosure Supplementary Components as appropriate.

Associated Masterformat Sections: 01 83 16

100	See <u>B30</u>	
200	See <u>B3010</u>	

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

B3040.10 21-02 30 40 10 Traffic Bearing Coatings

Includes: Surface applied waterproofing exposed to weather and suitable for pedestrian or vehicular traffic.

Associated Masterformat Sections: 07 18 00

B3040.30

21-02 30 40 30

Horizontal Waterproofing Membrane

Includes: Substrate board, deck insulation, vapor retarder, sheet metal flashing and trim, flexible flashing, and expansion joints.

Associated Masterformat Sections: 07 10 00

100	See <u>B30</u>	
200	See <u>B3040</u>	
300	Membrane assembly modeled by type to specified thickness.	
	Major openings such as shafts and hatches are modeled.	
350	Individual material layers of membrane assembly are modeled separately.	
	All openings and penetrations are modeled.	
	Expansion joints are modeled indicating specific width.	

B3040.50 21-02 30 40 50 Wear Surfaces

Includes: Wearing surfaces on top of horizontal waterproofing membrane that are suitable for pedestrian or vehicular traffic.

Associated Masterformat Sections: 07 76 00 / 32 13 00 / 32 14 00

100	See <u>B30</u>	
200	See <u>B3040</u>	
300	Wear surface system modeled by type to specified thickness/depth. Major openings such as shafts and hatches are modeled.	
350	Individual system elements are modeled separately. Pedestals are modeled and located properly, if applicable. Expansion joints are modeled indicating specific width.	

B3040.90

21-02 30 40 90

Horizontal Enclosure Supplementary Components

Includes: Substrate board, deck insulation, vapor retarder, sheet metal flashing and trim, flexible flashing, and expansion joints to be included with horizontal enclosure elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 07 20 00 / 07 26 00 / 07 62 00 / 07 65 00 / 07 71 13 07 71 16 / 07 71 19 / 07 71 29 / 09 28 00

B3060 21-02 30 60

Horizontal Openings

Includes: Openings in horizontal enclosures including roofing and traffic bearing horizontal enclosures. Includes Horizontal Opening Supplementary Components as appropriate.

Associated Masterformat Sections:

Γ	100	See <u>B30</u>	
	200	See <u>B2020</u>	

B3060.10 21-02 30 60 10 Roof Windows and Skylights

Includes: Operable and non-operable roof windows. Includes: Skylights without framing with plastic and glass glazing. Includes: Skylights with framing.

Associated Masterformat Sections: 01 83 16 / 08 60 00 / 08 61 00 / 08 62 00 / 08 63 00 08 64 00 / 08 67 00

[See <u>B2020.10</u>]

B3060.50 21-02 30 60 50 Vents and Hatches

Includes: Other roof openings such as roof hatches, smoke vents, and gravity roof ventilators.

Associated Masterformat Sections: 07 72 33 / 07 72 36

[See <u>B3020.10</u>]

B3060.90 21-02 30 60 90 Horizontal Opening Supplementary Components

Includes: Frames, hardware, glazing, flashing, and joint sealants to be included with horizontal opening elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 08 75 00 / 08 80 00 / 07 60 00 / 07 92 00

B3080

21-02 30 80

Overhead Exterior Enclosures

Includes: Exposed to weather construction under horizontal enclosure construction. Includes suspension and support systems, insulation, vapor retarders, and air barriers.

Associated Masterformat Sections: 01 83 16

100	See <u>B30</u>	
200	Generic assemblies indicative of overall scope and approximate thickness/system depth of overhead enclosure.	

B3080.10

21-02 30 80 10

Exterior Ceilings

Associated Masterformat Sections: 07 42 00 / 07 44 00 / 09 20 00 / 09 54 00 / 09 56 00 09 90 00

100	See <u>B30</u>	
200	See <u>B3080</u>	

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

300	Overall assembly modeled to specific system thickness including structural backing.	
	Location of expansion or control joints indicated, but not modeled.	
350	Face material modeled to specific thickness.	
	Structural backing members including bracing/lateral framing/kickers are modeled.	
	Expansion or control joints are modeled to indicate specific width.	

400	Individual elements of face material are modeled.	
	Structural backing members and all support members (kickers) are modeled including all connections.	
	Expansion or control joints are modeled.	

B3080.20 21-02 30 80 20 Exterior Soffits

Associated Masterformat Sections: 07 42 93 / 07 44 00 / 08 95 13 / 09 20 00 / 09 54 00 09 56 00 / 09 90 00

[See <u>B3080.10</u>]

B3080.30 21-02 30 80 30 Exterior Bulkheads Associated Masterformat Sections: 07 42 00 / 07 44 00 / 09 20 00 / 09 54 00 / 09 56 00 09 90 00

[See <u>B3080.10</u>]

I



INTERIORS

Associated Masterformat Sections: 01 84 00

C10

С

21-03 10

21-03

Interior Construction

Associated Masterformat Sections: 01 84 13

100	A schematic model element or symbol that is not distinguishable by type or material.	
	Types, layouts, and locations are still flexible.	

C1010 21-03 10 10 Interior Partitions

Includes: Enclosures and partitions which are fixed and secured in place. Includes walls of concrete; and masonry; and wood and metal stud partitions with associated wall surfaces. Includes partitions of an open nature, such as wire mesh partitions. Partitions may be load bearing or non-load bearing. Includes Interior Partition Supplementary Components as appropriate.

Associated Masterformat Sections: 10 22 00 / 01 84 13

100	See <u>C10</u>	
200	Generic wall objects separated by type of material (e.g. gypsum board vs. masonry).	
	Approximate overall wall thickness represented by a single assembly.	
	Layouts, locations, heights, and elevation profiles are still flexible.	

C1010.10 21-03 10 10 10

Interior Fixed Partitions

Includes: Enclosures and partitions which are fixed and secured in place. Includes walls of concrete; and masonry; and wood and metal stud partitions with associated wall surfaces. Includes partitions of an open nature, such as wire mesh partitions. Partitions may be load bearing or non-load bearing. Includes Interior Partition Supplementary Components as appropriate.

Associated Masterformat Sections: 03 30 00 / 03 40 00 / 04 20 00 / 05 41 00 / 06 11 00 / 09 20 00 / 10 22 13

See C10 100 See C1010 200 Composite model assembly by type with overall thickness that 300 accounts for framing and finish specified for the wall system. (Refer to LOD350 and LOD400 for individually modeled elements) Wall elements are modeled to specific layouts, locations, heights, and elevation profiles. Penetrations are modeled to nominal dimensions for major wall openings such as windows, doors, and large mechanical elements. Structure and finish layers of partition assembly modeled as 350 separate elements.

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

	All penetrations are modeled at actual rough-opening dimensions.	
	Major framing elements such as king studs, kickers, diagonal bracing, and headers are modeled.	
400	Element modeling to include: Studs and tracks Bracing Insulation Sheathing or wall boards Openings/penetrations 	


C1010.10.10 21-03 10 10 10 10 Interior Wall (Masonry)

Includes: Enclosures and partitions which are fixed and secured in place. Includes walls of concrete; and masonry; and wood and metal stud partitions with associated wall surfaces. Includes partitions of an open nature, such as wire mesh partitions. Partitions may be load bearing or non-load bearing. Includes Interior Partition Supplementary Components as appropriate.

Associated Masterformat Sections: 10 22 00 / 01 84 13

100	See <u>C10</u>	
200	See <u>C1010</u>	
		99 C1010.04-LOD-200 Interior Wall (Masonry)

Г	300	See <u>C1010.10</u>	
	300		100 C1010.04-LOD-300 Interior Wall (Masonry)
	350	 Element modeling to include: Members modeled at any interface with wall edges (top, bottom, sides) or opening through wall All penetrations are modeled at actual rough-opening dimensions. Any regions that would impact coordination with other systems such as but not limited to: Bond Beam & Lintel Regions Reinforcing & Embed Regions Jam Regions 	101 C1010.04-LOD-350 Interior Wall (Masonry)



Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

C1010.10.20 21-03 10 10 10 20 Interior Wall (Cold-Form Metal Framing)

Includes: Enclosures and partitions which are fixed and secured in place. Includes walls of concrete; and masonry; and wood and metal stud partitions with associated wall surfaces. Includes partitions of an open nature, such as wire mesh partitions. Partitions may be load bearing or non-load bearing. Includes Interior Partition Supplementary Components as appropriate.

Associated Masterformat Sections: 10 22 00 / 01 84 13

100	See <u>C10</u>	



200	See <u>C1010</u>	103 C1010.05-LOD-200 Interior Wall (Cold-Form Metal Framing)
300	See <u>C1010.10 C1010.10</u>	104 C1010.05-LOD-300 Interior Wall (Cold-Form Metal Framing)

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

350	 Cold formed metal framing is developed with sufficient elements to support detailed interface coordination with other systems such as MEP. All penetrations are modeled at actual rough-opening dimensions. Image notes: Elements in red are critical wall support elements that cannot be easily cut for coordination of MEP opening through the walls. Diagonal bracing (kickers) that may be in the above ceiling space are modeled for coordination with other building content such as MEP passing along the wall in the above ceiling spaces. Infill CFMF modeling (Orange) may be omitted at this LOD if stated in the BXP. Cladding and sheathing are not shown for clarity in this image. 	105 C1010.05-LOD-350 Interior Wall (Cold-Form Metal Framing)
-----	--	--

400	 Cold formed metal framing is developed with sufficient elements that support the fabrication of the CFMF system. <i>Image notes:</i> Connection content is development in the wall elements. This includes but is not limited to fasteners, clips, and other related hardware. Cladding and sheathing are not shown for clarity in this image. 	
		106 C1010.05-LOD-400 Interior Wall (Cold-Form Metal Framing)

C1010.10.30 21-03 10 10 10 30 Interior Wall (Wood)

Includes: Enclosures and partitions which are fixed and secured in place. Includes walls of concrete; and masonry; and wood and metal stud partitions with associated wall surfaces. Includes partitions of an open nature, such as wire mesh partitions. Partitions may be load bearing or non-load bearing. Includes Interior Partition Supplementary Components as appropriate.

Associated Masterformat Sections: 10 22 00 / 01 84 13

100	See <u>C10</u>	
-----	----------------	--

200	See <u>C1010</u>	
		107 C1010.06-LOD-200 Interior Wall (Wood)
300	See <u>C1010</u>	
		108 C1010.06-LOD-300 Interior Wall (Wood)

350	 Wood framing is developed with sufficient elements to support detailed interface coordination with other systems such as MEP. All penetrations are modeled at actual rough-opening dimensions. <i>Image notes:</i> Elements in red are critical wall support elements that cannot be easily cut for coordination of MEP opening through the walls. Infill wood framing modeling may be omitted at this LOD if stated in the BXP. Cladding and sheathing are not shown for clarity in this image. 	109 C1010.06-LOD-350 Interior Wall (Wood)
400	 Wood framing is developed with sufficient elements that support the fabrication of the wood framing system. Openings and penetrations through studs are modeled. <i>Image notes:</i> Connection content is development in the wall elements. This includes but is not limited to fasteners, anchor rods, and other related hardware. Cladding and sheathing are not shown for clarity in this image. 	Image: Note of the second se

Back to TOC

C1010.20 21-03 10 10 20 Interior Glazed Partitions

Includes: Partitions primarily composed of glazed elements that may be fabricated or field constructed. Includes Interior Partition Supplementary Components as appropriate.

Associated Masterformat Sections: 08 43 00

100	See <u>C10</u>
200	See <u>C1010</u>
300	Specified location and orientation of face of glass.
	Nominal face dimensions and thickness of glazing.
	Structural support systems of wall to be modeled.
	Spacing, location, size and orientation of mullions.
	Operable components defined (doors) and included in model.
350	 Mullion shapes and geometry defined. Actual anchorage layouts and types defined. Actual panel dimensions (including seating).
400	 Complete mullion extrusion profiles. Interface details between wall systems (within) and wall and support systems.

C1010.40

21-03 10 10 40

Interior Demountable Partitions

Associated Masterformat Sections: 10 22 19 / 01 84 13 / 10 22 19.13 / 10 22 19.23 / 10 22 19.33 10 22 19.43 / 10 22 19.53

100	See <u>C10</u>	
200	See <u>C1010</u>	
300	See <u>C1010.10</u>	
350	See <u>C1010.10</u> – also include hardware, accessories, and support structure.	
400	See <u>C1010.10</u>	

C1010.50 21

21-03 10 10 50

Interior Operable Partitions

Includes: Track-supported, operable panels and partitions, top hung and floor supported, and manually and power operated. Includes auditorium partitions and dividers. Includes overhead supports.

Associated Masterformat Sections: 01 84 13 / 01 84 13 / 10 22 33 / 10 22 36 / 10 22 39 10 22 43

100	See <u>C10</u>	
200	See <u>C1010</u>	

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

300	Operable partition system modeled to include spatial requirements for open/storage position and closed position. Spatial requirements for structure (overhead or below) to be modeled.	
350	Major support elements (overhead or below) Mechanical connections	
400	All assembly components including tracks, panels, hardware and supports.	

C1010.70 21-03 10 10 70 Interior Screens *Portable and open dividers.*

Associated Masterformat Sections: 10 22 23 / 10 82 23

[See <u>C1010.10</u>]

C1010.90 21-03 10 10 90 Interior Partitions Supplementary Components

Sound isolation components, firestopping, and expansion control to be included with interior partition elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 13 48 00 / 09 81 00 / 07 84 00 / 07 95 00

C1020

21-03 10 20

Interior Windows

Includes: Interior fixed or operable windows used singly and in multiples. Includes Interior Window Supplementary Components as appropriate. Includes metal, wood, plastic, and composite window units.

Associated Masterformat Sections: 08 50 00 / 01 84 13

100	See <u>C10</u>	
200	Windows approximate in terms of location, size, count and type. Units are modeled as a simple, monolithic component; or represented with simplified frame and glazing. Nominal unit size is provided.	

C1020.10 21-03 10 20 10

Interior Operating Windows

Includes: Interior fixed or operable windows used singly and in multiples. Includes Interior Window Supplementary Components as appropriate. Includes metal, wood, plastic, and composite window units.

Associated Masterformat Sections: 08 50 00

100	See <u>C10</u>	
200	See <u>C1020</u>	

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

300	Units are modeled based on specified location and nominal size. Outer geometry of window frame elements and glazing modeled.	
	Operation is indicated.	
	Non-graphic information associated with model element:	
	Aesthetic characteristics (finishes, glass types) Performance characteristics (i.e. U-value, wind loading, blast resistance, structural, air, thermal, water, sound) Functionality of the window (fixed, casement, double/single hung, awning/project out, pivot, sliding)	
350	Attachment method of window to structure	
	Embed geometry	
400	Frame profiles	
	Glazing sub-components (gaskets)	
	Attachment components	

C1020.20 21-03 10 20 20 Interior Fixed Windows

Includes: Interior fixed or operable windows used singly and in multiples. Includes Interior Window Supplementary Components as appropriate. Includes metal, wood, plastic, and composite window units.

Associated Masterformat Sections: 08 50 00

C1020.50 21-03 10 20 50 Interior Special Function Windows

Includes interior windows with special characteristics for a special function.

Associated Masterformat Sections: 08 56 00 / 08 56 19 / 08 56 46 / 08 56 49 / 08 88 49 / 08 56 53 / 08 88 53 / 08 88 56 / 08 56 63 / 08 56 73

C1020.90 21-03 10 20 90 Interior Window Supplementary Components

Includes: Frames, sills, operating hardware, glazing to be included with interior window elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 08 75 00 / 08 80 00

C1030 21-03 10 30

Interior Doors

Includes: Interior door assemblies. Includes metal doors and frames, wood doors and frames, plastic doors, and composite doors. Includes Interior Door Supplementary Components as appropriate.

Associated Masterformat Sections: 08 10 00 / 01 84 13

100	See <u>C10</u>	
200	Units are modeled as a simple, monolithic component; or represented with simple frame and panel. Nominal unit size is provided.	

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

C1030.10 21-03 10 30 10 Interior Swinging Doors

Includes: Interior door assemblies. Includes metal doors and frames, wood doors and frames, plastic doors, and composite doors. Includes Interior Door Supplementary Components as appropriate.

Associated Masterformat Sections: 08 10 00

100	See <u>C10</u>	
200	See <u>C1030</u>	
300	Door assemblies modeled by type to include the following:	
	Specific door panels and frames (if applicable).Operation is specified	
350	Major framing elements are modeled at jambs and head in containing wall.	
	Operation or mechanism enclosures are modeled, if applicable.	
400	Actual frame/mullion extrusions.	
	Actual panel size dimensions.	
	All connections and interfaces modeled including brackets, supports, sealants, and thresholds.	

C1030.20 21-03 10 30 20 Interior Entrance Doors

Includes: Exterior personnel door assemblies at interior main entrances. Includes automatic, revolving, balanced, and other special operating entrance doors, and sliding storefront wall systems. Includes Interior Door Supplementary Components as appropriate when not part of storefront system.

Associated Masterformat Sections: 08 42 00 / 08 42 26 / 08 42 29 / 08 42 33 / 08 42 36 08 43 29

[See <u>B2050.10</u>]

C1030.25 21-03 10 30 25 Interior Sliding Doors Associated Masterformat Sections: 08 11 73 / 08 32 00

[See <u>C1030.10</u>]

C1030.30	21-03 10 30 30	Interior Folding Doors
Associated Master	format Sections: 08 35 13	

[See C1030.10]

C1030.40 21-03 10 30 40 Interior Coiling Doors Associated Masterformat Sections: 08 33 00 / 08 33 13

100	See <u>C10</u>
200	See <u>C1030</u>
300	Coiling door assemblies modeled by type to include the following:
	Door panels with nominal dimensions.

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

	 Frames with nominal dimensions. Hardware set functionality and types included in non- graphic information. Clearance zones for operation of overhead doors are modeled or accommodated by model checking software. Enclosures and motor housings are modeled with overall nominal dimensions. 	
350	Major framing elements in wall are modeled at jambs and head.	
	Other major structural support elements are modeled.	
400	All connections and interfaces modeled including brackets, supports, sealants, and thresholds.	

C1030.50 21-03 10 30 50 Interior Panel Doors

Includes: Interior large opening doors constructed of panels that move.

Associated Masterformat Sections: 08 36 00 / 08 36 13 / 08 36 16 / 08 36 19 / 08 36 23

[See <u>C1030.40</u>]

C1030.70 21-03 10 30 70 Interior Special Function Doors

Includes: Interior door assemblies for a variety of special functions and applications involving a variety of operating methods. Includes Interior Door Supplementary Components as appropriate.

Associated Masterformat Sections: 08 30 00. / 08 34 13 / 08 34 19 / 08 34 33 / 08 34 36 08 34 46 / 08 34 49 / 08 88 49 / 08 34 53 / 08 42 33.13 / 08 88 53 / 08 88 56 / 08 34 59 08 34 63 / 08 34 73 / 08 38 00 / 08 39 00

[See <u>C1030.40</u>]

C1030.80 21-03 10 30 80 Interior Access Doors and Panels Includes: Doors and panels in walls, ceilings, and floors to provide access to concealed spaces. Includes frames and hardware.

Associated Masterformat Sections: 08 31 00

[See <u>C1030.40</u>]

C1030.90 21-03 10 30 90 Interior Door Supplementary Components

Includes: Frames, hardware, glazing, and louvers that are part of door to be included with interior door elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 08 10 00 / 08 30 00 / 08 71 00 / 08 80 00 / 08 91 26

C1040 21-03 10 40 Interior Grilles and Gates

Includes: Interior operable grilles and gates Includes frames and hardware.

100	See <u>C10</u>	
200	See <u>C1030</u>	

C1040.10 21-03 10 40 10 Interior Grilles

Associated Masterformat Sections: 08 11 74 / 08 33 00 / 08 35 16

100	See <u>C10</u>
200	See <u>C1030</u>
300	Grille assemblies modeled by type to include the following:
	 Nominal size of unit. Required openness provided as non-graphic information. Operation is specified graphically.
350	Major framing elements are modeled at jambs and head.
400	All connections and interfaces modeled including brackets, supports, sealants, and thresholds.

C1040.50 21-03 10 40 50 Interior Gates

Includes: Interior devices of solid or open construction, usually hinged, to provide moveable barrier for access through partition or other divider. Includes hardware, accessories, and finishing. Associated Masterformat Sections: 08 34 56 / 10 22 16

[See <u>C1040.10</u>]

C1060 21-03 10 60 Raised Floor Construction

Associated Masterformat Sections: 01 84 13 / 01 84 13 / 01 84 13 / 01 84 13 / 01 84 13 / 01 84 13 / 01 84 13 / 01 84 13 / 01 84 13 / 01 84 13

100	See <u>C10</u>	
200	Generic assembly that contains spatial allowance for support system and flooring material.	

C1060.10 21-03 10 60 10 Access Flooring

Includes: Free-standing, elevated accessible floor assembly forming an underfloor cavity that may be used for utility or other purposes. Associated Masterformat Sections: 09 69 00

Back to TOC

100	See <u>C10</u>	
200	See <u>C1060</u>	
300	Overall flooring assembly modeled by type to specified thickness/depth. Major openings such as shafts are modeled.	
350	Individual layers of assembly are modeled separately. All openings and penetrations are modeled. Expansion joints are modeled indicating specific width. Pedestals are modeled and located properly, if applicable.	
400	All assembly components are modeled including frame, floor tiles, pedestals, and cross bracing.	

C1060.30 21-03 10 60 30 Platform/Stage Floors

Includes: Fixed construction of raised floor for platforms or stages. [See <u>C1060.10</u>]

Suspended Ceiling Construction C1070 21-03 10 70

Includes: Ceiling Suspension Components.

Associated Masterformat Sections: 01 84 13 / 01 84 13

100	Ceiling construction is represented in other composite objects such as floors or rooms; or, schematic model elements that are not distinguishable by type or material. Assembly depth/thickness and locations still flexible.	
200	Generic assemblies indicative of overall scope and approximate thickness/system depth of suspended ceiling.	

C1070.10 21-03 10 70 10 Acoustical Suspended Ceilings

Includes: Suspended tiles and panels with specific characteristics for acoustical purposes.

Associated Masterformat Sections: 09 51 00 / 09 81 00

100	See <u>C1070</u>	
200	See <u>C1070</u>	
300	Overall assembly modeled to specific system thickness including structural backing. Location of expansion or control joints indicated, but not modeled.	

Back to TOC

	Ceiling grid is shown as linework.	
350	Ceiling suspension grid is modeled.	
	Structural backing members including bracing/lateral framing/kickers are modeled.	
	Expansion or control joints are modeled to indicate specific width.	
400	All assembly components are modeled including tees, hangers, support structure, and tiles.	

C1070.20 21-03 10 70 20 Suspended Plaster and Gypsum Board Ceilings Includes: Suspended assemblies with plaster and gypsum board surfaces.

Associated Masterformat Sections: 09 20 00 / 09 22 26 / 09 81 00

100	See <u>C1070</u>	
200	See <u>C1070</u>	
300	Overall assembly modeled to specific system thickness including framing.	
	Bulkheads	
	Major penetrations are modeled.	
350	Major bracing elements such as kickers are modeled.	
400	All assembly components including furring channels, hangers, lath, plaster coats, and gypsum boards.	

C1070.50 21-03 10 70 50 Specialty Suspended Ceilings

Includes: Suspended specialty ceiling panels, units, and materials manufactured as finished

Associated Masterformat Sections: 09 54 00 / 09 56 00

[See <u>C1070.10</u> or <u>C1070.20</u>]

C1070.70 21-03 10 70 70 Special Function Suspended Ceilings

Includes: Suspended ceiling assemblies with an additional special function including integrated ceiling assemblies.

Associated Masterformat Sections: 09 57 00 / 09 57 53 / 09 58 00

[See <u>C1070.10</u> or <u>C1070.20</u>]

C1070.90 21-03 10 70 90 Ceiling Suspension Components

Includes: Hangers and framing to suspend ceiling and sound isolation components to be included with suspended ceiling construction elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 13 48 00

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

C1090	21-03 10 90	Interior Specialties
100	See <u>C10</u>	
200	Generic model elements with approx	ximate nominal size.
	Placement and quantity remains flex	kible.

C1090.10 21-03 10 90 10 Interior Railings and Handrails

Includes: Complete interior railing assemblies of various types including glazed railings.

Associated Masterformat Sections: 01 84 00 / 01 84 00 / 01 84 00 / 01 84 00 / 05 52 00 05 73 00 / 06 43 16 / 06 63 00 / 06 81 00

100	See <u>C10</u>	
200	Generic model element representing approximate overall height and location of railing/handrail.	
300	 Railing/handrail systems modeled by type to include: All horizontal rails All vertical posts/balusters 	
350	Mounting/attachment components	
400	All assembly components including fasteners and supports.	

C1090.15 21-03 10 90 15 Interior Louvers

Includes: Interior louvers, and other items for ventilation which are not an integral part of the mechanical system. Includes operable and stationary louvers.

Associated Masterformat Sections: 08 91 00 / 01 84 00

100	See <u>C10</u>	
200	Generic model element that is indicative of approximate area and location of louver.	
300	Louver assembly modeled by type, indicative of area and location of intended louver/vent. Accurate frame and blade boundary areas	
	Opening for louver is cut from host wall.	
350	Rough opening is modeled in containing wall.	
	Major framing elements are modeled at jambs and head.	
	Connection points are modeled.	
400	All connections and interfaces modeled including brackets, supports, and sealants.	

C1090.20 21-03 10 90 20 Information Specialties Includes: Visual display units, display cases, directories, interior signage, telephone specialties, and informational kiosks.

nciudes: visual display units, display cases, directories, interior signage, telephone specialities, and informational klosks

Associated Masterformat Sections: 10 10 00 / 10 11 00 / 10 11 13 / 10 11 16 / 10 11 23 10 11 33 / 10 11 36 / 10 11 39 / 10 11 43 / 10 11 46 / 10 12 00 / 10 13 00 / 10 14 00 10 17 00 / 10 18 00

[See Fundamental LOD Definitions]

C1090.25 21-03 10 90 25 Compartments and Cubicles Includes: Manufactured compartments and cubicles for specific purposes. Includes toilet compartments, shower stalls, etc. Associated Masterformat Sections: 10 21 00 / 10 21 13 / 10 21 16 / 10 21 23 / 10 28 19

[See Fundamental LOD Definitions]

C1090.30 21-03 10 90 30 Service Walls Includes: Wall assemblies and wall-mounted units incorporating services. Associated Masterformat Sections: 10 25 00 / 10 25 13 / 10 25 16

[See C1010.10]

C1090.35 21-03 10 90 35 Wall and Door Protection

Includes: Manufactured protective devices for walls and doors. Includes corner guards, bumper guards, and protective wall covering.

Interior Gas Lighting

Associated Masterformat Sections: 10 26 00 / 10 26 13 / 10 26 16 / 10 26 23 / 10 26 33

[See Fundamental LOD Definitions]

C1090.40 21-03 10 90 40 Toilet, Bath and Laundry Accessories Includes: Manufactured items for use in conjunction with toilets, baths, and laundries.

Associated Masterformat Sections: 10 28 00 / 10 28 13 / 10 28 16 / 10 28 23

[See Fundamental LOD Definitions]

C1090.45 21-03 10 90 45 Associated Masterformat Sections: 10 84 16

[See Fundamental LOD Definitions]

C1090.50 21-03 10 90 50 Fireplaces and Stoves

Includes: Masonry fireplaces and manufactured and fabricated fireplaces, stoves, chimneys, dampers, and specialties for use in construction of fireplaces and stove units. Associated Masterformat Sections: 10 30 00 / 04 50 00 / 04 57 00 / 10 31 00 / 10 31 13 10 32 00 / 10 35 00

[See Fundamental LOD Definitions]

Back to TOC

C1090.60 21-03 10 90 60 Safety Specialties

Includes: Accessories that provide emergency aid. Associated Masterformat Sections: 10 40 00 / 10 41 00 / 10 43 00

[See Fundamental LOD Definitions]

C1090.70 21-03 10 90 70 Storage Specialties

Includes: Lockers, postal specialties, storage specialties, and wardrobe and closet specialties. Associated Masterformat Sections: 105000 / 105100 / 105153 / 105500 / 105523 / 105591 / 105600 / 105629 / 105633 / 105700 / 105713 / 105733

[See Fundamental LOD Definitions]

C1090.90 21-03 10 90 90 Other Interior Specialties

Includes: Pest control devices, flags and banners, security mirrors and domes, and scales. Associated Masterformat Sections: 10 80 00 / 10 81 00 / 10 81 16 / 10 81 19 / 10 83 00 / 08 83 00 / 10 86 00 / 10 88 00

[See Fundamental LOD Definitions]

\cap	0	n
C	Ζ	U

21-03 20

Interior Finishes

Associated Masterformat Sections: 01 84 19

100	Non-graphic information attached to model elements providing	
	assumptions about proposed finish materials. See Part II	

C2010 21-03 20 10 Wall Finishes

Includes: Wall finishes applied over solid substrates. Includes Wall Finish Supplementary Components as appropriate.

Associated Masterformat Sections: 09 70 00 / 01 84 19 / 01 84 19 / 01 84 19 / 01 84 19 / 01 84

100	See <u>C20</u>	
200	Generic materials other than sheet goods and coatings by type (e.g. tile or paneling), approximate thickness and scope in elevation.	
300	Materials are modeled based on specific types (e.g. Tile type CT-1).	
	Thickness and scope of finishes other than sheet goods and coatings are accurately modeled.	

Back to TOC

	Sheet goods and coatings may be specified in Part II related to interior partitions.	
350	Additional non-graphic information to include:	
	ManufacturerModel	
400	Pattern layouts	
	Expansion/control joints	
	Edges	

C2010.10 21-03 20 10 10 Tile Wall Finish

Includes: Manufactured surfacing units of impervious, vitreous, semi-vitreous, and non-vitreous materials; glazed, unglazed, conductive, and textured surfaces.

Associated Masterformat Sections: 09 30 00

[See <u>C2010</u>]

C2010.20 21-03 20 10 20 Wall Paneling

Includes: Covering or cladding of interior walls with paneling. Includes associated furring, fastening, and trim.

Associated Masterformat Sections: 06 42 00 / 06 25 00 / 06 26 00 / 06 64 00 / 06 83 00

[See <u>C2010</u>]

C2010.30 21-03 20 10 30 Wall Coverings

Includes: Wall coverings applied over solid substrates. Includes vinyl-coated fabric, vinyl and cork wall coverings; wall papers; and flexible wood sheets.

Associated Masterformat Sections: 09 72 00 / 09 74 00

[See <u>C2010</u>]

C2010.35 21-03 20 10 35 Includes: Wall carpet materials and accessories. Wall Carpeting

Associated Masterformat Sections: 09 73 00

C2010.50 21-03 20 10 50 Stone Facing Includes: Natural stone applied as an interior veneer surface.

Associated Masterformat Sections: 09 75 00

[See <u>C2010</u>]

C2010.60 21-03 20 10 60 Special Wall Surfacing Includes: Manufactured decorative interior wall surface products including plastic blocks.

Associated Masterformat Sections: 09 77 00 / 09 77 13 / 09 77 23 / 09 76 00

[See <u>C2010</u>]

Back to TOC

C2010.70 21-03 20 10 70 Wall Painting and Coating

Includes: Interior painting and coating with transparent and opaque finishes. Includes stains, varnishes, lacquers, primers, fillers, paint removers, and waxes, and preparation of surfaces.

Associated Masterformat Sections: 09 90 00

[See <u>C2010</u>]

C2010.80 21-03 20 10 80 Acoustical Wall Treatment Includes: Sound absorbing, reflecting, and diffusing wall units, and accessories.

Associated Masterformat Sections: 09 83 13 / 09 84 00 / 09 84 33

[See <u>C2010</u>]

C2010.90 21-03 20 10 90 Wall Finish Supplementary Components Includes: Furring to be included with wall finish elements above as appropriate.

Associated Masterformat Sections: 06 10 00 / 09 22 13

[See <u>C1010</u>]

C2020 21-03 20 20 Interior Fabrications

Includes: Interior fabrications of a variety of materials formed to various profiles for a variety of purposes including column covers.

Associated Masterformat Sections: 03 49 00 / 05 50 00 / 05 58 13 / 05 70 00 / 06 44 00 / 06 60 00 / 06 61 00 / 06 80 00 / 09 27 00

[See Fundamental LOD Definitions]

C2030 21-03 20 30 Flooring

Includes: Flooring Supplementary Components as appropriate.

Associated Masterformat Sections: 09 60 00 / 01 84 19

[See <u>C2010</u>]

Uniformat	Omniclass		
C2030.10	21-03 20 30 10	Flooring Treatment	TBD
C2030.20	21-03 20 30 20	Tile Flooring	TBD
C2030.30	21-03 20 30 30	Specialty Flooring	TBD
C2030.40	21-03 20 30 40	Masonry Flooring	TBD
C2030.45	21-03 20 30 45	Wood Flooring	TBD
C2030.50	21-03 20 30 50	Resilient Flooring	TBD
C2030.60	21-03 20 30 60	Terrazzo Flooring	TBD
C2030.70	21-03 20 30 70	Fluid-Applied Flooring	TBD
C2030.75	21-03 20 30 75	Carpeting	TBD
C2030.80	21-03 20 30 80	Athletic Flooring	TBD
C2030.85	21-03 20 30 85	Entrance Flooring	TBD
C2030.90	21-03 20 30 90	Floor Supplementary Components	TBD

C2040 21-03 20 40 Stair Finishes Includes: Stair tread, riser, and landing finish of various materials.

Associated Masterformat Sections: 01 84 19

[See <u>C2010]</u>

Uniformat	Omniclass		
C2040.20	21-03 20 40 20	Tile Stair Finish	TBD
C2040.40	21-03 20 40 40	Masonry Stair Finish 09 63 00	TBD
C2040.45	21-03 20 40 45	Wood Stair Finish 09 64 00	TBD
C2040.50	21-03 20 40 50	Resilient Stair Finish 09 65 00	TBD
C2040.60	21-03 20 40 60	Terrazzo Stair Finish 09 66 00	TBD
C2040.75	21-03 20 40 75	Carpeted Stair Finish 09 68 00	TBD

C2050 21-03 20 50

C2050 21-03 20 50 Ceiling Finishes Includes: Finishes applied to interior ceiling substrates. Ceiling finishes may be applied to suspended ceiling construction. Includes Ceiling Finish Supplementary Components as appropriate.

Associated Masterformat Sections: 09 50 00 / 01 84 19

C2050.10	21-03 20 50 10	Plaster and Gypsum Board Finish	TBD
C2050.20	21-03 20 50 20	Ceiling Paneling	TBD
C2050.70	21-03 20 50 70	Ceiling Painting and Coating	TBD
C2050.80	21-03 20 50 80	Acoustical Ceiling Treatment	TBD
C2050.90	21-03 20 50 90	Ceiling Finish Supplementary Components	TBD

1

D

Uniformat Omniclass

21-04 00 00 SERVICES

Associated Masterformat Sections: 01 86 00

D10 21-04 10 Conveying

Associated Masterformat Sections: 01 85 00 / 14 00 00

100	Schematic model elements that are not distinguishable by type or material.	
	Component sizes and locations still flexible.	

D1010 21-04 10 10 Vertical

Vertical Conveying Systems

Associated Masterformat Sections:

100	See <u>D10</u>	
200	Generic representation of the system envelope, including critical path of travel zones.	



D1010.10 21-04 10 10 10 Elevators

Includes: Passenger and freight elevators of all types, including cars, enclosures, controls, safety equipment, hoist way equipment, and elevator machinery. Includes associated metal fabrications including pit ladders.

Associated Masterformat Sections: 01 85 00 / 14 20 00 / 14 21 13 / 14 21 23 / 14 21 33 14 21 43 / 14 24 13 / 14 24 23 / 14 24 33 / 14 24 43 / 14 26 00 / 14 27 00 / 14 28 00

400	Case D10	
100	See <u>D10</u>	
200	See <u>D1010</u>	
		~



300	Specific system elements modeled by type, including all path of travel zones. Pits and/or control rooms and associated equipment to be modeled if applicable. Major structural support elements modeled. Connections to mechanical or electrical services.	
350	Sizing adjusted to the actual manufacturer specifications. Guiding tracks/rails Service/access zones	

Back to TOC

400	All connections, supports, framing, and other supplementary components.	
-----	---	--

D1010.20 21-04 10 10 20 Lifts Includes: Vertical or inclined lifts and related equipment for a variety of purposes. Sidewalk lifts include doors.

Associated Masterformat Sections: 01 85 00 / 14 40 00 / 14 41 00 / 14 42 00 / 14 43 00 14 43 13 / 14 43 16 / 14 44 00 / 14 45 00

[See <u>D1010.10</u>]

D1010.30 21-04 10 10 30 Escalators

Includes: Passenger conveying systems composed of moving treads installed in inclined position including associated components, hardware, controls, safety equipment, and related items.

Associated Masterformat Sections: 01 85 00 / 14 31 00

[See <u>D1010.10</u>]

D1010.50 21-04 10 10 50

Dumbwaiters

Includes: Packaged and field assembled, motorized and hand- operated dumbwaiters including associated components for book lifts, cart lifts, and other applications. Systems include associated components, hardware, controls, and safety equipment.

Associated Masterformat Sections: 01 85 00 / 14 10 00

Back to TOC

[See <u>D1010.10</u>]

D1010.60 21-04 10 10 60 Moving Ramps Includes: Passenger conveying systems composed of moving belts installed in inclined position including associated components, hardware, controls, safety equipment, and related items.

Associated Masterformat Sections: 01 85 00 / 14 33 00

[See <u>D1010.10</u>]

D1030 21-04 10 30 Associated Masterformat Sections: 01 85 00

Horizontal Conveying

[See D1010.10]

D1030.10 21-04 10 30 10 Moving Walks Includes: Passenger conveying systems composed of moving belts installed in horizontal position including associated components, hardware, controls, safety equipment, and related items.

Associated Masterformat Sections: 01 85 00 / 14 32 00

[See <u>D1010.10</u>]

D1030.30 21-04 10 30 30 Turntables Includes: Structural turntables for various applications.

Associated Masterformat Sections: 01 85 00 / 14 70 00 / 14 71 00 / 14 71 11 / 14 72 00 14 72 25 / 14 73 00 / 14 73 59 / 14 74 00 / 14 74 61

[See D1010.10]

D1030.50 21-04 10 30 50 Passenger Loading Bridges Includes: Operating bridges for loading and unloading of passengers to and from aircraft and ships.

Associated Masterformat Sections: 01 85 00 / 34 77 13

[See <u>D1010.10</u>]

D1030.70 21-04 10 30 70 P

People Movers

Includes: Single rail vehicles suspended from or straddle the guideway. Includes associated track, equipment, controls, and accessories. Includes: Steep cable railways in which ascending cars counterbalance descending cars. Includes associated track, cable. Includes: Steep slope transportation system utilizing moving cable. Includes associated cable, support structures, equipment, controls, and accessories.

Associated Masterformat Sections: 01 85 00 / 34 12 00 / 34 13 00 / 34 14 00

[See D1010.10]

D1050 21-04 10 50 Associated Masterformat Sections: 01 85 00 Material Handling

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>. 122

100	See <u>D10</u>	
200	Generic representation of the material handling system envelope, including critical path of travel zones.	

D1050.10 21-04 10 50 10 Cranes

Includes: Hoisting towers, cranes, crane rails, and related accessories.

Associated Masterformat Sections: 41 22 13

100	See <u>D10</u>	
200	See <u>D1050</u>	
300	Specific system elements modeled by type, including all path of travel/boom swing zones.	
	Lay-down/pick-up zones are modeled.	
	Major structural support elements modeled.	
	Connections to mechanical or electrical services.	
350	Sizing adjusted to the actual manufacturer specifications.	
	Guiding tracks/rails	
	Service/access zones	
400	All connections, supports, framing, and other supplementary components.	

D1050.20 21-04 10 50 20 Hoists Includes: Manual and motor operated hoists and related accessories.

Associated Masterformat Sections: 41 22 23

[See D1050.10]

D1050.30 21-04 10 50 30 Derricks Includes: Manual and motor operated derricks and related accessories.

Associated Masterformat Sections: 41 22 33

[See <u>D1050.10</u>]

D1050.40 21-04 10 50 40 Conveyors

Includes: Automatic guided vehicles, conveyors, diverters, and chutes. Includes controls and accessories.

Associated Masterformat Sections: 41 21 00

[See <u>D1050.10</u>]

21-04 10 50 50 Baggage Handling Equipment

Includes: Operating equipment for handling, scanning, and weighing of baggage at terminals. Includes controls and accessories.

Back to TOC

D1050.50

Associated Masterformat Sections: 34 77 16

100	See D10
200	See <u>D1050</u>
300	See <u>Fundamental LOD Definitions</u>
350	See Fundamental LOD Definitions
400	See Fundamental LOD Definitions

D1050.60 21-04 10 50 60 Chutes

Includes: Chutes which support the operation of the building or structure.

Associated Masterformat Sections: 14 91 00 / 14 91 13 / 14 91 23 / 14 91 33 / 14 91 82

[See <u>D1050.10</u>]

D1050.70 21-04 10 50 70 Pneumatic Tube Systems

Includes: Pneumatically operated tube system for the delivery of small items within a facility. Includes controls and accessories.

Associated Masterformat Sections: 14 92 00

100	Diagrammatic elements or quantitative call outs; conceptual and/or schematic flow diagrams;	
		111 D1050.70-LOD-100 Pneumatic Tube Systems
200	Generic elements; schematic layout with approximate size, shape, and location of equipment and tubing;	
		112 D1050.70-LOD-200 Pneumatic Tube Systems

300	Modeled as design-specified elements;	
000	specified size, shape, spacing, and location of equipment and tubing;	
	approximate allowances for spacing and clearances required for all specified hangers, supports, vibration and seismic control that are to be utilized in the layout of all equipment and tubing are modeled or accommodated by model checking software;	
	access/code clearance requirements modeled or accommodated by model checking software.	113 D1050.70-LOD-300 Pneumatic Tube Systems
350	Modeled as actual construction elements;	
	actual size, shape, spacing, and location/connections of equipment and tubing;	•
	actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all equipment and tubing are or accommodated by model checking software;	
	floor and wall penetrations modeled.	
	actual access/code clearance requirements modeled or accommodated by model checking software.	114 D1050.70-LOD-350 Pneumatic Tube Systems
400	Supplementary components added to the model required for fabrication and field installation	



Back to TOC

D1080 21-04 10 80

Associated Masterformat Sections:

[See Fundamental LOD Definitions]

D1080.10 21-04 10 80 10 Suspended Scaffolding Includes: Suspended scaffolding when part of the completed project.

Associated Masterformat Sections: 14 81 00

[See Fundamental LOD Definitions]

D1080.20 21-04 10 80 20 Rope Climbers Includes: Powered rope climbers to access exterior façade.

Associated Masterformat Sections: 14 82 00

[See See Fundamental LOD Definitions]

D1080.30 21-04 10 80 30 Elevating Platforms Includes: Fixed elevating platforms to provide a movable elevated working platform for people and materials.

Associated Masterformat Sections: 14 83 00

[See See Fundamental LOD Definitions]

D1080.40 21-04 10 80 40 Powered Scaffolding Includes: Powered scaffolding when part of the completed project.

Associated Masterformat Sections: 14 84 00 / 14 84 13

[See Fundamental LOD Definitions]

D1080.50 21-04 10 80 50 Associated Masterformat Sections: 11 24 23 **Building Envelope Access**

Operable Access Systems

[See Fundamental LOD Definitions]

D20

21-04 20

Plumbing

Associated Masterformat Sections: 01 86 16 / 22 00 00

100	Diagrammatic or schematic model elements;	
	conceptual and/or schematic layout/flow diagram;	
	design performance parameters as defined in the BXP to be associated with model elements as non-graphic information.	

D2010 21-04 20 10 Domestic Water Distribution

Includes: Facility domestic water distribution system. Include Domestic Water Distribution Supplementary Components as appropriate.

Associated Masterformat Sections: 01 86 16 / 22 11 00

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

100	See <u>D20</u>	
200	Schematic layout of generic model elements with approximate size, shape, and location of elements;	
	shaft requirements modeled;	

D2010.10 21-04 20 10 10 Facility Potable-Water Storage Tanks

Includes: Tanks for storage of potable water serving a facility and located within, on, under, or closely associated with a structure.

Associated Masterformat Sections: 22 12 00

100	See <u>D20</u>	
200	Schematic layout with approximate size, shape, and location of tank(s);	
		116 D2010.10-LOD-200 Facility Potable-Water Storage Tanks
300	Modeled as design-specified size, shape, spacing, and location of tank(s);	
	access/code clearance requirements and approximate allowances for spacing and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of tanks(s) are modeled or accommodated by model checking software;	
		117 D2010.10-LOD-300 Facility Potable-Water Storage Tanks
350	Modeled as actual construction elements <i>size and shape, spacing, and location</i> /connections of tank(s)	
	actual access/code clearance requirements and actual size and shape, spacing, and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of tanks(s) are modeled or accommodated by model checking software.	
		118 D2010.10-LOD-350 Facility Potable-Water Storage Tanks

400	Supplementary components added to the model required for fabrication and field installation.	
		119 D2010.10-LOD-400 Facility Potable-Water Storage Tanks

D2010.20 21-04 20 10 20 Domestic Water Equipment

Includes: Equipment for domestic water distribution system. Includes: Equipment for the softening of domestic water. Includes: Equipment for the filtering of domestic water. Includes: Equipment to heat domestic water. Includes: Equipment to heat domestic water by means of heat exchange.

Associated Masterformat Sections: 22 11 23 / 22 31 00 / 22 32 00 / 22 33 00 / 22 34 00 22 35 00

100	See <u>D20</u>	120 D2010.20-LOD-100 Domestic Water Equipment
		120 D2010.20-LOD-100 Domestic Water Equipment
200	Schematic layout with approximate size, shape, and location of equipment; approximate access/code clearance requirements modeled;	121 D2010.20-LOD-200 Domestic Water Equipment
300	Modeled as design-specified size, shape, spacing, and location of equipment; approximate allowances for spacing and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of equipment; access/code clearance requirements modeled.	122 D2010.20-LOD-300 Domestic Water Equipment

350	Modeled as actual construction elements size, shape, spacing, and location/connections of equipment; Actual size, shape, spacing, and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of equipment. actual access/code clearance requirements modeled.	
		123 D2010.20-LOD-350 Domestic Water Equipment
400	See <u>D2010.10</u>	124 D2010.20-LOD-400 Domestic Water Equipment

D2010.40 21-04 20 10 40 Domestic Water Piping

Includes: Piping, valves, and specialties associated with domestic water distribution located within, under, or closely associated with a structure. Includes circulating pumps. May Include: Water service from the structure to the utility water service line.

Associated Masterformat Sections: 22 11 16 / 22 11 19

100	Diagrammatic or schematic model elements;	
	conceptual and/or schematic flow diagrams;	
	design performance parameters as defined in the BXP to be associated with model elements as non-graphic information.	
200	Schematic layout with approximate size, shape, and location of mains and risers;	
	shaft requirements modeled;	
		125 D2010.40-LOD-200 Domestic Water Piping

Back to TOC

300	Modeled as design-specified size, shape, spacing, and location of pipe, valves, fittings, and insulation for risers, mains, and branches;	
	approximate allowances for spacing and clearances required for all specified hangers, supports, vibration and seismic control that are to be utilized in the layout of all risers, mains, and branches;	
	access/code clearance requirements modeled.	
		126 D2010.40-LOD-300 Domestic Water Piping
350	Modeled as actual construction elements;	
	Actual size, shape, spacing, and location/connections of pipe, valves, fittings, and insulation for risers, mains, and branches;	
	Actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all risers, mains, and branches;	
	Actual floor and wall penetration elements modeled.	
	actual access/code clearance requirements modeled.	127 D2010.40-LOD-350 Domestic Water Piping
400	See <u>D2010.10</u>	128 D2010.40-LOD-400 Domestic Water Piping
		12002010.40-LOD-400 Domestic Water Piping

D2010.60

21-04 20 10 60

Plumbing Fixtures

Includes: Terminal devices on the domestic water plumbing system. Includes rough-in piping, trim, fittings, and connection to vent piping.

Associated Masterformat Sections: 22 40 00 / 22 41 00 / 22 41 13 / 22 41 16 / 22 41 19
22 41 23 / 22 41 26 / 22 41 36 / 22 41 39 / 22 42 00 / 22 42 13 / 22 42 16 / 22 42 19
22 42 23 / 22 42 26 / 22 42 29 / 22 42 33 / 22 42 36 / 22 42 39 / 22 42 43 / 22 43 00
22 43 13 / 22 43 16 / 22 43 19 / 22 43 23 / 22 43 39 / 22 43 43 / 22 45 00 / 22 45 13
22 45 16 / 22 45 26 / 22 45 29 / 22 45 33 / 22 45 36 / 22 46 00 / 22 46 13 / 22 46 16
22 46 39 / 22 46 43 / 22 46 53 / 22 47 00 / 22 47 13 / 22 47 23

100 See <u>D20</u>

200	Schematic layout with approximate size, shape, and location of fixtures; carrier and wall width requirements modeled;	
		129D2010.60-LOD-200 Plumbing Fixtures
300	Modeled as design-specified size, shape, spacing, and location of fixtures; Approximate allowances for spacing and clearances required for all specified supports that are to be utilized in the layout of all fixtures; access/code clearance requirements modeled.	
		130 D2010.60-LOD-200 Plumbing Fixtures
350	Modeled as actual construction elements size, shape, spacing, and location/connections of fixtures/carriers; Actual size, shape, spacing, and clearances required for all supports that are utilized in the layout of all fixtures. Actual access/code clearance requirements modeled.	131 D2010.60-LOD-350 Plumbing Fixtures
400	See <u>D2010.10</u>	132 D2010.60-LOD-400 Plumbing Fixtures

D2010.90

21-04 20 10 90

Domestic Water Distribution Supplementary Components

Includes: Common work results for plumbing, plumbing insulation, and instrumentation. Includes: expansion fittings, meters, gages, valves, hangers, supports, heat tracing, vibration and seismic controls.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 05 45 13 / 22 05 00 / 22 05 16 / 22 05 19 / 22 05 23 22 05 29 / 22 05 33 / 22 05 48 / 22 05 53 / 22 07 00 / 22 09 00

Back to TOC

D2020

21-04 20 20

Sanitary Drainage

Includes: Facility sanitary sewerage system located within, under, or closely associated with a structure. Include Sanitary Drainage Supplementary Components as appropriate.

Associated Masterformat Sections: 01 86 16 / 22 13 00

100	See <u>D20</u>	
200	See <u>D2010</u>	

D2020.10 21-04 20 20 10 Sanitary Sewerage Equipment

Includes: Interceptor, separator, pumps, and septic tanks that are part of facility sanitary sewerage system.

Associated Masterformat Sections: 22 13 23 / 22 13 26 / 22 13 29 / 22 13 33 / 22 13 36 22 13 43 / 22 13 53

100	See D20	
200	Schematic layout with approximate size, shape, and location of equipment;	133 D2020.10-LOD-200 Sanitary Sewerage Equipment
300	Modeled as design specified size, shape, spacing, and location of equipment; Approximate allowances for spacing and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of equipment are modeled. access/code clearance requirements modeled.	134.D2020.10-LOD-300 Sanitary Sewerage Equipment
350	Actual size, shape, spacing, and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of equipment; actual access/code clearance requirements modeled.	135 D2020.10-LOD-350 Sanitary Sewerage Equipment

400	Supplementary components added to the model required for fabrication and field installation	
		136 D2020.10-LOD-400 Sanitary Sewerage Equipment

D2020.30 21-04 20 20 30 Sanitary Sewerage Piping

Includes: Sanitary waste and vent piping system within and under structures. May Include: Sanitary piping from the structure to the utility sanitary sewer.

Associated Masterformat Sections: 22 13 13 / 22 13 16 / 22 13 19 / 22 05 73 / 22 05 76

100	See <u>D20</u>	
200	Schematic layout with approximate size, shape, and location of mains and risers; shaft requirements modeled;	4
		137 D2020.30-LOD-200 Sanitary Sewerage Piping
300	Modeled as design-specified size, shape, spacing, location, and slope of pipe, valves, fittings, and insulation for risers, mains, and branches;	~
	Approximate allowances for spacing and clearances required for all specified hangers, supports, vibration and seismic control that are to be utilized in the layout of all risers, mains, and branches;	
	access/code clearance requirements modeled	138D2020.30-LOD-300 Sanitary Sewerage Piping

350	Modeled as actual construction elements;	
	Actual size, shape, spacing, location, connections, and slope of pipe, valves, fittings, and insulation for risers, mains, and branches;	
	Actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all risers, mains, and branches;	
	Actual floor and wall penetration elements modeled.	
	Actual access/code clearance requirements modeled	139 D2020.30-LOD-350 Sanitary Sewerage Piping
400	See <u>D2020.10</u>	140 D2020.30-LOD-400 Sanitary Sewerage Piping

D2020.90 21-04 20 20 90 Sanitary Drainage Supplementary Components

Includes: Common work results for plumbing, plumbing insulation, and instrumentation and control for plumbing to be included with sanitary drainage elements above as appropriate. Includes expansion fittings, meters, gages, valves, hangers, supports, heat tracing, vibration and seismic controls.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 05 45 13 / 22 05 00 / 22 05 16 / 22 05 19 / 22 05 23 22 05 29 / 22 05 33 / 22 05 48 / 22 05 53 / 22 07 00 / 22 09 00

D2030

21-04 20 30

Building Support Plumbing Systems

Includes: Facility storm water drainage and gray water systems. Include Building Support Plumbing System Supplementary Components as appropriate.

Associated Masterformat Sections: 01 86 16 / 22 14 00

100	See <u>D20</u>	
200	See <u>D2010</u>	

D2030.10

21-04 20 30 10

Stormwater Drainage Equipment

Includes: Drainage pumps, and sump pumps that are part of stormwater drainage system.

Associated Masterformat Sections: 22 14 29 / 22 14 33 / 22 14 36 / 22 14 53

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

100	Diagrammatic or schematic model elements;	
	conceptual and/or schematic layout;	
200	Schematic layout with approximate size, shape, and location of equipment; approximate access/code clearance requirements modeled;	
		141 D2030.10-LOD-200 Stormwater Drainage Equipment
300	Modeled as design-specified size, shape, spacing, and location of equipment; approximate allowances for spacing and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of equipment; access/code clearance requirements modeled.	
		142 D2030.10-LOD-300 Stormwater Drainage Equipment
350	Modeled as actual construction elements size, shape, spacing, and location/connections of equipment, actual size, shape, spacing, and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of equipment; actual access/code clearance requirements modeled.	
		143 D2030.10-LOD-350 Stormwater Drainage Equipment
400	Supplementary components added to the model required for fabrication and field installation.	144 D2030.10-LOD-400 Stormwater Drainage Equipment

D2030.20

21-04 20 30 20

Stormwater Drainage Piping

Includes: Storm drainage piping system within, under, or closely associated with a structure. Includes storm drains for areas closely associated with a structure such as courtyards, plazas, and loading dock areas. May Include: Storm drainage piping from the structure to the utility storm drain.

Back to TOC

100	See <u>D20</u>	
200	Schematic layout with approximate size, shape, and location of mains and risers; shaft requirements modeled;	145 D2030.20-LOD-200 Stormwater Drainage Piping
300	Modeled as design-specified size, shape, spacing, location, and slope of pipe, valves, fittings, and insulation for risers, mains, and branches; approximate allowances for spacing and clearances required for all specified hangers, supports, vibration and seismic control that are to be utilized in the layout of all risers, mains, and branches; access/code clearance requirements modeled.	146D2030.20-LOD-300 Stormwater Drainage Piping
350	Modeled as actual size, shape, spacing, location, connections, and slope of pipe, valves, fittings, and insulation for risers, mains, and branches; actual size and shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all risers, mains, and branches; Actual access/code clearance requirements modeled. actual floor and wall penetration elements modeled.	
		147 D2030.20-LOD-350 Stormwater Drainage Piping

Associated Masterformat Sections: 22 05 73 / 22 05 76 / 22 14 13 / 22 14 16 / 22 14 23

400	See <u>D2030.10</u>	148 D2030 20-1 OD-400 Stormwater Drainage Pining
		148 D2030.20-LOD-400 Stormwater Drainage Piping

D2030.30 21-04 20 30 30 Facility Stormwater Drains

Includes: Various types of drains to collect storm water.

Associated Masterformat Sections: 22 14 26

100	See <u>D20</u>	
200	Schematic layout with approximate size, shape, and location of components;	
		149 D2030.30-LOD-200 Facility Stormwater Drains

300	Modeled as design-specified size, shape, spacing, and location of components; approximate allowances for spacing and clearances required for all specified hangers, supports, vibration and seismic control that are to be utilized in the layout of all components; access/code clearance requirements modeled.	
		150 D2030.30-LOD-300 Facility Stormwater Drains
350	Modeled as actual construction elements size, shape, spacing, and location/connections of components; actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all components. Actual access/code clearance requirements modeled.	151 D2030.30-LOD-350 Facility Stormwater Drains
400	See <u>D2030.10</u>	152 D2030.30-LOD-400 Facility Stormwater Drains

D2030.60 21-04 20 30 60 Gray Water Systems Includes: Systems to collect, treat, and distribute gray water for other uses such as irrigation.

Associated Masterformat Sections: 22 13 63

[See D2030.20]

D2030.90

21-04 20 30 90 Components Building Support Plumbing System Supplementary

Includes: Common work results for plumbing, plumbing insulation, and instrumentation and control for plumbing to be included with building support plumbing system elements above as appropriate. Includes expansion fittings, meters, gages, valves, hangers, supports, heat tracing, vibration and seismic controls.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Back to TOC

Associated Masterformat Sections: 05 45 13 / 22 05 00 / 22 05 16 / 22 05 19 / 22 05 23 22 05 29 / 22 05 33 / 22 05 48 / 22 05 53 / 22 07 00 / 22 09 00

D2050 21-04 20 50 General Service Compressed-Air

Includes: Compressed air system serving general service requirements

Associated Masterformat Sections: 01 86 16 / 22 15 00 / 22 15 13 / 22 15 16 / 22 15 19

[See <u>D2060.10</u> – Compressed-Air Systems]

D2060 21-04 20 60 Process Support Plumbing Systems

Includes: Process Support Plumbing System Supplementary Components as appropriate.

Associated Masterformat Sections:

100	See <u>D20</u>	
200	Schematic layout with approximate size, shape, and location of mains and risers;	
	shaft requirements modeled;	

D2060.10 21-04 20 60 10 Compressed-Air Systems

Associated Masterformat Sections: 01 86 16 / 22 61 00 / 22 61 13 / 22 61 19

100	See <u>D20</u>	
200	See <u>D2060</u>	153 D2060.10-LOD-200 Compressed-Air Systems
300	Modeled as design-specified size, shape, spacing, location, and slope of equipment/pipe, valves, fittings, and insulation for risers, mains, and branches; approximate allowances for spacing and clearances required for all specified hangers, supports, vibration and seismic control that are to be utilized in the layout of all risers, mains, and branches; access/code clearance requirements modeled.	154 D2060.10-LOD-300 Compressed-Air Systems

350	Modeled as actual size, shape, spacing, location, connections, and slope of equipment/pipe, valves, fittings, and insulation for risers, mains, and branches; actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all risers, mains, and branches; actual access/code clearance requirements modeled. actual floor and wall penetration elements modeled.	
		155 D2060.10-LOD-350 Compressed-Air Systems
400	Supplementary components added to the model required for fabrication and field installation.	156 D2060.10-LOD-400 Compressed-Air Systems

D2060.20 21-04 20 60 20 Vacuum Systems

Includes: Vacuum systems for laboratory and healthcare purposes.

Associated Masterformat Sections: 01 86 16 / 22 62 00 / 22 62 13 / 22 62 19 / 22 62 23

[See <u>D2060.10</u>]

D2060.30 21-04 20 60 30 Gas Systems Includes: Gas systems for laboratory and healthcare purposes.

Associated Masterformat Sections: 01 86 16 / 22 63 00 / 22 63 13 / 22 63 19

[See <u>D2060.10</u>]

D2060.40 21-04 20 60 40 Chemical-Waste Systems Includes: Chemical-waste systems for laboratory and healthcare purposes.

Associated Masterformat Sections: 01 86 16 / 22 66 00 / 22 66 53 / 22 66 70 / 22 66 83

[See <u>D2060.10</u>]

D2060.50 21-04 20 60 50 Processed Water Systems Includes: Processed water systems for laboratory and healthcare purposes.

Associated Masterformat Sections: 01 86 16 / 22 67 00 / 22 67 13 / 22 67 19

[See D2060.10]

Back to TOC

D2060.90 21-04 20 60 90

Process Support Plumbing System Supplementary Components

Includes expansion fittings, meters, gages, valves, hangers, supports, heat tracing, vibration and seismic controls. Includes: Common work results for plumbing, plumbing insulation, and instrumentation and controls to be included with process support plumbing systems elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 05 45 13 / 05 45 23 / 22 05 00 / 22 05 23 / 22 05 29 / 22 05 33 / 22 05 48 / 22 05 53 / 22 07 00 / 22 09 00

D30

21-04 30

Heating, Ventilation, and Air Conditioning (HVAC)

Associated Masterformat Sections: 01 86 19 / 23 00 00

100	Diagrammatic or schematic model elements;	
	conceptual and/or schematic layout/flow diagram;	

D3010 21-04 30 10 Facility Fuel Systems

Includes: Fuel-oil, gasoline, natural-gas, and liquefied-petroleum fuel systems associated with a structure.

Associated Masterformat Sections: 01 86 19 / 23 10 00

100	See <u>D30</u>	
200	Schematic layout with approximate size, shape, and location of element(s);	
	approximate access/code clearance requirements modeled; shaft requirements modeled;	

D3010.10 21-04 30 10 10

Fuel Piping

Includes: Fuel piping, valves, piping specialties, and other components within, under, or closely associated with a structure.

Associated Masterformat Sections: 23 11 00

100	See <u>D30</u>	
200	See <u>D3010</u>	
		157 D3010.10-200 Fuel Piping



Copyright © 2017 by BIMForum. All rights reserved

This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

300	Modeled as design-specified size, shape, spacing, and location of pipe, valves, fittings, and insulation for risers, mains, and branches; approximate allowances for spacing and clearances required for all specified hangers, supports, vibration and seismic control that are to be utilized in the layout of all risers, mains, and branches; access/code clearance requirements modeled.	
		158 D3010.10-300 Fuel Piping
350	Modeled as actual size, shape, spacing, and location/connections of pipe, valves, fittings, and insulation for risers, mains, and branches;	
	actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all risers, mains, and branches;	
	actual access/code clearance requirements modeled.	
	actual floor and wall penetration elements modeled.	159 D3010.10-350 Fuel Piping
400	Supplementary components added to the model required for fabrication and field installation	

Back to TOC

160 D3010.10-400 Fuel Pig	bing
---------------------------	------

D3010.30 21-04 30 10 30 Fuel Pumps

Includes: Fuel pumps within or closely associated with a structure.

Associated Masterformat Sections: 23 12 00 $\,/\,$ 23 12 13 $\,/\,$ 23 12 16

100	See <u>D30</u>	
200	See <u>D3010</u>	
300	Modeled as design-specified size, shape, spacing, and location of equipment;	
	approximate allowances for spacing and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of equipment;	
	access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location/connections of equipment;	
	actual size, shape, spacing, and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of equipment.	
	actual access/code clearance requirements modeled.	
400	See <u>D3010.10</u>	

D3010.50 21-04 30 10 50 Fuel Storage Tanks

Includes: Fuel tanks under or closely associated with a structure.

Associated Masterformat Sections: 23 13 00

100 See <u>D30</u>

Back to TOC

200	See <u>D3010</u>	
300	Modeled as design-specified size, shape, spacing, and location of tank(s);	161 D3010.50-LOD-200 Fuel Storage Tanks
	approximate allowances for spacing and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of tanks(s); access/code clearance requirements modeled.	
		162 D3010.50-LOD-300 Fuel Storage Tanks
350	Modeled as actual size, shape, spacing, and location/connections of tank(s); actual size, shape, spacing, and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of tanks(s). actual access/code clearance requirements modeled.	I.
		163 D3010.50-LOD-350 Fuel Storage Tanks
400	See <u>D3010.10</u>	
		164 D3010.50-LOD-400 Fuel Storage Tanks

D3020 21-04 30 20 Heating Systems Includes: Associated ductwork, piping, valves, and specialties. Includes: Heating System Supplementary Components as appropriate.

Back to TOC

Associated Masterformat Sections: 01 86 19

100	See <u>D30</u>	
200	Schematic layout with approximate size, shape, and location of element(s); shaft requirements modeled;	

D3020.10 21-04 30 20 10 Heat Generation

Includes: Boilers, furnaces, solar, geothermal, and biomass heat generation, fuel fired heaters, and heat exchangers. Includes: Fuelfired boilers and generators for hot water and steam systems. Includes breechings, chimneys, and stacks. Includes: Electric boilers and generators for hot water and steam systems. Includes: Equipment to remove oxygen and other dissolved gases in boiler feed. Includes: Fuel-fired and electric furnaces. Includes: Equipment powered by solar energy. Includes: Fuel-fired radiant and unit heaters. Includes: Equipment used to transfer heat from one medium to another.

Associated Masterformat Sections: 23 51 00 / 23 52 00 / 23 52 13 / 23 53 00 / 23 53 13 / 23 53 16 / 23 54 00 / 23 56 00 / 23 56 13 / 23 56 16 / 23 55 00 / 23 57 00

100	See <u>D30</u>	
200	See <u>D3020</u>	165 D3020.10-LOD-200 Heat Generation
300	Modeled as design-specified size, shape, spacing, and location of equipment; approximate allowances for spacing and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of equipment; access/code clearance requirements modeled.	166 D3020. 10-LOD-300 Heat Generation

350	Modeled as actual size, shape, spacing, and location/connections of equipment, actual size, shape, spacing, and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of equipment. actual access/code clearance requirements modeled.	167 D3020.10-LOD-350 Heat Generation
400	Supplementary components added to the model required for fabrication and field installation.	168 D3020.10-LOD-400 Heat Generation

D3020.30 21-04 30 20 30 Thermal Heat Storage

Includes: Equipment to store thermal energy for use in heating and with charging or discharging this energy at a controllable rate.

Associated Masterformat Sections: 23 71 13

[See D3020.10]

D3020.70 21-04 30 20 70

Decentralized Heating Equipment

Includes: Heating equipment that serves a portion of a HVAC system. Includes: Convection units may provide heating and cooling. Includes: Electric cables or panels and hydronic piping used for radiant heating for space heating.

Associated Masterformat Sections: 23 80 00 / 23 82 00 / 23 82 13 / 23 82 14 / 23 82 16 / 23 82 19 / 23 82 23 / 23 82 26 / 23 82 29 / 23 82 33 / 23 82 36 / 23 82 39 / 23 83 00

[See D3020.10]

D3020.90 21-04 30 20 90

Heating System Supplementary Components

Includes: Common work results for HVAC, insulation, and instrumentation and control to be included in heating system elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 05 45 13 / 23 05 00 / 23 05 19 / 23 05 23 / 23 05 29 / 23 05 48 / 23 05 53 / 23 05 63 / 23 05 66 / 23 05 93 / 23 07 00 / 23 09 00

D3030

21-04 30 30

Cooling Systems

Includes: Associated ductwork, piping, valves, and specialties. Includes: Cooling System Supplementary Components as appropriate.

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

Associated Masterformat Sections: 01 86 19

100	See <u>D30</u>	
200	Schematic layout with approximate size, shape, and location of element(s); shaft requirements modeled;	

D3030.10

21-04 30 30 10 Central Cooling

Includes: Refrigerant compressors, condensers, packaged compressor and condenser units, water chillers, and cooling towers. Includes: Various type of compressors used in refrigeration process. Includes: Condensing units used to reject heat from the refrigeration process. Includes: Compressor in combination with condensing units used to reject heat from the refrigeration process. Includes: Various types of chillers used for building space cooling. Includes: Factory- and field-fabricated cooling towers and liquid coolers. Includes piping and specialties; chemical water treatment; vibration and seismic controls; and integral controls not a part of the condenser water distribution systems.

Associated Masterformat Sections: 23 60 00 / 23 61 00 / 23 62 00 / 23 63 00 / 23 64 00 / 23 65 00

100	See <u>D30</u>	
200	See <u>D3030</u>	
		169 D3030.10-LOD-200 Central Cooling
300	Modeled as design-specified size, shape, spacing, and location of equipment; approximate allowances for spacing and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of equipment; access/code clearance requirements modeled.	
		170 D3030.10-LOD-300 Central Cooling

350	Modeled as actual size, shape, spacing, and location/connections of equipment;	
	actual size, shape, spacing, and clearances required for all specified anchors, supports, vibration and seismic control that are utilized in the layout of equipment.	
	actual access/code clearance requirements modeled.	
		171 D3030.10-LOD-350 Central Cooling
400	Supplementary components added to the model required for fabrication and field installation.	
		172 D3030.10-LOD-400 Central Cooling

D3030.30 21-04 30 30 30 Evaporative Air-Cooling

Includes: Equipment used to reject heat from the refrigeration process by evaporation.

Associated Masterformat Sections: 23 76 00

100	See <u>D3030.10</u>	
200	See <u>D3030.10</u>	
		•
		173D3030.30-LOD-200 Evaporative Air-Cooling

300	See <u>D3030.10</u>	
		174D3030.30-LOD-300 Evaporative Air-Cooling
350	See <u>D3030.10</u>	
		175 D3030.30-LOD-350 Evaporative Air-Cooling
400	See <u>D3030.10</u>	176 D3030.30-LOD-400 Evaporative Air-Cooling

D3030.50 21-04 30 30 50 Thermal Cooling Storage Includes: Equipment to store thermal energy for use in cooling and with charging or discharging this energy at a controllable rate.

Associated Masterformat Sections: 23 71 00 / 23 71 16 / 23 71 19

[See <u>D3030.10</u>]

21-04 30 30 70 D3030.70 Decentralized Cooling Includes: Cooling equipment that serves a portion of a HVAC system. Note: Convection units may provide heating and cooling. Associated Masterformat Sections: 23 80 00 / 23 81 13 / 23 81 16 / 23 81 19 / 23 81 23 / 23 81 26 / 23 81 43 / 23 81 46 / 23 82 00 / 23 82 13 / 23 82 14 / 23 82 16 / 23 82 19 / 23 82 23 / 23 82 26

Back to TOC

[See <u>D3030.10</u>]

D3030.90 21-04 30 30 90 Cooling System Supplementary Components

Includes expansion fittings, meters, gages, valves, hangers, supports, heat tracing, vibration and seismic controls. Includes: Common work results for HVAC, insulation, and instrumentation and control to be included in cooling system elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 05 45 13 / 23 05 00 / 23 05 19 / 23 05 23 / 23 05 29 / 23 05 48 / 23 05 53 / 23 05 63 / 23 05 66 / 23 05 93 / 23 07 00 / 23 09 00

D3050 21-04 30 50 Facility HVAC Distribution Systems

Includes: Facility Distribution Systems Supplementary Components as appropriate.

Associated Masterformat Sections:

100	See <u>D30</u>	
200	Schematic layout with approximate size, shape, and location of element(s);	

D3050.10 21-04 30 50 10 Facility Hydronic Distribution

Includes: Piping systems and equipment for distribution of heating hot water and cooling chilled water. Includes piping systems, pumps, tanks, supports and anchors, vibration and seismic controls, identification, and piping and equipment insulation.

Associated Masterformat Sections: 01 86 19 / 23 21 13 / 23 21 23 / 23 25 00

100	See <u>D30</u>	
200	See <u>D3050</u>	
		177 D3050.10-LOD-200 Facility Hydronic distribution

300	Modeled as design-specified size, shape, spacing, location, and slope of pipe, valves, fittings, and insulation for risers, mains, and branches; approximate allowances for spacing and clearances required for all specified hangers, supports, vibration and seismic control that are to be utilized in the layout of all risers, mains, and branches; access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, location, connections, and slope of pipe, valves, fittings, and insulation for risers, mains, and branches; actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all risers, mains, and branches; actual floor and wall penetration elements modeled. actual access/code clearance requirements modeled.	178 D3050.10-LOD-300 Facility Hydronic Distribution
		179 D3050.10-LOD-350 Facility Hydronic Distribution
400	Supplementary components added to the model required for fabrication and field installation.	

	180 D3050. 10-LOD-400 Facility Hydronic Distribution

D3050.30 21-04 30 50 30 Facility Steam Distribution

Includes: Piping systems and equipment for distribution of steam and condensate return. Includes piping systems, pumps, tanks, supports and anchors, vibration and seismic controls, identification, and piping and equipment insulation.

Associated Masterformat Sections: 01 86 19 / 23 22 13 / 23 22 23 / 23 25 19

[See <u>D3050.10</u>]

D3050.50 21-04 30 50 50 HVAC Air Distribution

Includes: Systems for distribution of air including supply systems, return systems, and general exhaust systems. Does not include special exhaust systems such as kitchen hood, paint booth, and fume hood exhaust systems. Includes: Air-handling units consisting of fans, coils, dampers, control devices, and other accessories. Includes: Ducts, duct accessories, fans, terminal units, and air inlets and outlets. Includes: Devices of a variety of types to clean distribution air. Includes: Equipment that adds or removes moisture from a medium in order to control the humidity.

Associated Masterformat Sections: 01 86 19 / 23 73 00 / 23 74 00 / 23 75 00 / 23 30 00 / 23 34 00 / 23 31 00 / 23 32 00 / 23 33 00 / 23 36 00 / 23 37 00 / 23 40 00 / 23 41 00 / 23 42 00 / 23 43 00 / 23 84 00

100	See <u>D30</u>	
200	See <u>D3050</u>	
300	Modeled as design-specified size, shape, spacing, and location of duct, dampers, fittings, and insulation for risers, mains, and branches;	
	approximate allowances for spacing and clearances required for all specified hangers, supports, vibration and seismic control that are to be utilized in the layout of all risers, mains, and branches; access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location/connections of duct, dampers, fittings, and insulation for risers, mains, and branches;	

	actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all risers, mains, and branches;	
	actual floor and wall penetration elements modeled.	
	actual access/code clearance requirements modeled.	
400	See <u>D3050.10</u>	

D3050.90 21-04 30 50 90 Facility Distribution Systems Supplementary Components

Includes expansion fittings, meters, gages, valves, hangers, supports, heat tracing, vibration and seismic controls. Includes: Common work results for HVAC, insulation, and instrumentation and control to be included in distribution system elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 05 45 13 / 23 05 00 / 23 05 16 / 23 05 19 / 23 05 23 / 23 05 29 / 23 05 33 / 23 05 48 / 23 05 53 / 23 05 63 / 23 05 66 / 23 05 93 / 23 07 00 / 23 09 00

D3060 21-04 30 60 Ventilation

Includes: Supply air, return air, exhaust air, outside air, and air cleaning systems. Includes Ventilation Supplementary Components as appropriate.

Associated Masterformat Sections: 01 86 19

100	See <u>D30</u>	
200	Schematic layout with approximate size, shape, and location of mains and risers;	

D3060.10 21-04 30 60 10 Supply Air

Associated Masterformat Sections: 23 34 00 / 23 31 00 / 23 32 00 / 23 33 00 / 23 36 00 / 23 37 00

100	See <u>D30</u>	
200	See <u>D3060</u>	
		<
		181 D3060.10-LOD-200 Supply Air

300	Modeled as design-specified size, shape, spacing, and location of duct, dampers, fittings, and insulation for risers, mains, and branches; approximate specified allowances for spacing and clearances required for all hangers, supports, vibration and seismic control that are to be utilized in the layout of all risers, mains, and branches; access/code clearance requirements modeled.	182 D3060.10-LOD-300 Supply Air
350	Modeled as actual size, shape, spacing, and location/connections of duct, dampers, fittings, and insulation for risers, mains, and branches; actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all risers, mains, and branches; actual floor and wall penetration elements modeled. actual access/code clearance requirements modeled.	183 D3060. 10-LOD-350 Supply Air
400	Supplementary components added to the model required for fabrication and field installation.	184D3060.10-LOD-400 Supply Air

D3060.20 21-04 30 60 20 Return Air

Associated Masterformat Sections: 23 34 00 / 23 31 00 / 23 32 00 / 23 33 00 / 23 37 00

[See <u>D3060.10</u>]

D3060.30 21-04 30 60 30 Exhaust Air

Includes: Special systems for exhausting air such as kitchen hood, paint booth, and fume hood exhaust systems.

Associated Masterformat Sections: 23 35 00 / 23 35 13.13 / 23 35 16 / 23 38 00 / 23 38 13 / 23 38 16 / 23 34 00 / 23 31 00 / 23 32 00 / 23 33 00 / 23 37 00

100	See <u>D30</u>	
200	See <u>D3060</u>	
		185 D3060.30-LOD-200 Exhaust Air
300	Modeled as design-specified size, shape, spacing, location, duct slope (if required), dampers, fittings, insulation for risers, mains, and branches; approximate specified allowances for spacing and clearances required for all hangers, supports, vibration and seismic control that are to be utilized in the layout of all risers, mains, and branches; access/code clearance requirements modeled.	
		186 D3060.30-LOD-300 Exhaust Air
350	Modeled as actual size, shape, spacing, location, and slope (if required)/connections of duct, dampers, fittings, and insulation for risers, mains, and branches; actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all risers, mains, and branches; actual floor and wall penetration elements modeled. actual access/code clearance requirements modeled.	187 D3060.30-LOD-350 Exhaust Air
400	See <u>D3060.10</u>	

	188 D3060.30-LOD-400 Exhaust Air

D3060.40 21-04 30 60 40 Outside Air Associated Masterformat Sections: 23 34 00 / 23 31 00 / 23 32 00 / 23 33 00 / 23 36 00 / 23 37 00

[See <u>D3060.10</u>]

D3060.60 21-04 30 60 60 Includes: Air-to-air energy recovery units. Air-to-Air Energy Recovery

Associated Masterformat Sections: 23 72 00

[See <u>D3060.10</u>]

D3060.70 21-04 30 60 70 Associated Masterformat Sections: 23 40 00

HVAC Air Cleaning

[See D3060.10]

D3060.90 21-04 30 60 90

Ventilation Supplementary Components

Includes expansion fittings, meters, gages, valves, hangers, supports, heat tracing, vibration and seismic controls. Includes: Common work results for HVAC, insulation, and instrumentation and control to be included in ventilation elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 05 45 13 / 23 05 00 / 23 05 29 / 23 05 48 / 23 05 53 / 23 05 66 / 23 05 93 / 23 07 00 / 23 09 00

D3070 21-04 30 70 Special Purpose HVAC Systems

Associated Masterformat Sections:

100	See <u>D30</u>	
200	Schematic layout with approximate size, shape, and location of components;	

D3070.10 21-04 30 70 10 Snow Melting

Includes: Electric cables and hydronic piping used for snow and ice control.

Associated Masterformat Sections: 23 83 13 / 23 83 16

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

OSE Opphysice 2017 by binn order, an ignest esserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

100	See <u>D30</u>	
200	See <u>D3070</u>	
300	Modeled as design-specified size, shape, spacing, and location of supplementary components;	
	approximate allowances for spacing and clearances required for all specified hangers, supports, vibration and seismic control that are to be utilized in the layout of all supplementary components;	
	access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location/connections of supplementary components;	
	actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all supplementary components.	
	actual access/code clearance requirements modeled.	
400	Supplementary components added to the model required for fabrication and field installation.	

D40 21-04 40 Fire Protection

Associated Masterformat Sections:

10	00	Diagrammatic or schematic model elements;
		conceptual and/or schematic layout/flow diagram;

D4010 21-04 40 10 Fire Suppression

Includes: Fire Suppression Supplementary Components as appropriate.

Associated Masterformat Sections: 01 86 13 / 21 00 00

100	See <u>D40</u>	
200	Schematic layout with approximate size, shape, and location of mains and risers;	

D4010.10

21-04 40 10 10

Water-Based Fire-Suppression

Includes: Systems that use water for fire extinguishing and suppression. Includes piping, fittings, and specialties; hoses, valves, cabinets; fire pumps, accessories, and controls. Includes: Piping, fittings, valves, hangers, supports, other specialties, and sprinklers for fire protection systems. Includes limited area sprinkler systems, fire pumps, accessories, and controls.

Associated Masterformat Sections: 01 86 13 / 21 10 00 / 21 11 00 / 21 12 00 / 21 13 00 / 21 13 13 / 21 13 16 / 21 13 19 / 21 13 23 / 21 13 26 / 21 13 29 / 21 13 36 / 21 13 39 / 21 30 00 / 21 40 00

100	See <u>D40</u>	
200	See <u>D4010</u>	
		189 D4010.10-LOD-200 Water-Based Fire- Suppression
300	Modeled as design-specified size, shape, spacing, and location of pipe/slope (if required)/valves/fittings/insulation for risers, mains, and branches/standpipes; approximate allowances for spacing and clearances required for all specified hangers, supports, vibration and seismic control that are to be utilized in the layout of all risers, mains, and branches/standpipes;	
	access/code clearance requirements modeled.	190 D4010.10-LOD-300 Water-Based Fire- Suppression
350	Modeled as actual size, shape, spacing, and location/ slope (if required)/connections of pipe, valves, fittings, and insulation for risers, mains, and branches/standpipes; actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all risers, mains, and branches/standpipes; actual floor and wall penetration elements modeled. actual access/code clearance requirements modeled.	
		191 D4010.10-LOD-350 Water-Based Fire- Suppression
400	Supplementary components added to the model required for fabrication and field installation.	
		192 D4010.10-LOD-400 Water-Based Fire- Suppression

D4010.50

21-04 40 10 50

Fire-Extinguishing

Includes: Systems that use other than water for fire extinguishing and suppression. Includes piping, fittings, and specialties; valves, accessories, and controls.

Back to TOC

Associated Masterformat Sections: 21 20 00 / 21 21 00 / 21 22 00 / 21 23 00 / 21 24 00

21-04 40 10 90

[See <u>D4010.10</u>]

D4010.90

Fire Suppression Supplementary Components

Includes: Expansion fittings and loops, meters and gages, general-duty valves, hanger and supports, heat tracing, vibration and seismic controls, identification, insulation, and instrumentation and control to be included in fire protection elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections: 05 45 13 / 21 05 00 / 21 05 16 / 21 05 19 / 21 05 23 / 21 05 29 / 21 05 33 / 21 05 48 / 21 05 53 / 21 07 00 / 21 09 00

D4030 21-04 40 30 Fire Protection Specialties

Includes: Firefighting devices and storage cabinets except devices connected to a fire suppression system.

Associated Masterformat Sections: 10 44 00

100	See <u>D40</u>	
200	Schematic layout with approximate size, shape, and location of components;	

D4030.10 21-04 40 30 10

Fire Protection Cabinets

Associated Masterformat Sections: 10 44 13

100	See <u>D40</u>	
200	See <u>D4030</u>	
300	Modeled as design-specified size, shape, spacing, and location of components;	
	approximate allowances for spacing and clearances required for all specified hangers, supports, vibration and seismic control that are to be utilized in the layout of all components;	
	access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location/connections of components;	
	actual size, shape, spacing, and clearances required for all hangers, supports, vibration and seismic control that are utilized in the layout of all components.	
	actual access/code clearance requirements modeled.	
400	Supplementary components added to the model required for fabrication and field installation.	

D4030.30 21-04 40 30 30 Associated Masterformat Sections: 10 44 16

Fire Extinguishers

[See <u>D4030.10</u>]

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

D4030.50 Associated Master	21-04 40 30 50 format Sections: 10 44 33	Breathing Air Replenishment Systems
[See <u>D4030.10</u>	נ	
D4030.70 Associated Master	21-04 40 30 70 format Sections: 10 44 43	Fire Extinguisher Accessories
[See D4030.10	ו	

D50 21-04 50 Electrical

Associated Masterformat Sections: 26 00 00 / 01 86 26

100	Diagrammatic or schematic model elements:	
	conceptual and/or schematic layout;	

D5010 21-04 50 10 Facility Power Generation

Includes: Power Generation Supplementary Components as appropriate.

Associated Masterformat Sections: 01 86 26

100	See <u>D50</u>	
200	Schematic layout with approximate size, shape, and location of equipment;	

D5010.10 21-04 50 10 10 Packaged Generator Assemblies

Includes: Generator, frequency changers, and rotary converters and uninterruptible power units.

Associated Masterformat Sections: 26 32 00 / 26 32 13 / 26 32 16 / 26 32 19 / 26 32 23 / 26 32 26 / 26 32 29 / 26 32 33

100	See <u>D50</u>	
200	See <u>D5010</u>	193 D5010.10-LOD-200 Packaged Generator Assemblies

300	Modeled as design-specified size, shape, spacing, and location of equipment and associated components; approximate allowances for spacing and clearances required for all specified supports and seismic control; access/code clearance requirements modeled.	
		194 D5010.10-LOD-300 Packaged Generator Assemblies
350	Modeled as actual size, shape, spacing, and location of equipment and associated components;	
	actual size, shape, spacing, and location for supports and seismic control;	
	actual size, shape, and location/connections of equipment and support structure/pads.	
	actual access/code clearance requirements modeled.	
		195 D5010.10-LOD-350 Packaged Generator Assemblies
400	Supplementary components added to the model required for fabrication and field installation.	196 D5010.10-LOD-400 Packaged Generator
		Assemblies

D5010.20 21-04 50 10 20 Battery Equipment

Includes: Batteries, battery racks, battery chargers, static power converters, uninterruptible power supplies, and accessories.

Associated Masterformat Sections: 26 33 00 / 26 33 13 / 26 33 16 / 26 33 19 / 26 33 23 / 26 33 33 / 26 33 43 / 26 33 46 / 26 33 53

[See <u>D5010.10</u>]

D5010.30 21-04 50 10 30 Includes: Solar cells to convert sunlight to electricity. Photovoltaic Collectors

Associated Masterformat Sections: 26 31 00

[See <u>D5010.10</u>]

D5010.40 Includes: Fuel cell elect Associated Masterform [See <u>D5010.10</u>]	21-04 50 10 40 <i>tricity generating equipment.</i> Pat Sections: 48 18 00	Fuel Cells	
D5010.60	21-04 5010 60	Power Filtering and Conditioning	TBD
D5010.70 Includes: Switches that	21-04 50 10 70 t transfer from one source of elect	Transfer Switches tricity to another.	
Associated Masterform	at Sections: 26 36 00		
[See <u>D5010.10</u>]			
D5010.90	21-05 50 10 90	Facility Power Generation Supplementary Components	TBD
D5020 Includes: Electrical Se	21-04 50 20 rvice and Distribution Supplemen	Electrical Service and Distribution tary Components as appropriate.	
Associated Masterform	at Sections: 01 86 26		

100	See <u>D50</u>	
200	Schematic layout with approximate size, shape, and location of equipment;	

D5020.10 21-04 50 20 10 Electrical Service Entrance

Includes: Meters, substations, transformers, switchgear, switchboards, and protective devices where electrical power enters structure.

Associated Masterformat Sections: 26 21 00 / 26 16 00 / 26 11 00 / 26 12 00 / 26 22 00 / 26 13 00 / 22 23 00 / 26 18 00 / 22 28 00

100	See <u>D50</u>	
200	See <u>D5020</u>	
300	Modeled as design-specified size, shape, spacing, and location of equipment and associated components;	
	approximate allowances for spacing and clearances required for all specified supports and seismic control;	
	access/code clearance requirements modeled.	

		197 D5020.10-LOD-300 Electrical Service Entrance
350	Modeled as actual size, shape, spacing, and location of equipment and associated components; actual size, shape, spacing, and location for supports and seismic control; actual size, shape, and location/connections of equipment and support structure/pads. actual access/code clearance requirements modeled.	198 D5020.10-LOD-350 Electrical Service Entrance
400	Supplementary components added to the model required for fabrication and field installation.	199 D5020.10-LOD-400 Electrical Service Entrance

D5020.30

21-04 50 20 30

Power Distribution

Includes: Bus assemblies, distribution equipment, and electrical wiring system to distribute electrical power to switchboards, panelboards, and motor control centers.

Associated Masterformat Sections: 26 20 00 / 26 24 00 / 26 24 13 / 26 24 16 / 26 24 19 / 26 25 00 / 26 27 00 / 26 27 16 / 26 05 33 / 26 05 43 / 26 05 36 / 26 05 13

100	See <u>D50</u>	
200	See <u>D5020</u>	

Back to TOC

300	Modeled as design-specified size, shape, spacing, and location of raceways, boxes, enclosures, and equipment; approximate allowances for spacing and clearances required for all specified hangers, supports and seismic control; access/code clearance requirements modeled.	200 D5020.30-LOD-300 Power Distribution
350	Modeled as actual size, shape, spacing, and location of raceways, boxes, and enclosures; actual size, shape, spacing, and location for supports and seismic control; actual size, shape, and location/connections of equipment and support structure/pads; actual floor and wall penetration elements are modeled. actual access/code clearance requirements modeled.	201 D5020.30-LOD-350 Power Distribution
400	Supplementary components added to the model required for fabrication and field installation.	202 D5020.30-LOD-400 Power Distribution

D5020.70 21-04 50 20 70 Facility Grounding Includes: Raceways, wiring and devices for grounding and bonding an electrical distribution system.

Associated Masterformat Sections: 26 05 26 / 26 05 33 / 26 05 13

Back to TOC

400	Cas DE0	
100	See <u>D50</u>	
200	See <u>D5020</u>	
300	Modeled as design-specified size, shape, spacing, and location of raceways, boxes, enclosures, and the electrical equipment and end-devices served;	
	approximate allowances for spacing and clearances required for all specified hangers, supports, and seismic control;	
	access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location of raceways, boxes, enclosures, and the electrical equipment and end-devices served;	
	actual size, shape, spacing, and location for supports and seismic control;	
	actual floor and wall penetration elements are modeled.	
	actual access/code clearance requirements modeled.	
400	Supplementary components added to the model required for fabrication and field installation.	

D5020.90

21-04 50 20 90

Electrical Service and Distribution Supplementary Components

TBD

General Purpose Electrical Power D5030 21-04 50 30

Includes: General Purpose Electrical Power Supplementary Components as appropriate.

Associated Masterformat Sections: 01 86 26

100	See <u>D50</u>	
200	Schematic layout with approximate size, shape, and location of equipment;	

D5030.10 21-04 50 30 10 **Branch Wiring System**

Includes: Raceways, ducts, cable trays, and wiring to deliver power from branch panelboards to the point of use.

Associated Masterformat Sections: 26 05 33 / 26 05 43 / 26 05 36 / 26 05 19

100	See <u>D50</u>	
200	See <u>D5030</u>	
300	Modeled as design-specified size, shape, spacing, and location of raceways, boxes, and enclosures;	
	approximate allowances for spacing and clearances required for all specified hangers, supports and seismic control;	
	access/code clearance requirements modeled.	

Back to TOC

		203 D5030.10-LOD-300 Branch Wiring System
350	Modeled as actual size, shape, spacing, and location of raceways, boxes, enclosures; actual size, shape, spacing, and location for supports and seismic control; actual floor and wall penetration elements are modeled. actual access/code clearance requirements modeled.	204 D5030.10-LOD-350 Branch Wiring System
400	Supplementary components added to the model required for fabrication and field installation.	

D5030.50 21-04 50 30 50 Wiring Devices

Includes: Electrical devices at point of use including electrical outlets and switches.

Associated Masterformat Sections: 26 27 26

100	See <u>D50</u>	
200	See <u>D5030</u>	
300	Modeled as design-specified size, shape, spacing, and location of outlet boxes and devices; access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location of outlet boxes and devices. actual access/code clearance requirements modeled.	
400	Supplementary components added to the model required for fabrication and field installation.	

D5030.90 21-04 50 30 90 **General Purpose Electrical Power** TBD Supplementary Components

D5040 21-04 50 40 Lighting

Includes: Lighting Supplementary Components as appropriate.

Associated Masterformat Sections: 26 50 00 / 01 86 26

100	See <u>D50</u>	
200	Schematic layout with approximate size, shape, and location of equipment;	

D5040.10 21-04 50 40 10 Lighting Control

Includes: Clock and calendar, photoelectric switches, occupancy sensors, and light-leveling control devices.

Associated Masterformat Sections: 26 09 23 / 26 09 26 / 26 09 33 / 26 09 36 / 26 09 43 / 26 09 61

100	See <u>D50</u>	
200	See <u>D5040</u>	
300	Modeled as design-specified size, shape, spacing, and location of enclosures, equipment, and devices; access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location of enclosures, equipment, and control devices; actual size, shape, and location/connections of equipment and control devices. actual access/code clearance requirements modeled.	
400	Supplementary components added to the model required for fabrication and field installation.	

D5040.20

21-04 50 40 20

Branch Wiring for Lighting

Includes: Raceways, ducts, cable trays, and wiring beyond branch circuit panelboards to lighting fixtures.

Associated Masterformat Sections: 26 05 33 / 26 05 43 / 26 05 36 / 26 05 19 / 26 27 26

100	See <u>D50</u>	
200	See <u>D5040</u>	
300	Modeled as design-specified size, shape, spacing, and location of raceways, boxes, and enclosures to fixture locations;	
	approximate allowances for spacing and clearances required for all specified hangers, supports, and seismic control.	

Back to TOC

	access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location of raceways, boxes, and enclosures to fixture locations;	
	actual size, shape, spacing, and location for supports and seismic control;	
	actual floor and wall penetration elements are modeled.	
	actual access/code clearance requirements modeled.	
400	Supplementary components added to the model required for fabrication and field installation.	

D5040.50 21-04 50 40 50 Lighting Fixtures

Includes: Luminaires, lighting equipment, ballasts, and accessories. Includes fluorescent, high intensity discharge, incandescent, mercury vapor, neon, and sodium vapor lighting.

Associated Masterformat Sections: 26 50 00 / 26 51 00 / 26 52 00 / 26 53 00 / 26 54 00 / 26 55 00 / 26 55 23 / 26 55 29 / 26 55 33 / 26 55 36 / 26 55 39 / 26 55 53 / 26 55 59 /

26 55 61 / 26 55 63 / 26 55 70

100	See <u>D50</u>	
200	See <u>D5040</u>	
300	Modeled as design-specified size, shape, spacing, and location of lighting fixtures; approximate allowances for spacing and clearances required for all specified hangers, supports and seismic control; access/code clearance requirements modeled.	
		205 D5040.50-LOD-300 Lighting Fixtures
350	Modeled as actual size, shape, spacing, and location of lighting fixtures. actual size, shape, spacing, and location for supports and seismic control. actual access/code clearance requirements modeled.	206 D5040.50-LOD-350 Lighting Fixtures
		206 D3040.50-LOD-330 Lighting Fixtures
400	Supplementary components added to the model required for fabrication and field installation.	

D5040.90 21-04 50 40 90 Lighting S

Lighting Supplementary Components

TBD

D5080 21-04 50 80 Miscellaneous Electrical Systems

Includes: Miscellaneous Electrical Systems Supplementary Components as appropriate.

Associated Masterformat Sections:

100	See <u>D50</u>	
200	Schematic layout with approximate size, shape, and location of equipment;	

D5080.10 21-04 50 80 10 Lightning Protection

Includes: Wiring and equipment for lightning protection.

Associated Masterformat Sections: 26 41 00 / 01 86 26 / 26 41 13 / 26 41 16 / 26 41 19 /

26 41 23

100	See <u>D50</u>	
200	See <u>D5080</u>	
300	Modeled as design-specified size, shape, spacing, and location of raceways, boxes, enclosures including the electrical equipment and end-devices served;	
	approximate allowances for spacing and clearances required for all specified hangers, supports and seismic control;	
	access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location of raceways, boxes, enclosures including the electrical equipment, fixtures, and end-devices served	
	actual size, shape, spacing, and location for supports and seismic control;	
	actual size, shape, and location/connections of equipment and support structure/pads;	
	actual floor and wall penetration elements are modeled.	
	actual access/code clearance requirements modeled.	
400	Supplementary components added to the model required for fabrication and field installation.	

D5080.40

21-04 50 80 40

Cathodic Protection

TBD

D5080.70

21-04 50 80 70

Transient Voltage Suppression

Includes: Devices to protect against voltage surges on electrical distribution systems.

Back to TOC

Omniclass Uniformat

Associated Masterformat Sections: 26 43 00

100	See <u>D50</u>	
200	See <u>D5080</u>	
300	Modeled as design-specified size, shape, spacing, and location of equipment; approximate allowances for spacing and clearances required for all specified hangers, supports and seismic control; access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location of the equipment; actual size, shape, spacing, and location for supports and seismic control. actual access/code clearance requirements modeled.	
400	Supplementary components added to the model required for fabrication and field installation.	

D5080.90

21-04 50 80 90

Miscellaneous Electrical Systems Supplementary TBD Components

21-04 60 Communications D60

Associated Masterformat Sections: 27 00 00 / 01 86 29

[See Fundamental LOD Definitions]

Data Communications D6010 21-04 60 10

Includes: Communications Supplementary Components as appropriate.

Associated Masterformat Sections: 27 20 00 / 01 86 29

[See Fundamental LOD Definitions]

D6010.10	21-04 60 10 10	Data Communications Network Equipment	TBD
D6010.20	21-04 60 10 20	Data Communications Hardware	TBD
D6010.30	21-04 60 10 30	Data Communications Peripheral Data Equipment	TBD
D6020	21-04 60 20	Voice Communications	

21-04 60 20 Voice Communications

Includes: Communications Supplementary Components as appropriate.

Associated Masterformat Sections: 27 30 00 / 01 86 29

Back to TOC

[See Fundamental LOD Definitions]

D6030	21-04 60 30	Audio-Video Communication
Includes:	Communications Supplementary Compo	nents as appropriate.

Associated Masterformat Sections: 27 40 00 / 01 86 29

[See Fundamental LOD Definitions]

D6060 21-04 60 60 Distributed Communications and Monitoring Includes: Communications Supplementary Components as appropriate.

Associated Masterformat Sections: 27 50 00 / 01 86 29

[See Fundamental LOD Definitions]

D6090 21-04 60 90 [See <u>Fundamental LOD Definitions</u>] **Communications Supplementary Components**

D70 21-04 70 Electronic Safety and Security

[See Fundamental LOD Definitions]

D7010 21-04 70 10 Access Control and Intrusion Detection Includes: Electronic Safety and Security Supplementary Components as appropriate.

Associated Masterformat Sections: 28 10 00 / 01 86 33

[See Fundamental LOD Definitions]

D7030 21-04 70 30 Electronic Surveillance

Includes: Equipment for detecting and controlling access by persons to a facility site, building, or within a building. Includes Electronic Safety and Security Supplementary Components as appropriate.

Associated Masterformat Sections: 28 20 00 / 01 86 33

[See Fundamental LOD Definitions]

D7050

21-04 70 50

Detection and Alarm

Includes: Equipment for detecting hazardous conditions in a building or on a facility site and communicating an alarm signal. Includes alarm devices, detection devices, safety switches, and associated items. Includes Electronic Safety and Security Supplementary Components as appropriate.

Associated Masterformat Sections: 28 30 00 / 01 86 33

D7070 21-04 70 70 Electronic Monitoring and Control

Includes: Electronic Safety and Security Supplementary Components as appropriate.

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

Associated Masterformat Sections: 28 46 00 / 01 86 33

D7090 21-04 70 90 Electronic Safety and Security Supplementary Components

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

Associated Masterformat Sections:

D80 21-04 80 Integrated Automation

Associated Masterformat Sections: 25 00 00 / 01 86 23

[See Fundamental LOD Definitions]

D8010 21-04 80 10 Integrated Automation Facility Controls

Includes: Hardware and/or software that allows the building automation system to monitor and control other facility equipment and systems. Includes Integrated Automation Supplementary Components as appropriate.

Associated Masterformat Sections: 25 50 00 / 01 86 23

[See Fundamental LOD Definitions]

Ε

Uniformat Omniclass

21-05 00 00 E

EQUIPMENT & FURNISHINGS

Associated Masterformat Sections: 01 87 00

E10 21-05 10 Equipment

Associated Masterformat Sections: 11 00 00 / 01 87 13

100	Diagrammatic or schematic model elements:	
	conceptual and/or schematic layout;	
	design performance parameters as defined in the BXP to be associated with model elements as non-graphic information.	

O Vehicle and Pedestrian Equipment

E1010 21-05 10 10 Associated Masterformat Sections: 11 10 00

100	See <u>E10</u>	
200	Schematic layout with approximate size, shape, and location of equipment;	
	design performance parameters as defined in the BXP to be associated with model elements as non-graphic information.	

E1010.10 21-05 10 10 10 Vehicle Servicing Equipment

Includes: Equipment associated with vehicle service facilities.

Associated Masterformat Sections: 11 11 00 / 11 11 19 / 11 11 23 / 11 11 26

100	See <u>E10</u>	
200	See <u>E1010</u>	
300	Modeled as design-specified size, shape, spacing, and location of equipment and associated components;	
	approximate allowances for spacing and clearances required for all specified supports and seismic control;	
	access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location of equipment and associated components;	
	actual size, shape, spacing, and location for supports and seismic control;	
	actual size, shape, and location of service connections and support structure/pads.	
	Actual access/code clearance requirements modeled.	
400	Supplementary components added to the model required for fabrication and field installation.	

E1010.30 21-05 10 10 30 Interior Parking Control Equipment Includes: Equipment associated with the control of movement of vehicle parking.

Associated Masterformat Sections: 11 12 00 / 11 12 13 / 11 12 16 / 11 12 23 / 11 12 26 / 11 12 33

[See <u>E1010.10</u>]

E1010.50 21-05 10 10 50 Lo

Loading Dock Equipment

Includes: Equipment for the protection of service docks and for the loading and unloading of service vehicles.

Associated Masterformat Sections: 11 13 00 / 11 13 13 / 11 13 16 / 11 13 19.13 / 11 13 19.23 / 11 13 26

[See <u>E1010.10</u>]

E1010.70 21-05 10 10 70 Interior Pedestrian Control Equipment Includes: Equipment associated with the control of movement of pedestrians.

Associated Masterformat Sections: 11 14 00 / 11 14 13 / 11 14 16 / 11 14 26 / 11 14 43 / 11 14 53

[See <u>E1010.10</u>]

E1030 21-05 10 30 Associated Masterformat Sections: 11 20 00 **Commercial Equipment**

[See E1010]

E1030.10 21-05 10 30 10 Mercantile and Service Equipment Includes: Equipment used in retail and service stores.

Associated Masterformat Sections: 11 21 00 / 11 21 13 / 11 21 23 / 11 21 33 / 11 21 43 / 11 21 53

[See <u>E1010.10</u>]

E1030.20 21-05 10 30 20 Vault Equipment Includes: Equipment specifically designed for money or valuable material storage, including vault ventilators and specialized security equipment.

Associated Masterformat Sections: 11 16 00 / 11 16 13 / 11 16 16 / 11 16 23

[See <u>E1010.10</u>]

E1030.25 21-05 10 30 25 Teller and Service Equipment

Includes: Equipment specifically designed for handling and transfer of money and other high-security items.

Associated Masterformat Sections: 11 17 00 / 11 17 13 / 11 17 16 / 11 17 23 / 11 17 33 / 11 17 36

[See E1010.10]

Back to TOC

E1030.30 21-05 10 30 30 Includes: Display cases that include refrigeration.

Refrigerated Display Equipment

Associated Masterformat Sections: 11 22 00

[See <u>E1010.10</u>]

E1030.35 21-05 10 30 35 Commercial Laundry and Dry Cleaning Equipment Includes: Equipment for commercial laundry and dry-cleaning operations including coin-operated equipment.

Associated Masterformat Sections: 11 23 00 / 11 23 13 / 11 23 16 / 11 23 19 / 11 23 23 / 11 23 26 / 11 23 33 / 11 23 43

[See <u>E1010.10</u>]

E1030.40

Maintenance Equipment

Includes: Built-in and free-standing equipment for building maintenance.

Associated Masterformat Sections: 11 24 00 / 11 24 13 / 11 24 16 / 11 24 19 / 11 24 23.13

[See <u>E1010.10</u>]

E1030.50 21-05 10 30 50 Hospitality Equipment Includes: Specialized equipment for the purpose of registering, admitting, and controlling rooms and other information at hotels, motels, hospitals, and other similar facilities.

Associated Masterformat Sections: 11 25 00 / 11 25 13

[See <u>E1010.10</u>]

E1030.55 21-05 10 30 55 Unit Kitchens Includes: Manufactured units incorporating plumbing fixtures, appliances, casework and countertops.

Associated Masterformat Sections: 11 26 00

[See <u>E1010.10</u>]

E1030.60 21-05 10 30 60 Photographic Processing Equipment Includes: Photographic film processing equipment and other products for darkroom use.

Associated Masterformat Sections: 11 27 00 / 11 27 13 / 11 27 16

[See <u>E1010.10</u>]

E1030.70 21-05 10 30 70 Postal, Packaging and Shipping Equipment

Includes: Equipment for normal mailing, packaging, shipping, and delivery operations for professional, commercial, and institutional applications.

Associated Masterformat Sections: 11 29 00 / 11 29 23 / 11 29 33 / 11 29 55 / 11 28 23

[See <u>E1010.10</u>]

E1030.75 21-05 10 30 75 Office Equipment

Includes: Computers, printers, copiers, drafting equipment, plotters, carto-stereographs, and other equipment used in offices.

Associated Masterformat Sections: 11 28 00 / 11 28 13 / 11 28 16 / 11 28 19 / 11 28 23

[See E1010.10]

21-05 10 30 80 Foodservice Equipment E1030.80 Includes: Equipment used for liquid and solid food storage, preparation, display, serving, and clean-up in commercial and institutional kitchens and bars.

Associated Masterformat Sections: 11 40 00 / 11 41 00 / 11 41 13 / 11 41 23 / 11 41 26 / 11 41 33 / 11 42 00 / 11 43 00 / 11 41 13 / 11 41 16 / 11 44 00 / 11 44 13 / 11 44 16 / 11 46 00 / 11 46 13 / 11 46 16 / 11 46 19 / 11 47 00 / 11 48 00 / 11 48 13

[See E1010.10]

E1040 21-05 10 40 Associated Masterformat Sections: 11 50 00

Institutional Equipment

[See E1010]

21-05 10 40 10 E1040.10 Educational and Scientific Equipment

Includes: Equipment associated with libraries, education facilities, laboratories, planetariums, observatories, and museums.

Associated Masterformat Sections: 11 50 00 / 11 51 00 / 11 51 13 / 11 51 16 / 11 51 19 / 11 51 23 / 11 52 00 / 11 52 13 / 11 52 16 / 11 52 19 / 11 53 00 / 11 53 13 / 11 53 16 / 11 53 19 / 11 53 23 / 11 53 33 / 11 53 43 / 11 53 53 / 11 55 00 / 11 55 13 / 11 55 16 / 11 56 00 / 11 56 13 / 11 57 00 / 11 59 00 / 11 95 00 / 11 95 13

[See E1010.10]

21-05 10 40 20

E1040.20 Healthcare Equipment Includes: Specialized equipment for healthcare facilities for humans and animals. Includes film illuminators, fluoroscopes, hubbard tubs, radio isotopic equipment, and surgical equipment.

Associated Masterformat Sections: 11 70 00 / 05 45 23 / 11 71 00 / 11 72 00 / 11 73 00 / 11 74 00 / 11 75 00 / 11 76 00 / 11 77 00 / 11 78 00 / 11 78 13 / 11 78 16 / 11 78 19 / 11 79 00

[See E1010.10]

E1040.40 21-05 10 40 40 Religious Equipment Includes: Built-in and free-standing religious equipment, including baptistery and chancel fittings.

Associated Masterformat Sections: 11 91 00 / 11 91 13

[See E1010.10]

E1040.60 21-05 10 40 60 Security Equipment Includes: Equipment specifically designed for secure operations.

Associated Masterformat Sections: 11 18 00 / 11 18 13 / 11 18 16 / 11 18 23

Back to TOC

[See <u>E1010.10</u>]

E1040.70 21-05 10 40 70 Detention Equipment Includes: Equipment specifically designed for detention facilities.

Associated Masterformat Sections: 11 19 00 / 01 87 13 / 11 19 13 / 11 19 16

[See <u>E1010.10</u>]

E1060 21-05 10 60 Residential Equipment

Includes: Built-in and free-standing appliances and other components specifically for residential use.

Associated Masterformat Sections: 11 30 00

[See <u>E1010</u>]

E1060.10 21-05 10 60 10 Residential Appliances Associated Masterformat Sections: 11 31 00 / 11 31 13 / 11 31 23

[See <u>E1010.10</u>]

E1060.50 21-05 10 60 50 Associated Masterformat Sections: 11 33 00 **Residential Stairs**

[See <u>B1080</u>]

E1060.70	21-05 10 60 70	Residential Ceiling Fans
Associated Masterform	at Sections: 11 34 00	-

[See E1010.10]

E1070 21-05 10 70 Entertainment and Recreational Equipment Includes: Equipment for use in athletic, recreational, and therapeutic activities.

Associated Masterformat Sections:

[See <u>E1010</u>]

E1070.10 21-05 10 70 10 Theater and Stage Equipment Includes: Equipment for support of theatrical, instrumental, and voice programs. Includes cycloramas, entertainment ticket dispensers, scenery and flats, and tormentors.

Associated Masterformat Sections: 11 61 00 / 11 61 13 / 11 61 23 / 11 61 33 / 11 61 43

[See E1010.10]

E1070.20 21-05 10 70 20 Musical Equipment Includes: Musical instruments, including prefabricated and field assembled instruments. Associated Masterformat Sections: 11 62 00 / 11 62 13 / 11 62 16 / 11 62 19 [See E1010.10]

Back to TOC

E1070.50 21-05 10 70 50 Athletic Equipment

Includes: Equipment for use in interior athletic and exercise activities.

Associated Masterformat Sections: 11 66 00 / 11 66 13 / 11 66 23 / 11 66 43 / 11 66 53 [See E1010.10]

E1070.60 21-05 10 70 60 Recreat

Recreational Equipment

Includes: Equipment for use in recreational activities. Includes curling rinks and pistol and rifle range equipment.

Associated Masterformat Sections: 11 67 00 / 11 67 13 / 11 67 23 / 11 67 33 / 11 67 43 / 11 67 53

[See <u>*E1010.10</u>]</u>*

E1090 21-05 10 90 Associated Masterformat Sections: 11 90 00 [See <u>E1010]</u>

Other Equipment

E1090.10 21-05 10 90 10 Solid Waste Handling Equipment Includes: Equipment involving the collection, shredding, compaction, removal and incineration of trash and other solid waste Associated Masterformat Sections: 11 82 00 / 01 87 13 / 11 82 13 / 11 82 19 / 11 82 23 / 11 82 26 / 11 82 29 / 11 82 33 / 11 82 36

[See <u>E1010.10</u>]

E1090.30 21-05 10 90 30 Agricultural Equipment Includes: Equipment related to land cultivating, raising crops, and feeding, breeding, and raising of livestock.

Associated Masterformat Sections: 11 92 00 / 11 92 13 / 11 92 16 / 11 92 19 / 11 92 23

[See E1010.10]

E1090.40 21-05 10 90 40 Horticultural Equipment Includes: Equipment related to cultivating flowers, fruits, vegetables, or ornamental plants.

Associated Masterformat Sections: 11 93 00 / 11 93 13 / 11 93 16 / 11 93 19 / 11 93 23 / 11 93 26 / 11 93 29 / 11 93 33 / 32 86 00

[See <u>E1010.10</u>]

E1090.60 21-05 10 90 60 Decontamination Equipment Includes: Equipment associated with decontamination operations.

Associated Masterformat Sections:

[See <u>*E1010.10</u>]</u>*

E20

21-05 20

Furnishings

Associated Masterformat Sections: 12 00 00 / 01 87 16

Back to TOC

100	A schematic model element or symbol that is not distinguishable by type or material.	
	Types, layouts, and locations are still flexible.	

E2010

21-05 20 10

Fixed Furnishings

Associated Masterformat Sections:

100	See <u>E20</u>	
200	Generic model elements with approximate nominal size.	
	Placement and quantity remains flexible.	
	•	

Fixed Art

E2010.10 21-05 20 10 10

Includes: Interior and exterior fixed art objects.

Associated Masterformat Sections: 12 10 00 / 12 11 00 / 12 12 00 / 12 12 23 / 12 12 26 / 12 14 00 / 12 17 00 / 12 19 00

100	See <u>E20</u>	
200	See <u>E2010</u>	
300	Modeled types with specific dimensions, locations, and quantities.	
350	Include any applicable service or installation clearances.	
	Include any applicable support and connection points.	
400	Supplementary components added to the model required for fabrication and field installation.	

E2010.20 21-05 20 10 20 Window Treatments

Includes: Interior window coverings and associated hardware and controls.

Associated Masterformat Sections: 12 20 00 / 12 21 00 / 12 22 00 / 12 23 00 / 12 24 00 / 12 25 00

[See <u>E2010.10</u>]

E2010.30

21-05 20 10 30

Casework

Includes: Custom and manufactured stock design steel, wood, and laminate faced cabinets and other casework units. Includes countertops with integral sinks, fixtures and accessories.

Associated Masterformat Sections: 12 30 00 / 12 35 00 / 12 35 17 / 12 35 25 / 12 35 30 / 12 35 33 / 12 35 50 / 12 35 53 / 12 35 59 / 12 35 70 / 12 35 91 / 12 36 00 [See <u>E2010.10</u>]

Back to TOC

E2010.70 21-05 20 10 70 Fixed Multiple Seating

Includes: Fixed, and telescoping seating for theaters, auditoriums, lecture halls, stadiums, arenas, gymnasiums, religious buildings, restaurants, and other facilities where multiple seating is required.

Associated Masterformat Sections: 12 60 00 / 12 61 00 / 12 63 00 / 13 34 16.53 / 12 64 00 / 12 65 00 / 12 66 00 / 12 67 00 / 12 68 00

[See <u>E2010.10</u>]

E2010.90 21-05 20 10 90 Other Fixed Furnishings

Includes: Fixed artificial plants, planters, and accessories.

Associated Masterformat Sections: 12 90 00 / 12 92 00 / 12 92 13 / 12 92 33 / 12 92 43 [See <u>E2010.10</u>]

E2050 21-05 20 50 Movable Furnishings

Includes: Items of moveable furniture and furnishing accessories. Includes furniture for a variety of uses including classroom, dormitory, ecclesiastical, hotel and motel, laboratory, library, lounge, medical, office, restaurant, and residential. Associated Masterformat Sections:

[See <u>E2010</u>]

E2050.1021-05 20 50 10Movable ArtIncludes:Interior and exterior moveable art objects such as paintings, and sculpture.Associated Masterformat Sections:12 10 00 / 12 14 00 / 12 19 00[See E2010.10]

E2050.30 21-05 20 50 30 Furniture Includes: Movable interior furniture. Associated Masterformat Sections: 12 50 00 / 12 51 00 / 12 52 00 / 12 52 23 / 12 52 70 / 12 53 00 / 12 54 00 / 12 54 13 / 12 54 16 / 12 55 00 / 12 56 00 / 12 56 33 / 12 56 39 / 12 56 43 / 12 56 51 / 12 56 52 / 12 56 53 / 12 56 70 / 12 57 00 / 12 57 13 / 12 57 16 / 12 58 00 / 12 59 00 [See E2010.10]

 E2050.40
 21-05 20 50 40
 Accessories

 Includes:
 Interior furnishing accessories not attached to permanent construction.

 Associated Masterformat Sections:
 12 40 00 / 12 41 00 / 12 42 00 / 12 43 00 / 12 44 00 / 12 44 00 / 12 44 00 / 12 45 00 / 12 46 00 / 12 48 00

 [See E2010.10]
 E2010.10

E2050.60 21-05 20 50 60 Movable Multiple Seating Includes: Portable seating for auditoriums, lecture halls, stadiums, arenas, gymnasiums, religious buildings, restaurants, and other facilities where multiple seating is required. Associated Masterformat Sections: 12 60 00 / 12 62 00 / 12 65 00 / 12 67 00 / 12 68 00 [See E2010.10]

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

E2050.90 21-05 20 50 90 Other Movable Furnishings Includes: Moveable artificial plants, and planters. Associated Masterformat Sections: 12 90 00 / 12 92 00 / 12 92 13 / 12 92 33 / 12 92 43 [See E2010.10]

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

21-06 00 00 SPECIAL CONSTRUCTION & DEMOLITION

Associated Masterformat Sections:

F

F10 21-06 10 Associated Masterformat Sections: 01 88 13 **Special Construction**

Integrated Construction

F101021-06 10 10Associated Masterformat Sections:[See Fundamental LOD Definitions]


F1020 21-06 10 20 Associated Masterformat Sections: 13 30 00 / 0

Special Structures

Associated Masterformat Sections: 13 30 00 / 01 88 13 [See Fundamental LOD Definitions]

F1020.40 21-06 10 20 40 Special Structures: Metal Building Systems Includes: Prefabricated buildings and structures assembled on temporary and permanent foundations.

Associated Masterformat Sections: 13 34 00 / 01 88 13 / 13 34 13 / 13 34 16 / 13 34 19 / 13 34 56



F1020.40.10 21-06 10 20 40 Special Structures: Metal Building Systems -Primary Framing and Bracing

Includes: Prefabricated buildings and structures assembled on temporary and permanent foundations. Associated Masterformat Sections: 13 34 00 / 01 88 13 / 13 34 13 / 13 34 16 / 13 34 19 / 13 34 56

200	 Generic mass of frame shown in an approximate location, and a general span/direction with a design narrative for conceptual pricing. Model elements to include: Framing grids defined. Sections shapes shown but profiles, tapers and plate thicknesses and flange widths still flexible. Primary braced bay locations End wall framing type (i.e., main frame versus post and beam) Crane runways 	208 F1020.40-LOD 200 Metal Building Systems - Primary Framing
300	 Metal Building System components including: End wall or wind column End frame main members Module or interior columns Frames and main members Columns Frames and wall diagonal bracing Crane beams Element modeling to include: Specific sizes of frame structural members, all with correct orientation Web tapers Frame connection type (Extended/Flush) Any lateral bracing components connecting to frame or foundation (i.e., portal frames, fixed base columns, diagonal bracing - rods or cables, struts) all with specific sizes and orientation. 	209 F1020.40-LOD 300 Metal Building Systems - Primary Framing

350	Element modeling to include:	
	 Base plate locations Bracing components (i.e. gussets) Critical or large elements of connections applied to all structural steel connections such as base plates, gusset plates, anchor rods, etc. Clips required for connection to secondary framing 	
	 Any miscellaneous steel members with correct size, shape, orientation and material required for the frame structure. (i.e., roof beams, spandrels) 	
	Any steel structure reinforcement such as web stiffeners, connection plate stiffeners, sleeve penetrations, etc. required for coordination.	210 F1020.40-LOD 350 Metal Building Systems - Primary Framing

400	Element modeling to include fabrication level information:	
	 Welds Reinforcement plates Coping of members Bolts, nuts, washers, etc. Holes, slots, etc., including holes for future element attachments All assembly elements 	
		211 F1020.40-LOD 400 Metal Building Systems - Primary Framing

F1020.40.20 21-06 10 20 40

Special Structures: Metal Building Systems -Secondary Framing

Includes: Prefabricated buildings and structures assembled on temporary and permanent foundations. Associated Masterformat Sections: 13 34 00 / 01 88 13 / 13 34 13 / 13 34 16 / 13 34 19 / 13 34 56

200	Generic mass of special structure with system typically noted with a design narrative for conceptual pricing. Generic open wall conditions identified (i.e., open for material by others, open for passage, etc.) Approximate overall depth and extent represented by secondary roof and wall framing members.	212 F1020.40-LOD 200 Metal Building Systems - Secondary Framing
300	 Metal Building System components, including: Purlins and bridging Eave strut Sidewall girts Endwall girts Sag braces Framed openings (jambs, headers, etc.) Window sub-frames Walk door sub-frames Wall member connection type (Flush/Bypass/Inset) Base condition (i.e., angle, channel, tube) Element modeling to include: Specific sizes of main structural members, (mass for open web members), all with correct orientation 	Visit of the secondary Framing



Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

350	Element modeling to include:	
	 Nested members Connections for member bracing Clips joining secondary framing members Large elements of typical connections applied to all secondary steel connections such as girt to column, purlin to rafter, jamb to girt, header to jamb, etc. Secondary angles, including sheeting angles and rake angles Base attachment members Any miscellaneous secondary steel members with correct orientation, i.e. canopies, parapets, door framing, etc. Web members and bridging for open web purlins For bar joist, see Steel Open Web Joists LOD. 	214 F1020.40-LOD 350 Metal Building Systems- Secondary Framing
400	Element modeling to include fabrication level information: • Welds • Bolts, nuts, washers, screws, and fasteners • Coping of members • Holes cut for bracing • Nested member attachments • All assembly elements • Continuous web vs. open web	215 F1020.40-LOD 400 Metal Building Systems - Secondary Framing

F1020.40.30 21-06 10 20 40

Special Structures: Metal Building Systems -Cladding and Exterior Trim

Includes: Prefabricated buildings and structures assembled on temporary and permanent foundations.

Associated Masterformat Sections: 13 34 00 / 01 88 13 / 13 34 13 / 13 34 16 / 13 34 19 / 13 34 56

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

200	Element modeling to include:	
	 Panel: Generic mass of panel with a generic profile or graphical texture shown, Openings/Voids are represented, identifying cladding boundaries within the wall/roof plane. Trim: Major exterior trim used to separate roof and walls and trim used for aesthetic accent, represented by a generic trim profile. 	
		216 F1020.40-LOD 200 Metal Building Systems – Cladding and Exterior Trim
300	Element modeling to include:	
	 Panel: Panel with actual profile or graphical texture shown, filling the boundary set by the plane object. Significant accessories (i.e., light transmitting panels, ridge vents, curbs) shown Openings/Voids are represented in true dimensions/locations. 	
	 Trim: Major trims (primary exterior pieces) are shown, represented by the actual trim profile, thickness, and color. Gutters Corner boxes Corners Open wall trim Framed opening trim 	217 F1020.40-LOD 300 Metal Building Systems – Cladding and Exterior Trim

350	Element modeling to include:	
	 Panel: Actual profile modeled filling the boundary set by the plane object. Closures Downspouts Trim: Minor trims (end caps, transition pieces, etc.) are shown generically. 	
	Other non-graphic information may be included such as: Textual information on installation details	218 F1020.40-LOD 350 Metal Building Systems – Cladding and Exterior Trim
		F1020.40-LOD 350 Metal Building Systems – Cladding and Exterior Trim

400	Element modeling to include fabrication level information:	
	Danah	
	Panel: O Individual panel objects, with actual	
	profile shown, positioned accurately	
	within the building plane boundary	
	and shown at installed length.	
	 Fasteners at critical locations 	
	 Closures 	
	 Cinch straps 	
	 Caulk/mastic and other field- 	
	installed weather-tightness	
	materials shown at critical locations	
	Trim:	
	 Minor trims (end caps, transition 	
	pieces, etc.) are shown accurately.	
	 Attachment or accessories 	
	(fasteners, etc.) shown at critical	
	o Caulk/mastic and other field-	
	 Caulk/mastic and other field- installed weather-tightness 	
	materials shown at critical locations	
	Other non-graphic information may be included such	
	as:	
	Additional material and its installation instructions	
	required for proper installation	
	Mark identification that correlates with bill of material	
	(i.e., piece mark) Fastener material and installation instructions	
	Caulk/mastic and other field-installed weather-	
	tightness materials and installation instructions	
l l		

F1030 21-06 10 30 Associated Masterformat Sections: [See Fundamental LOD Definitions] **Special Function Construction**

F1050 21-06 10 50 Associated Masterformat Sections: [See Fundamental LOD Definitions] **Special Facility Components**

F1060 21-06 10 60 Athletic and Recreational Special Construction Includes: Special construction for athletic and recreational activities that are directly related to the adjacent construction.

Associated Masterformat Sections: 13 28 00

[See Fundamental LOD Definitions]

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.</u>

Omniclass Uniformat

F1080

21-06 10 80

Special Instrumentation

Includes: Instrumentation for measuring and recording phenomena such as stresses in structures, solar and wind energy, and effects of earthquakes.

Associated Masterformat Sections: 13 50 00

[See Fundamental LOD Definitions]

F20 Associated Masterformat Sections:

21-06 20

Facility Remediation

F2010 21-06 20 10 Hazardous Materials Remediation Includes: Remediation for abatement and removal and disposal of contaminated materials within structures. Associated Masterformat Sections: 02 80 00

[See Fundamental LOD Definitions]

F30 21-06 30 Associated Masterformat Sections:

Demolition

Structure Demolition F3010 21-06 30 10 Includes: Complete removal and disposal of structures. Associated Masterformat Sections: 02 41 16

[See Fundamental LOD Definitions]

F3030 21-06 30 30 Includes: Removal and disposal of parts of structures. Selective Demolition

Associated Masterformat Sections: 02 41 19

[See Fundamental LOD Definitions]

F3050 21-06 30 50 Structure Moving Includes: Preparation and processes of relocating and raising structures.

Associated Masterformat Sections: 02 43 00

[See Fundamental LOD Definitions]

G 21-07 00 00 **BUILDING SITEWORK**

Associated Masterformat Sections: 01 89 00

G10 21-07 10 Associated Masterformat Sections: 01 89 13 Site Preparation

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

100	A simple topographic surface is provided.	
		219 G10-LOD-100 Site Preparation
200	Element modeling to include: • Approximate size and shape of foundation element • Approximate size/location of utilities and structures • Approximate code and clearance requirements • Approximate pipe material • Rough modeling of site grading	

G1010 21-07 10 10 Site Clearing

Includes: Removal of vegetation from the site, including stripping of sod and soil, and tree pruning for site clearing.

Associated Masterformat Sections: 31 10 00 / 31 11 00 / 31 13 00 / 31 14 00 / 31 14 13 / 31 14 16

G1020 21-07 10 20 Site Elements Demolition

Includes: Removal of above and below grade site improvements. Associated Masterformat Sections: 02 41 13

G1030 21-07 10 30

Includes: Relocation of utility systems.

21-07 10 50

Site Remediation

Site Element Relocations

Includes: Remediation of contaminated sites. Associated Masterformat Sections: 02 50 00 / 01 89

Site Earthwork G1070 21-07 10 70 Includes: Moving earth to establish new contours and elevations.

Associated Masterformat Sections: 31 20 00 / 01 89 13

G1070.10 21-07 10 70 10 Includes: Earthmoving to reshape contours.

Grading

Associated Masterformat Sections: 31 20 00 / 01 89 13

Back to TOC

G1050

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

100	Proposed Surfaces shown as a plane.	
200	Proposed Surface: Generic Surface Interpolation between the following elements: Building Envelope at Finish Floor, Finish Grade at Retaining Walls, Grading Limits. Curbs, hardscape, finish surface at building envelopes.	
300	Proposed Surface: Complete and accurate surface definition based on defined fine grading, grade breaks, curbs, hardscape, buildings, swales, etc. Local Coordinate Control. Shared Coordinate from Building Grid base point to real-world project control	
350	Include existing Surface: 3D surface generated from site topography, with grade breaks and lines as needed to define accurate surface. 3D site features included if provided by surveyor (i.e. walls, signage, stairs, etc., as defined in Survey LOC-Grade). Added definition from supplemental survey, revised limits of work	
400	Surface modeled to facilitate robotic controlled grading and GPS grade-control systems.	

G20

21-07 20

Site Improvements

Associated Masterformat Sections: 01 89 16

100 Diagrammatic or schematic model elements.	
---	--

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

200	Element modeling to include:	
	 Approximate size and shape of foundation element Approximate size/location of utilities and structures Approximate code and clearance requirements Rough modeling of site grading Local structural building grids defined in model and coordinated with global state plane coordinate system for site model. 	

G2010 21-07 20 10 Roadways

Includes: Pavement, curbs and gutters, appurtenances, lighting, and vehicle fare collection for roadways. May Include: Site earthwork.

Associated Masterformat Sections: 01 89 16

[See Fundamental LOD Definitions]

G2020 21-07 20 20 Parking Lots

Includes: Pavement, curbs and gutters, appurtenances, lighting, and parking control equipment for parking lots. May Include: Site earthwork

Associated Masterformat Sections: 01 89 16

[See Fundamental LOD Definitions]

G2020.10 21-07 20 20 10 Parking Lot Pavement

Includes: Prepared and compacted soil and granular layers placed prior to installation of parking lot pavement. Includes: Finished parking lot pavement of granular and asphaltic materials. Includes: Finished parking lot pavement with high bending resistance, usually of concrete. Includes: Blocks or tiles used for parking lot pavement. Unit pavers set in mastic, sand, or mortar.

Associated Masterformat Sections: 32 10 00 / 32 12 00 / 32 13 00 / 32 14 00 / 32 15 00

100	See <u>G20</u>	
200	See <u>G20</u>	
300	Specific thickness of pavement and substrate modeled. All drainage slopes modeled.	
350	Openings for drains and other services modeled.	

G2020.20

21-07 20 20 20

Parking Lot Curbs and Gutters

Includes: Construction at perimeter of parking lot pavement to separate pavement from adjacent surfaces, provide vehicular restraint, and facilitate drainage.

Associated Masterformat Sections: 32 16 13

100	See G20
200	See <u>G20</u>
300	Full extents of curbs and gutters (above and below grade) are modeled.
350	Element modeling to include:
	 Reinforcing Pour stops Expansion joints

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

G2020.40 21-07 20 20 40

Includes traffic signals, signage, striping.

Associated Masterformat Sections: 32 17 00 / 32 17 13 / 32 17 43 / 10 14 53 / 32 17 23

G2030 21-07 20 30 Pedestrian Plazas and Walkways

Includes: Pavement, curbs and gutters, appurtenances, lighting, and pedestrian control equipment for pedestrian plazas and walkways. Includes exterior steps and ramps. May Include: Site earthwork.

Parking Lot Appurtenances

Associated Masterformat Sections: 01 89 16

G2040

21-07 20 40 Airfields

Includes: Pavement, curbs and gutters, appurtenances, lighting, and airfield signally and control equipment for airfields.May Include: Site earthwork.

Associated Masterformat Sections: 01 89 16

G2050 21-07 20 50 Athletic, Recreational, and Playfield Areas Includes: Surfacing, fencing, equipment, grandstands and bleachers, and lighting for athletic, recreational, and playfield areas. May Include: Site earthwork.

Associated Masterformat Sections: 01 89 16

G2060 21-07 20 60 [See Fundamental LOD Definitions]

Site Development

G2080 21-07 20 80 [See Fundamental LOD Definitions]

Landscaping

Includes: Trees

Associated Masterformat Sections: 31 20 00 / 01 89 13

G30

21-07 30

Liquid and Gas Site Utilities

Associated Masterformat Sections: 01 89 19

100	Narrative that references the grading model	
200	Approximate sizes, vertical control, and apparatus.	

G3010 21-07 30 10 Water Utilities

Includes: Water distribution for domestic consumption, fire fighting, and irrigation for a facility site and for multiple facilities. Includes trenching and backfilling. Includes Liquid and Gas Site Utilities Supplementary Components as appropriate.

Associated Masterformat Sections: 33 10 00

1	00	See <u>G30</u>	
2	200	See G30	

G3010.10 21-07 30 10 10 Site Domestic Water Distribution

Includes: Supply wells, piping, equipment, storage tanks, and water ponds and reservoirs.

Associated Masterformat Sections: 01 89 19 / 33 21 00 / 33 11 00 / 33 12 00 / 33 12 13 33 12 16 / 33 12 19 / 33 12 23 / 33 12 33 / 33 13 00 / 33 16 00 / 33 47 19.13 / 33 47 13.13 33 47 16.13

100	See <u>G30</u>	
200	See G30	

G3010.30 21-07 30 10 30 Site Fire Protection Water Distribution

Includes: Supply wells, piping, equipment, storage tanks, and water ponds and reservoirs.

Associated Masterformat Sections: 01 89 19 / 33 21 00 / 33 11 19 / 33 12 00 / 33 12 13 / 33 12 16 / 33 12 19 / 33 12 23 / 33 12 33 / 33 16 00 / 33 47 19.33 / 33 47 13.13 / 33 47 16.13

100	See <u>G30</u>	
200	See G30	

G3020 21-07 30 20 Sanitary Sewerage Utilities

Includes: Sanitary sewerage for a facility site and for multiple facilities. Includes piping, septic tanks that serve multiple facilities, structures, and lagoons. Includes trenching and backfilling. Includes Liquid and Gas Site Utilities Supplementary Components as appropriate.

Associated Masterformat Sections: 33 30 00 / 01 89 19

100	See <u>G30</u>	
200	See G30	

G3020.20

21-07 30 20 20

Sanitary Sewerage Piping

Associated Masterformat Sections: 33 31 00 / 33 33 00 / 33 34 00

100	See <u>G30</u>	
200	See G30	
300	Specific elevations, sizes, materials	

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

G3020.50 21-07 30 20 50 Sanitary Sewerage Structures

Associated Masterformat Sections: 33 39 00 / 33 39 13 / 33 39 23

100	See <u>G30</u>	
200	Approximate structure types, sizes and materials	
300	Specific structure elements at all locations, specific sizes and materials	

G3030 21-07 30 30 Storm Drainage Utilities

Includes: Storm drainage for surface or combination of surface and subsurface water for a facility site or for multiple facilities. Includes piping, culverts, water drains, drainage pumps, Subdrainage, and storm drainage ponds and reservoirs. Includes trenching and backfilling. Includes Liquid and Gas Site Utilities Supplementary Components as appropriate.

Associated Masterformat Sections: 01 89 19

100	See <u>G30</u>	
200	See G30	

G3050

21-07 30 50

Site Energy Distribution

Includes: Energy distribution for a facility site or multiple facilities. Includes hydronic heating, steam energy, and hydronic cooling distribution. Includes trenching and backfilling. Includes Liquid and Gas Site Utilities Supplementary Components as appropriate.

100	See <u>G30</u>	
200	See G30	

G3060

21-07 30 60

Site Fuel Distribution

Includes: Gas, fuel-oil, gasoline, diesel fuel, and aviation fuel distribution for a facility site or multiple facilities. Includes trenching and backfilling. Includes Liquid and Gas Site Utilities Supplementary Components as appropriate.

100	See <u>G30</u>	
200	See G30	

G3090

21-07 30 90

Liquid and Gas Site Utilities Supplementary Components

Includes: Common work results for utilities and instrumentation and control to be included in liquid and gas utility elements above as appropriate.

These components are typically modeled as part of other assemblies listed in the tables above. Do not assign this Uniformat classification unless a supplementary component is modeled independently of another assembly.

G40



Associated Masterformat Sections: 01 89 26

Electrical Site Improvements

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved

This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

100	Diagrammatic or schematic model elements:	
	conceptual and/or schematic layout;	
	design performance parameters as defined in the BXP to be associated with model elements as non-graphic information.	

G4010 21-07 40 10 Site Electric Distribution Systems

Description: Electrical wiring systems to distribute electrical power to on the Site. Includes Duct Banks, Pullboxes, vaults and transformers from the utility point of connection, to the building's main electric room. Associated Masterformat Sections: 01 89 26

100	See <u>G40</u>	
200	Generic model elements in schematic layout with:	
	approximate size, shape, and location of equipment;	
	approximate access/code clearance requirements modeled;	
	design performance parameters as defined in the BXP to be associated with model elements as non-graphic information.	
300	Modeled as design-specified size, shape, spacing, and location of raceways/ boxes/enclosures/duct banks in the power distribution system	
	specified size, shape, spacing, and location of equipment and associated components;	
	approximate allowances for spacing and clearances required for all specified hangers, supports and seismic control	
	access/code clearance requirements modeled	
		220 G4010-LOD-300 Site Electric Distribution Systems
350	Modeled as actual size, shape, spacing, and location of raceways/ boxes/enclosures/duct banks in the power distribution system;	
	actual size, shape, spacing, and location for supports and seismic control;	
	actual size, shape, and location/connections of equipment and support structure/pads.	
	Actual access/code clearance requirements modeled	
		221 G4010-LOD-350 Site Electric Distribution Systems

400	Supplementary components added to the model required for fabrication and field installation.	
		222 G4010-LOD-400 Site Electric Distribution Systems

G4050 21-07 40 50 Site Lighting

Description: Luminaires, lighting equipment, ballasts, and accessories. Includes fluorescent, high intensity discharge, incandescent, mercury vapor, neon, and sodium vapor lighting. Includes Pole Mount, Building Mount and on-grade fixtures for exterior lighting. Associated Masterformat Sections: 26 56 29

100	See <u>G40</u>	
200	Generic elements in schematic layout with:	
	approximate size, shape, and location of equipment;	
	approximate access/code clearance requirements modeled;	
	design performance parameters as defined in the BXP to be associated with model elements as non-graphic information.	
300	Modeled as design-specified size, shape, spacing, and location of lighting fixtures;	
	approximate allowances for spacing and clearances required for all specified hangers, supports and seismic control;	
	required pole bases and footing elements;	
	access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location of lighting fixtures;	
	actual size, shape, spacing, and location for supports and seismic control;	
	actual size, shape, and location/connections of equipment and support structure/pads.	
	Actual access/code clearance requirements modeled.	
400	Supplementary components added to the model required for fabrication and field installation.	

21-07 50 Site Communications G50

Diagrammatic or schematic model elements: 100

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.</u>

conceptual and/or schematic layout;	
design performance parameters as defined in the BXP to be associated with model elements as non-graphic information.	

G5010 – Site Communications Systems Description: Conduit Systems for routing of Communication trunk systems.

Associated Masterformat Sections: 33 80 00

100	See <u>G50</u>	
200	Generic elements in a schematic layout with:	
	approximate size, shape, and location of equipment;	
	approximate access/code clearance requirements modeled;	
	design performance parameters as defined in the BXP to be associated with model elements as non-graphic information.	
300	Modeled as design-specified size, shape, spacing, and location of raceways, boxes, and enclosures in the power distribution system;	
	size, shape, spacing, and location of equipment and associated components;	
	approximate allowances for spacing and clearances required for all specified hangers, supports and seismic control;	
	access/code clearance requirements modeled.	
350	Modeled as actual size, shape, spacing, and location of raceways, boxes, and enclosures in the power distribution system;	
	size, shape, spacing, and location for supports and seismic control;	
	size, shape, location, and connections of equipment and support structure or pads;	
	floor and wall penetration elements are modeled.	
	Actual access/code clearance requirements modeled.	
400	Supplementary components added to the model required for fabrication and field installation.	

G90

21-07 90

Miscellaneous Site Construction

Associated Masterformat Sections: 01 89 29

G9010

21-07 90 10

Tunnels

Includes: Vehicular, pedestrian, and service tunnels. Includes tunnel boring, bracing and jacking work, linings and casing, grouting support systems, boring machines, and control and spoil removal systems. Includes Tunnel Construction Related Activities as appropriate.

Associated Masterformat Sections: 31 70 00 / 01 89 29

Back to TOC

Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

Level of Development Specification Version: 2017

Uniformat Omniclass

[See Fundamental LOD Definitions]



Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

N/A23-13STRUCTURAL AND EXTERIOR
ENCLOSURE PRODUCTSN/A23-13-23Mechanical Fasteners, Adhesives,

and Sealants

N/A 23-13 23 11 Mechanical Fasteners – L-Bolt

Includes: Cast-in anchors per American Concrete Institute 318 building code.

Associated Masterformat Sections: N/A

200	Refer to the model element of the main assembly being connected.	N/A
300	Refer to the model element of the main assembly being connected.	N/A
350	 Element modeling to include: Anchor Length Embedment Length Projection Length Edge Distance Zone Spacing Zone Geometry, base size without threads Required non-graphic information associated with model elements to include: Anchor materials defined Anchor type defined Base material type (steel, concrete, masonry, etc) Base material strength Base material condition (New, existing, cracked, uncracked, saturated, etc.) Finishes, i.e. primed, galvanized, etc. 	LOD 350 L-Bolt Anchor


information: Anchor Thr Anchor Wa Anchor Nut Other non-graphic ir as: Mark identi material (i.e Member fin Fastener fin	shers	LOD 400 L-Bolt Anchor
--	-------	-----------------------

N/A 23-13 23 11 Mechanical Fasteners – J-Bolt

Includes: Cast-in anchors per American Concrete Institute 318 building code.

Associated Masterformat Sections: N/A

200	Refer to the model element of the main assembly being connected.	N/A
300	Refer to the model element of the main assembly being connected.	N/A
350	 Element modeling to include: Anchor Length Embedment Length Projection Length Edge Distance Zone Spacing Zone Geometry, base size without threads Required non-graphic information associated with model elements to include: Anchor materials defined Anchor type defined Base material type (steel, concrete, masonry, etc) Base material strength Base material condition (New, existing, cracked, uncracked, saturated, etc.) Finishes, i.e. primed, galvanized, etc. 	LOD 350 J-Bolt Anchor



N/A 23-13 23 11 Mechanical Fasteners – Hex Head Bolt with

Washer

Includes: Cast-in anchors per American Concrete Institute 318 building code.

Associated Masterformat Sections: N/A

200	Refer to the model element of the main assembly being connected.	N/A
300	Refer to the model element of the main assembly being connected.	N/A

350	Element modeling to include:	
	 Anchor Length Embedment Length Projection Length Edge Distance Zone Spacing Zone Geometry, base size without threads Required non-graphic information associated with model elements to include:	
	 Anchor materials defined Anchor type defined Base material type (steel, concrete, masonry, etc) Base material strength Base material condition (New, existing, cracked, uncracked, saturated, etc.) Finishes, i.e. primed, galvanized, etc. 	
		LOD 350 Hex Head Bolt with Washer
400	 Element modeling to include fabrication level information: Anchor Threads Anchor Washers Anchor Nuts Other non-graphic information may be included such as: Mark identification that correlates with bill of material (i.e., piece mark) Member finish (primer, galvanized, etc.) Fastener finish (i.e., black, zinc electroplated, hot-dipped galvanized) 	LOD 400 Hex Head Bolt with Washer

N/A

23-13 23 11

Mechanical Fasteners – Welded Headed Stud Bolt

Includes: Cast-in anchors per American Concrete Institute 318 building code.

Associated Masterformat Sections: N/A

200	Refer to the model element of the main assembly being connected.	N/A
300	Refer to the model element of the main assembly being connected.	N/A
350	 Element modeling to include: Anchor Length Embedment Length Projection Length Edge Distance Zone Spacing Zone Geometry, base size without threads Required non-graphic information associated with model elements to include: Anchor materials defined Anchor type defined Base material type (steel, concrete, masonry, etc) Base material strength Base material condition (New, existing, cracked, uncracked, saturated, etc.) Finishes, i.e. primed, galvanized, etc. 	LOD 350 Welded Headed Stud Bolt

400	Element modeling to include fabrication level information:	
	Anchor ThreadsAnchor WashersAnchor Nuts	
	Other non-graphic information may be included such as:	
	 Mark identification that correlates with bill of material (i.e., piece mark) Member finish (primer, galvanized, etc.) Fastener finish (i.e., black, zinc electroplated, hot-dipped galvanized) 	
		LOD 400 Welded Headed Stud Bolt

N/A 23-13 23 11 Mechanical Fasteners – Adhesive Anchor

Includes: Post-installed anchors per American Concrete Institute 318 building code.

Associated Masterformat Sections: N/A

200	Refer to the model element of the main assembly being connected.	N/A
300	Refer to the model element of the main assembly being connected.	N/A

350	Element modeling to include:	
	 Anchor Length Embedment Length Projection Length Edge Distance Zone Spacing Zone Geometry, base size without threads 	
	Required non-graphic information associated with model elements to include:	
	 Anchor materials defined Anchor type defined Base material type (steel, concrete, masonry, etc) Base material strength Base material condition (New, existing, cracked, uncracked, saturated, etc.) Finishes, i.e. primed, galvanized, etc. Hole preparation specification 	
		LOD 350 Adhesive Anchor
400	 Element modeling to include fabrication level information: Anchor Threads Anchor Washers Anchor Nuts Other non-graphic information may be included such as: Mark identification that correlates with bill of material (i.e., piece mark) Member finish (primer, galvanized, etc.) Fastener finish (i.e., black, zinc electroplated, hot-dipped galvanized) 	
		LOD 400 Adhesive Anchor

N/A 23-13 23 11 Mechanical Fasteners – Undercut Anchor

Includes: Post-installed anchors per American Concrete Institute 318 building code.

Associated Masterformat Sections: N/A

200	Refer to the model element of the main assembly being connected.	N/A
300	Refer to the model element of the main assembly being connected.	N/A
350	Element modeling to include: • Anchor Length • Embedment Length • Projection Length • Edge Distance Zone • Spacing Zone • Geometry, base size without threads Required non-graphic information associated with model elements to include: • Anchor materials defined • Anchor materials defined • Base material type (steel, concrete, masonry, etc) • Base material strength • Base material condition (New, existing, cracked, uncracked, saturated, etc.) • Finishes, i.e. primed, galvanized, etc. • Hole preparation specification	LOD 350 Undercut Anchor

400	Element modeling to include fabrication level information:	_
	 Anchor Threads Anchor Washers Anchor Nuts Other non-graphic information may be included such as: Mark identification that correlates with bill of material (i.e., piece mark) Member finish (primer, galvanized, etc.) Fastener finish (i.e., black, zinc electroplated, hot-dipped galvanized) 	LOD 400 Undercut Anchor



N/A

23-13 23 11

Mechanical Fasteners – Torque-controlled Expansion Anchor (Sleeve Type)

Includes: Post-installed anchors per American Concrete Institute 318 building code.

Associated Masterformat Sections: N/A

200	Refer to the model element of the main assembly being connected.	N/A
300	Refer to the model element of the main assembly being connected.	N/A
350	being connected. Element modeling to include: • Anchor Length • Embedment Length • Projection Length • Edge Distance Zone • Spacing Zone • Geometry, base size without threads Required non-graphic information associated with model elements to include: • Anchor materials defined • Anchor type defined • Base material type (steel, concrete, masonry, etc) • Base material strength • Base material condition (New, existing, cracked, uncracked, saturated, etc.) • Finishes, i.e. primed, galvanized, etc. • Hole preparation specification	
		LOD 350 Torque-Controlled Expansion Anchor (Sleeve Type)

400	Element modeling to include fabrication level information:	
	 Anchor Threads Anchor Washers Anchor Nuts Other non-graphic information may be included such	
	 as: Mark identification that correlates with bill of material (i.e., piece mark) Member finish (primer, galvanized, etc.) Fastener finish (i.e., black, zinc electroplated, hot-dipped galvanized) 	
		LOD 400 Torque-Controlled Expansion Anchor (Sleeve Type)

N/A

23-13 23 11

Mechanical Fasteners – Torque-controlled Expansion Anchor (Stud Type)

Includes: Post-installed anchors per American Concrete Institute 318 building code.

Associated Masterformat Sections: N/A

200	Refer to the model element of the main assembly being connected.	N/A
300	Refer to the model element of the main assembly being connected.	N/A
350	Element modeling to include: • Anchor Length • Embedment Length • Projection Length • Edge Distance Zone • Spacing Zone • Geometry, base size without threads Required non-graphic information associated with model elements to include: • Anchor materials defined • Anchor type defined • Base material type (steel, concrete, masonry, etc) • Base material strength • Base material condition (New, existing, cracked, uncracked, saturated, etc.) • Finishes, i.e. primed, galvanized, etc. • Hole preparation specification	LOD 350 Torque-Controlled Expansion Anchor (Stud Type)

400	Element modeling to include fabrication level information:	
	Anchor ThreadsAnchor WashersAnchor Nuts	
	Other non-graphic information may be included such as:	
	 Mark identification that correlates with bill of material (i.e., piece mark) Member finish (primer, galvanized, etc.) Fastener finish (i.e., black, zinc electroplated, hot-dipped galvanized) 	
		LOD 400 Torque-Controlled Expansion Anchor (Stud Type)

N/A

23-13 23 11

Mechanical Fasteners – Drop-in Type Displacement-Controlled Expansion Anchor

Includes: Post-installed anchors per American Concrete Institute 318 building code.

Associated Masterformat Sections: N/A

200	Refer to the model element of the main assembly being connected.	N/A
300	Refer to the model element of the main assembly being connected.	N/A
350	Element modeling to include: • Anchor Length • Embedment Length • Projection Length • Edge Distance Zone • Spacing Zone • Geometry, base size without threads Required non-graphic information associated with model elements to include: • Anchor materials defined • Anchor type defined • Base material type (steel, concrete, masonry, etc) • Base material strength • Base material condition (New, existing, cracked, uncracked, saturated, etc.) • Finishes, i.e. primed, galvanized, etc. • Hole preparation specification	LOD 350 Drop-In Type Displacement-Controlled

400	Element modeling to include fabrication level information:	
	Anchor ThreadsAnchor WashersAnchor Nuts	
	Other non-graphic information may be included such as:	
	 Mark identification that correlates with bill of material (i.e., piece mark) Member finish (primer, galvanized, etc.) Fastener finish (i.e., black, zinc electroplated, hot-dipped galvanized) 	
		LOD 400 Drop-In Type Displacement-Controlled Expansion Anchor

N/A N/A

23-13 31 23-13 31 17

Structural Concrete Products Formwork– Concrete Column

Associated Masterformat Sections: 03-10-00

200	Element modeling to include:	
	Approximate geometry (e.g. panel dimensions or depth).	
		LOD 200 Concrete Column Formwork
300	 Element modeling to include: Formwork materials are defined. These may include, but are not limited to plastic, wood or steel. Material properties are defined. These may include, but are not limited to material finish, type, size, grade, strength, etc. Products manufacturer is defined. 	
		LOD 300 Concrete Column Formwork

350	Element modeling to include:	
	 Insulating faces are defined. Insulating details are defined. These include, but are not limited, too, the type of insulation specified, the temperature change the insulation will cause and the thickness of the insulation within the formwork. Hardware and fastener specification defined (may include Nails, Wood Screws, Bolts, Lag Screws, Ties, Anchors, Hangers, etc.) Shoring connections are defined. Scaffolding connections are defined Liner details are defined. 	LOD 350 Concrete Column Formwork
400	 Element modeling to include: All connections. fasteners, and forms detailed and modeled. Nails, Screws, Anchors, etc. 	LOD 400 Concrete Column Formwork

N/A 23-13 31 17

Formwork- Concrete Slab

Associated Masterformat Sections: 03-10-00

200	 Element modeling to include: Approximate geometry (e.g. formwork dimensions or depth). 	
		LOD 200 Concrete Slab Formwork
300	 Element modeling to include: Formwork materials are defined. These may include, but are not limited to plastic, wood or steel. Material properties are defined. These may include, but are not limited to material finish, type, size, grade, strength, etc. Products manufacturer is defined. 	
		LOD 300 Concrete Slab Formwork

350	 Element modeling to include: Insulating faces are defined. Insulating details are defined. These include, but are not limited, too, the type of insulation specified, the temperature change the insulation will cause and the thickness of the insulation within the formwork. Hardware and fastener specification defined (may include Nails, Wood Screws, Bolts, Lag Screws, Ties, Anchors, Hangers, etc.) Shoring connections are defined. Scaffolding connections are defined Liner details are defined. 	
400	Element modeling to include:	LOD 350 Concrete Slab Formwork
	 All supports and formwork detailed and modeled. Wood supports, metal supports, plates, etc. 	
		LOD 400 Concrete Slab Formwork



Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a <u>Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License</u>.

CIVIL

Highway Bridges Precast Structural I Girder (Concrete)

100		
200	Element modeling to include:	
	 Type of structural concrete system Approximate geometry (e.g. depth) of structural elements 	LOD 200 Highway Bridges Precast Structural I Girder (Concrete)

	-	
300	Element modeling to include:	
	 Specific sizes and locations of main concrete structural members modeled per defined structural grid with correct orientation Concrete defined per spec (strength, air entrainment, aggregate size, etc.) All sloping surfaces included in model element with exception of elements affected by manufacturer selection 	LOD 300 Highway Bridges Precast Structural I Girder (Concrete)
350	Element modeling to include:	
350	 Reinforcing Post-tension profiles and strand locations Reinforcement called out, modeled if required by the BXP, typically only in congested areas Chamfer Pour joints and sequences to help identify reinforcing lap splice locations, scheduling, etc. Expansion Joints Lifting devices Embeds and anchor rods Post-tension profile and strands modeled if required by the BXP Penetrations for items such as MEP Any permanent forming or shoring components 	
		LOD 350 Highway Bridges Precast Structural I Girder (Concrete)

400	Element modeling to include:	
	All reinforcement including post tension elements detailed and modeled	
		LOD 400 Highway Bridges Precast Structural I Girder (Concrete)



Copyright © 2017 by BIMForum. All rights reserved This document is copyrighted under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

Highway Bridge Girder Steel

200	Generic mass of Girder	
		LOD 200 Highway Bridge Girder Steel
300	Element modeling to include 3) Girder Depth 4) Web Plate Length • Flange Plate Width	
		LOD 300 Highway Bridge Girder Steel

350	Element modeling to include: • Stiffeners • Exact sloping of members • Splits between Plate Girders	LOD 350 Highway Bridge Girder Steel
400	Element modeling to include fabrication level information: • Welds • Coping of members • Washers, nuts, etc. • Grating, holes in grating • All assembly elements	LOD 400 Highway Bridge Girder Steel

Railroad Bridges Precast Structural I Girder (Concrete)

100

200	Element modeling to include:	
	 Type of structural concrete system Approximate geometry (e.g. depth) of structural elements 	
		LOD 200 Railroad Bridges Precast Structural I Girder (Concrete)
300	Element modeling to include:	
	 Specific sizes and locations of main concrete structural members modeled per defined structural grid with correct orientation Concrete defined per spec (strength, air entrainment, aggregate size, etc.) All sloping surfaces included in model element with exception of elements affected by manufacturer selection 	
		LOD 300 Railroad Bridges Precast Structural I Girder (Concrete)

350	Element modeling to include:	
	 Reinforcing Post-tension profiles and strand locations Reinforcement called out, modeled if required by the BXP, typically only in congested areas Pour joints and sequences to help identify reinforcing lap splice locations, scheduling, etc. Chamfer Expansion Joints Lifting devices Embeds and anchor rods Post-tension profile and strands modeled if required by the BXP Penetrations for items such as MEP Any permanent forming or shoring components 	LOD 350 Railroad Bridges Precast Structural I Girder
		(Concrete)
400	 Element modeling to include: All reinforcement including post tension elements detailed and modeled Finishes 	
		LOD 400 Railroad Bridges Precast Structural I Girder (Concrete)

Railroad Bridge Girder Steel

200	Generic mass of Girder	
200		LOD 200 Railroad Bridge Girder Steel
300	Element modeling to include: • Girder Depth • Web Plate Length • Flange Plate Width	LOD 300 Railroad Bridge Girder Steel
350	Element modeling to include: • Stiffeners • Exact sloping of members • Splits between Plate Girders	LOD 350 Railroad Bridge Girder Steel

400	Element modeling to include fabrication level information: Welds Coping of members Washers, nuts, etc. Grating, holes in grating All assembly elements	
		LOD 400 Railroad Bridge Girder Steel

